



# WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Bona**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Bona Stone, Tile and Laminate Floor Polish](#)

# Bona Tile & Laminate Polish

## Technical data sheet

**Bona Tile & Laminate Polish** is a ready-to-use waterborne maintenance coating for a large variety of hard surface floors including laminate flooring, vinyl linoleum, unglazed tile (ceramic, quarry), stone and sealed marble. It gives new shine while offering extended protection against wear.

- Durable, reinforced with polyurethane
- Easy and safe to use
- Works with a wide range of surfaces
- Quick drying

### Technical data

Binding agent:	Acrylate/polyurethane
Gloss:	High gloss
Dilution:	Do not dilute
Drying time:	- Touch dry: 30-60 minutes - Recoatable: minimum 2 hours
Application tools:	Bona Applicator Pad
Coverage:	Approx. 50 m <sup>2</sup> /litre
Safety:	The product is not classified as dangerous according to European Directive 1999/45/EC and its amendments.
Cleaning:	Clean tools with water directly after use. Dried material can be removed with acetone.
Shelf life:	2 years from date of production in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Sizes:	1 litre

### Preparations

Remove loose dirt and grit from your floor. Clean floor thoroughly with Bona Tile & Laminate Cleaner and let dry. Do not use over any floor that has been waxed or oiled. Wax and oil residues will prevent proper adhesion of Bona Tile & Laminate Polish to floor. **If uncertain, perform a small test before use.**

Shake bottle thoroughly before use and apply at normal room temperature, 18-25°C.

### Application

1. Pour a wide, wavy line of Tile & Laminate Polish on a small section of the floor.
2. Spread the product over the section using a Bona Applicator Pad.
3. Complete section by smoothing with the applicator pad in the direction of the wood.
4. Continue section by section until the whole floor has been treated.

The floor can be walked on already after 2 hours but avoid heavy traffic and replacement of furniture and rugs the first 12 hours.

### Maintenance



# Bona Tile & Laminate Polish

## Technical data sheet

Clean floor with Bona Tile & Laminate Cleaner and a Bona Cleaning Pad. When the floor is starting to show signs of wear and needs freshening up, clean and apply a new layer of Bona Tile & Laminate Polish. For removal of polish build up use Bona Polish Remover.

For information on maintenance and maintenance products see [www.bona.com/care](http://www.bona.com/care)