



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Bona**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Bona Wood Floor Polish](#)

Bona Wood Floor Polish (matt)

Technical data sheet

Bona Wood Floor Polish is a ready-to-use waterborne maintenance coating for varnished or painted wooden floors. It restores and gives the surface new life while offering extended protection against wear.

- Durable, reinforced with polyurethane
- Easy and safe to use
- Quick drying
- Contains natural wax
- Available in gloss and matt version

Technical data

Binding agent:	Acrylate/polyurethane
Gloss:	High gloss and Matt
Dilution:	Do not dilute
Drying time:	- Touch dry: 30-60 minutes - Recoatable: minimum 2 hours
Application tools:	Bona Applicator Pad
Coverage:	Approx. 50 m ² /litre
Safety:	The product is not classified as dangerous according to European Regulation (EC) 1272/2008 and its amendments.
Cleaning:	Clean tools with water directly after use. Dried material can be removed with acetone.
Shelf life:	1 year from date of production in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Sizes:	1L
Certification:	Greenguard



Preparations

Remove loose dirt and grit from your floor. Clean floor thoroughly with Bona Wood Floor Cleaner and let dry. Do not use over any floor that has been waxed or oiled. Wax and oil residues will prevent proper adhesion of Bona Wood Floor Polish to floor. **If uncertain, perform a small test before use.**

Shake bottle thoroughly before use and apply at normal room temperature, 18-25°C.

Instructions for use

1. Pour a wide, wavy line of Wood Floor Polish on a small section of the floor.
2. Spread the product over the section using a Bona Applicator Pad.
3. Complete section by smoothing with the applicator pad in the direction of the wood.
4. Continue section by section until the whole floor has been treated.



Bona Wood Floor Polish (matt)

Technical data sheet

The floor can be walked on already after 2 hours but avoid heavy traffic and replacement of furniture and rugs the first 12 hours.

Maintenance

Clean floor with Bona Wood Floor Cleaner and a Bona Cleaning Pad. When the floor is starting to show signs of wear and needs freshening up, clean and apply a new layer of Bona Wood Floor Polish. For removal of polish build up use Bona Polish Remover.

For more information, please visit bona.com