



# WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Osmo**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Osmo Intensive Cleaner](#)



## INTENSIVE CLEANER

Highly effective special cleaner, ideal for intensive cleaning!



8019 Clear



### PRODUCT DESCRIPTION

Highly effective, lightly alkaline special cleaner for removing interior and exterior organic and inorganic dirt and stains. Ideal for intensively cleaning oiled and waxed surfaces before the actual surface treatment with Osmo wood finishes.

### RECOMMENDED USE

Osmo Intensive Cleaner is ideal as an alternative to sanding all wooden surfaces treated with oils and waxes, e.g. flooring or furniture, and also suitable for cleaning plastics, stainless steel and other waterproof surfaces.

### INGREDIENTS

Alkaline basic cleaner (according to EC Regulation 648/2004 on detergents): <5% cationic tensides; non-ionic tensides; silicates; complexing agents; NTA and additives.

Detailed declaration of ingredients available upon request.

### TECHNICAL DATA

Specific gravity: 1.01-1.03 g/cm<sup>3</sup>

Odour: faint/mild, after drying odourless

pH value (10g/l): 10.9

### STORAGE

Up to 2 years and longer if container is kept dry and closed tightly.

### SURFACE PREPARATION

Remove loose dirt from the surface with a firm broom or hand broom.

Dilute the concentrate from 1:10 to 1:20 with water. A trial application is absolutely necessary.

### METHOD OF APPLICATION

Apply cleaning solution to the dirty surface, loosen dirt and afterwards wipe away with clear water. For mechanical processing on flooring, we recommend using a single disc machine (e.g. Osmo FloorXcenter) with a brush ring, red or green pad. Remove dirt with Osmo Micro-Mop Plush or a lint-free cotton cloth. After drying, recoat oiled or waxed surfaces with an appropriate Osmo wood finish, e.g. Osmo Polyx<sup>®</sup>-Oil.

### CLEANING OF TOOLS

With water.

### DRYING TIME

Before beginning with surface treatment, allow cleaned surface to dry thoroughly and completely, at least 3-4 hours (normal climatic conditions, 23 °C/50 % rel. humidity).

### COVERAGE

1 litre covers approx. 30-100 m<sup>2</sup> with one coat, depending on the amount of dirt and stains.

### NOTE

Do not use undiluted. Osmo Intensive Cleaner may lead to discolourations or surface changes on unfamiliar substrates. Extractive-rich woods (especially Oak) darken when they come in contact with undiluted Intensive Cleaner. Even when diluted, always carry out a trial application. Avoid allowing the solution to dry. Not suitable for everyday cleaning and maintenance.

Hazardous note for the concentrate

Harmful: Xi: irritant. Irritating to eyes and skin.



## CAUTION

Keep out of the reach of children. Do not inhale steam/aerosol. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and turn to a doctor. Please wear protective clothes, protective gloves and glasses while working with Osmo Intensive Cleaner. If swallowed, seek medical advice immediately and show the container or label. Reacts with acids under heat development. Risk of splashing! Observe the normal safety precautions for handling of chemicals.

Danger



## DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

## COLOUR TONES

8019 Clear

## CAN SIZES

1 L; 5 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 05/15