



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Polyvine**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Polyvine Acrylic Enamel Paint](#)

ACRYLIC ENAMEL

PRODUCT DESCRIPTION

An ultra hard, high quality, cross linked acrylic, sandable coating with a gloss/satin finish.

This coating dries to a gloss coloured film with extremely good sanding properties allowing a very high quality of finish to be obtained.

Polyvine Acrylic Enamel is specially formulated to bond to a wide range of surfaces.
metal surfaces • laminate • timber surfaces • tile • ceramic • glass • plastics

Interior/exterior very hard and durable finish 1-2 hour drying time water resistant stain resistant heat resistant water wash up

For interior and exterior use, in fact, anywhere a traditional solvent based enamel was used, these tough, durable enamels are available in a large range of intermixable colours which can be used on plastic, metal, wood, glass, ceramic, card and porcelain. Safe for children's toys. Suitable for brush or airbrush application.

metallic silver, metallic gold, metallic black, antique bronze, metallic chrome, silver, midnight blue, french blue, baltic blue, sea blue, brown, bright red, scarlet, ferrari red, pink, fire orange, brunswick green, emerald, signal green, lime, purple tan, leather, white, orange, yellow, lemon, oak, ivory, matt white, satin varnish, clear black, matt black.

SURFACE PREPARATION

Ensure the surface to be coated is clean and free from grease, wax or polish

APPLICATION

Apply 2-3 coats.

Dilute 10% with water to prime porous surfaces.

By good quality synthetic brush, recommended, or by airbrush.

Low-pressure spray.

Rollers are not recommended, stippling may occur. Stir well.

If cissing occurs, rub onto affected area with a damp cloth to break the surface tension and re-apply.

CAUTION

Apply to a test area before application

COVERAGE

Approx. 10-20 sq. m per litre. 108-215 sq. ft per US qt.

CLEAN UP

Any equipment used can be cleaned using soap and water before the coating dries. Wipe any excess off surfaces with a damp cloth. Any dried deposits will need a paint stripper to remove them.

PACKAGING

Our enamels come in 20ml, 50ml and 100ml, though not all colours are available in all sizes. Check online at www.polyvine.com

STORAGE

Store in unopened containers in a cool dry place away from direct sunlight.

HEALTH SAFETY AND THE ENVIROMENT

Non-hazardous. Ensure good ventilation. Keep out of reach of children. Contact with eyes-wash immediately with warm water. Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

Date of Issue: January 2019

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • www.polyvine.com • email info@polyvine.co.uk