



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Polyvine**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Polyvine Wood Dye](#)

WOOD DYE

PRODUCT DESCRIPTION

The perfect product to colour and enrich wood. A quick drying, light fast, versatile, water based wood dye with minimum grain raising. Colours can be intermixed to produce the exact shade required. It is suitable for use indoors and outdoors, but must be finished with a suitable coating. Uniquely formulated to avoid the unsightly overlap marks that can be a big problem with some wood dyes.

Formulated to avoid unsightly overlap marks, giving an even lustrous finish. Polyvine Woodcolours are INTERMIXABLE giving a limitless range of possibilities to colour and enrich the wood.

available colours green, blue, black, white, teak, mahogany, walnut, medium oak, antique pine, grey, taupe

PREPARATION

Ensure the surface is clean, dry and free of any previous finishes, wax, oil, grease and dust. Sand thoroughly to a smooth finish and remove the dust. application Stir before use, do not shake. Apply liberally with a brush or clean cotton cloth and wipe off any excess immediately, working with the grain wherever possible. For a lighter shade, the dye may be diluted with water. For a stronger colour apply a second coat after 4 hours. Make sure you have sufficient dye to finish the work. If more than one tin is required, mix the contents together in a clean container to ensure uniform colour. Always test product on a spare or inconspicuous area for compatibility and end result.

protection We recommend protecting

CAUTION

Different woods and woodgrain will alter the appearance of woodcolour. Apply to a test area prior to application.

protection We recommend protecting with a Polyvine water-based varnish after leaving to dry overnight.

COVERAGE

Approx. 10-20 sq. m per litre. 108-215 sq. ft per US qt.

CLEAN UP

Any equipment used can be cleaned using soap and water before the Woodcolour dries. Wipe any excess off surfaces with a damp cloth. Any dried deposits will need a paint stripper to remove them.

PACKAGING

500ml, US pint, plastic containers.

STORAGE

Store in unopened containers in a cool dry place away from direct sunlight.

HEALTH SAFETY AND THE ENVIROMENT

Non-hazardous. Ensure good ventilation. Keep out of reach of children. Contact with eyes-wash immediately with warm water. Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

The information supplied herein is accurate to the best of our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to assess the suitability of the product on a test area before application

Date of issue: January 2019

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • www.polyvine.com • email info@polyvine.co.uk