



# WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Protek**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Protek Royal Interior Paint](#)



# ROYAL EXTERIOR SUPERIOR WOOD FINISH

**LEFT:** Front door painted in Somerset Blue with panelling in China Clay

**CENTER:** UK Garden Buildings summer house treated with Royal Exterior Leafy Herb (bespoke colour) and Parsonage Cream

**RIGHT:** Stable door treated with Clear Wood Preserver then weather-proofed with Royal Exterior Sage Leaf



From the hills of Somerset Protek brings you the Royal range, a high quality decorative wood finish. Inspired by the lush countryside and rich heritage houses nestled within, the colours in the extensive Royal range are classic, contemporary and fit perfectly with modern design. Royal has been specially designed to give a long lasting protective coating with a soft lustre that allows the wood grain to show through.

Royal Exterior Superior Wood Finish is a high-grade water-repelling timber treatment that contains a mould inhibitor to protect the coating. It is perfect for use on all **softwood and hardwood** products such as windows, doors, conservatories, summerhouses, gates, cladding and garden furniture. This hard-wearing coating can be used on horizontal and vertical surfaces. Royal Exterior wood finish is low in odour and with low VOC (volatile organic compounds). It complies to EN71 parts 2 & 3 relating to child toy safety and flammability. The unique formulation is a water-based acrylic and alkyd hybrid that incorporates a polyurethane dispersion based on linseed oil - a renewable resource.

## Suitable For:

**Conservatories ✓**

**Gates ✓**

**Cladding ✓**

**Garden Furniture ✓**

**Summerhouses ✓**

**Windows & Doors ✓**

**COVERAGE: APPROX. 8m<sup>2</sup> PER LITRE**

**AVAILABLE IN 1, 2.5, 5 and 25 LITRE CONTAINERS**

**Royal Interior** is also available in the full Royal Exterior colour range for use on interior wood and joinery including skirting boards, window and door frames, furniture, doors, kitchen units and wood panelling.

A 1 litre tin will cover approximately 8m<sup>2</sup> depending on moisture content and porosity of the timber. It is recommended that 2 - 3 coats be applied. Royal Exterior Wood Finish is a high build formulation so each extra coat increases the colour and sheen. No primer or basecoat required. If applying to bare timber a knotting agent or stain blocking primer should be applied prior to Royal to prevent any possible resin bleed staining the coating.



Protek, Crowne Trading Estate, Shepton Mallet, Somerset, BA4 5QQ  
www.protekwoodstain.co.uk Tel: 01749 344697 Email: info@protekproducts.co.uk