



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Blanchon**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Blanchon Maintenance Oil Spray](#)

Maintenance Oil



Specially designed for the maintenance of all traditional oils



Natural matt finish



Contains oils and waxes of natural origin



Quick drying



Dust-proof



PRODUCT DESCRIPTION

- Blanchon **Maintenance Oil** is the natural complement for the maintenance of all Blanchon traditional oils: Hard Waxoil, Wood Floor Oil, Solid'Oil™ and factory-oiled wood floors.
- Containing raw materials of natural origin, the **Maintenance Oil** is a great regenerator. It penetrates to the core of solid wood, plywood and cork floors for long-lasting protection, whilst preserving the wood's natural appearance and elasticity.

Note: suitable for interior use only.

- **Maintenance Oil** enables quick and easy revival of traditional oiled wood floors and, without polishing, gives a natural and even matt look.
- **Maintenance Oil** has a pleasant, subtle fragrance of natural wax and is easy to apply to all pre-oiled surfaces and commonly used wood species.
- **Maintenance Oil** is available in 3 finishes: natural for light coloured or non stained wood, white for white-oiled wood floors (or light grey), and oak for tropical woods or dark stained oiled wood floors. Natural colour is also available in a spray bottle.

SURFACE PREPARATION

- **Maintenance Oil** is specially intended for parquets and wood floors impregnated with Hard Waxoil, Wood Floor Oil, Solid'Oil and factory-oiled wood floors.
- **Maintenance Oil** should be applied on a clean, dry floor: always remove all traces of dust beforehand (using a brush, vacuum cleaner, etc).
- Ordinary stains and marks can easily be removed with Blanchon Lagoon™ (using a damp cloth or mop, never a soaking wet one).

NB: do not use **Maintenance Oil** until the floor is fully cured, wait at least 2 weeks before first application of **Maintenance Oil**.

- Stains, difficult dirty marks and scratches should be removed with fine abrasive sandpaper. At these places the floor will need reapplication of Hard Waxoil, Wood Floor Oil or Solid'Oil™.

NB: see Appendix* for regular cleaning of waxed/oiled wood floors (on the next page).

Important: for wood that has been stained or coloured with Hard Waxoil, Wood Floor Oil or Solid'Oil™, the shade may change with frequency of use. Floor maintenance should be done regularly and thoroughly to ensure long-lasting protection and decoration.

DIRECTIONS FOR USE

- The **Maintenance Oil** is ready to use. Shake well before use and do not dilute. Stir regularly during use. Do not apply if the temperature is below 12°C. Only use in well ventilated areas. Remove plants and aquariums from the area of contact with the solvent vapours.
- Evenly spread on the **Maintenance Oil** in a fine coat, using a cotton cloth, a microfiber brush or an applicator brush, always in the grain direction of the wood, and avoid laying it on too thickly. Allow to dry.
- You can also spray the **Maintenance Oil** onto the wood floor which is dusted and clean (use a hand-held spray) and wipe it regularly as you go along, with a clean, dry cotton cloth, until you obtain a matt finish. To make application easier, proceed by applying to a small area at a time. The floor can be touched up periodically and in localised places by impregnating it and polishing it directly with a cotton cloth.
- To even out the sheen of your oiled wood floor, you can polish it during application with a polishing machine fitted with a beige or white pad (or a white cotton cloth).
- The frequency of maintenance will depend on levels of use: it is recommended to treat the wood floor regularly at high traffic areas (frequently walked on, chair scrapes etc.).
- More maintenance with **Maintenance Oil** is regular, the easier maintenance becomes.

PROPERLY MAINTAINED WAXED/OILED WOOD FLOORS LOOK BETTER AND BETTER AS TIME GOES BY.

Cleaning of tools

- Clean tools immediately after use with Blanchon Odourless Thinner.
- Rinse cloths, pads and tools with water immediately after use (risk of auto-ignition if textiles and tools are stored impregnated with oil.) Do not throw away cloths and pads without soaking them in water. If a spray is used for application, after each use unscrew the nozzle and spray it with a little water to avoid blockages. Dry tools before storing them.
- Take care to close the container tightly after use.
- Do not dispose of residues in drains.

Blanchon

Maintenance Oil

DRYING TIMES

- Drying time: around 4-6 hours at 20°C.
- Return to use: 12 to 24 hours after application.

COVERAGE

- 25 to 35 m² per litre per coat.

TECHNICAL DATA

USE	Maintenance for parquets and wood floors impregnated with Hard Waxoil, Wood Floor Oil, Solid'Oil™ and factory-oiled wood floors
RESIN TYPES	Resins and waxes of natural origin
AFNOR CLASSIFICATION	Family I, class 2b
DENSITY	0.84 [at 20°C, as per NF T 30020]
FLUIDITY	Around 35 seconds (CA n°4 at 20°C)
REGULATORY INFORMATION	Refer to the relevant Material Safety Data Sheets (also available on www.blanchon.com or www.quickfds.com)
RESISTANCE TO HOUSEHOLD PRODUCTS	Vegetable oil, acetone, 40° alcohol, water, coffee, tea, ink: no adverse effects found [after 20 days' drying, as per NF T 30053]

Appendix 1: EVERYDAY CLEANING OF AN OILED OR HARD WAXOILED FLOOR

- Use a damp mop with Blanchon Natural Soap For Oiled Wood Floors, diluted 250ml for 10 litres of water or Blanchon Lagoon™.
- Work on a small area at a time rinsing the cloth or mop regularly: it should always be well wrung out to avoid getting the wood floor too wet.
- Frequency: from once a week on light-traffic floors to daily cleaning on heavy-traffic floors. Natural Soap For Oiled Wood Floors, which is 100% natural, is ideal for cleaning waxed/oiled wood floors thoroughly and boosting their protection.
- Do not let water lie on an oiled or hard wax oiled floor.

Appendix 2: REFINISHING

- Refinishing small areas: for small areas with specific damage [cigarette burns, impact damage, etc.] rub or scrape to remove the damage and then reapply. One of the great benefits of an oiled or hard wax oiled floor.
- Larger renovation: on a hard wax oiled wood floor that has not been fully maintained will require an overall sanding with a sanding machine fitted with an abrasive pad [grit 120, for example] before applying a coat of undiluted Hard Waxoil, Wood Floor Oil or Solid'Oil™ (brush, paintbrush, short haired roller or spray on method). Polish by hand or with a buffing machine.

Technical Data Sheet issued on the 10.05.2012.

The information provided in this Technical Data Sheet is given in good faith for information purposes only. In no case whatsoever can this information be considered as a guarantee given by us nor engage our responsibility when our products are used. Since we are constantly striving to improve our products, the information given here may be subject to modification without prior notice. This Technical Data Sheet cancels and supersedes all previous versions.



28 rue Charles Martin - BP 105
69192 SAINT-FONS CEDEX - FRANCE
Tél. 04 72 89 06 00 - Fax 04 78 70 07 18
Export Lines: Tel: (0033) 472 89 06 09
Fax: (0033) 472 89 06 02

Blanchon

BLANCHON S.A. - Est. 1832 - A stock company with a board of directors and a supervisory board, with a registered capital of € 4 258 258
390 112 886 RCS LYON - APE 2030 Z - E-mail: info.uk@blanchon.com
Internet : www.blanchon.com