



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Blanchon**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Blanchon Protector](#)

Protects and enhances lacquered wood floors with a gloss or satin finish

Protective film



Revives brightness



Non-slip: tested as per French standard EN 13036-4



Preserves the original look of lacquered wood floors subject to heavy traffic



Eliminates small scratches



Back in service quickly



Protector Satin



PRODUCT DESCRIPTION

- BLANCHON PROTECTOR SATIN combines the hardness of metallised acrylic resins with the flexibility of polyethylene waxes to provide long-term protection and decoration for lacquered wood floors.
- PROTECTOR SATIN forms a protective film that gives a uniform finish to tarnished and worn lacquered wood floors and prolongs the life of the lacquer.
- The protective film prevents the build up of dirt and resists black marks caused by heavy use.
- PROTECTOR SATIN is non-yellowing and does not flake.
- Non-slip.
- PROTECTOR SATIN is a white liquid which becomes totally transparent when dry.

SURFACES

- PROTECTOR SATIN is compatible with all wood floor lacquers* (finished on site or in the factory).
- It is also suitable for use on laminate and plastic flooring: carry out a test on an inconspicuous area before treating the whole surface.

*On pre-varnished wood floors whose wood can have a high moisture content (beech, etc.), carry out a test before applying.

SURFACE PREPARATION

- Before applying, the varnished floor must have dried and hardened for at least 10 days.
- The wood floor must be clean: clean with BLANCH CLEANER LISABRIL™ or deep clean with diluted BLANCHON POLISH.
- REMOVER, then rinse twice with water using a mop or cloth that is damp but not dripping.
- Apply PROTECTOR SATIN to a clean, dry, grease-free surface.
- **IMPORTANT: an excessive amount of water must never be used on wood floors; always use tools that are thoroughly wrung out, not soaking wet.**

DIRECTIONS FOR USE

- Apply 1 or 2 coats of PROTECTOR SATIN with a damp (not soaking) microfibre mop, sponge mop or floor cloth.
- Leave to dry for 1 hour between each coat to allow thorough polymerisation.

Cleaning of tools

- Clean tools with water immediately after use.
- Protecting the environment:
 - Carefully remove excess moisture from the equipment after application; dry thoroughly.
 - Rinse using very little water in a container; allow the water to evaporate.
 - The dry residue may then be disposed of normally in a bin.
 - Seal the containers properly after use.
 - Do not discharge the residue into drains.
 - Dispose of empty containers at a waste recycling centre.

DRYING TIMES

- Dust free time: 15 minutes.
- Before recoating: 1hr under normal conditions.
- Return to use: 1 hr 30.

Blanchon

Protector Satin

COVERAGE

- 50 m² per litre per coat.

MAINTENANCE AND UPKEEP

- ROUTINE CLEANING: vacuum cleaner, broom, wool cloth. Occasionally mop the surface with diluted CLEANER LISABRIL™ using a damp (not soaking wet) mop. Do not use ammonia- or silicone-based products or abrasives.
- PROTECTOR SATIN can be applied over itself: apply a thin coat from time to time to give a perfect finish.

TECHNICAL DATA

USE	Protecting and refinishing of gloss and satin lacquered wood floors and plastic flooring
RESIN TYPE	Metal complex acrylic
AFNOR CLASSIFICATION	Family 1, class 7b
DENSITY	1.027 (at 20°C, as per NFT 30020)
REGULATORY INFORMATION	Refer to the relevant Safety Data Sheets (available on www.blanchon.com or on www.quickfds.com)
pH	8.5
RESISTANCE TO HOUSEHOLD PRODUCTS	PROTECTOR SATIN is sensitive to alkaline detergents. Do not use alkaline cleaning products - for maintenance use CLEANER LISABRIL™
STORAGE	Protect from frost (be especially careful when storing in vehicles)

Technical Data Sheet approved by the Technical Service and issued in July 2018.

Designed, developed and manufactured in France.

The information contained in this Technical Data Sheet is provided in good faith as a guideline only.

Under no circumstances can this information be considered as a guarantee given by us or incur our liability when our products are used.

This Technical Data Sheet cancels and replaces all previous versions.

50 8^{ème} Rue
69800 SAINT-PRIEST - FRANCE
Tél. 04 72 89 06 00 - Fax 04 78 70 07 18
Export Lines: Tel: (0033) 472 89 06 09
Fax: (0033) 472 89 06 02

Blanchon

BLANCHON S.A.S. - Est. 1832 - A stock company with a board of directors and a supervisory board, with a registered capital of 4 258 258
390 112 886 RCS LYON - APE 2030 Z - E-mail: info.uk@blanchon.com - Internet : www.blanchon.com