

The following Technical Datasheet is provided by **Blanchon**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: Blanchon Wood Reactive Stain

White patina



PROPERTIES

The effect of bleached wood

Highlights the grain of wood

Highlights the appearance of the graining

Odourless

Ц

APPLICATION

To be applied on Wood Ageing Agent, Wood Stain or Grey Wood Reactive

Perfect for parquets and large surface areas

For interiors

PRODUCT DESCRIPTION

- Odourless, decorative wood stain White Patina Blanchon washable with water, perfect for achieving the
 effect of bleached wood on hard wood species with a distinct graining (oak, chestnut, etc.).
- For all large surfaces: parquets, floors, stairs, perfectly suited for furniture or wood panelling.
- White Patina bleaches and emphasises the graining by highlighting the wood graining (including non-brushed wood).

SURFACE PREPARATION

- Parquets, floors, stairs should be polished to the «raw» wood (it is not recommended to use coat removers and wax-removing agents), and then smoothened. Make sure that the surface is clean and devoid of all traces of detergents, grease, wax, polish, furniture polish or flax oil (or other specialist oils). Do not use detergents, bleaches or parquet-cleaning agents (see ATTACHMENT*).
- Apply White Patina on the wood previously stained with Wood Ageing Agent, Wood Stain or Grey Wood Reactive.

For the proper wooden surface preparation before application of **White Patina**, be sure to clean it with buffing machine with a white pad (see product Technical Data Sheet).

INSTRUCTIONS FOR USE

- Use only in well ventilated areas. Do not leave the aquariums and potted plants in the stained rooms.
- Apply White Patina on the wood previously stained with Wood Ageing Agent, Wood Stain or Grey Wood Reactive. For the proper surface preparation before application of White Patina, be sure to clean it with buffing machine with a white pad.
- The best results are achieved on surfaces coated with dark or grey wood stains as the contrast with the bleached wood graining is highlighted.
- Apply a thin and even layer using a brush or paint brush, always in the direction of the grain. Do not use a gun.
- After drying, in an interval of 4 to a maximum of 12 h, brush the surface with the buffing machine with a green or black pad until achieving the desired effect.
- Brush the corners and edges manually with the central part of the pad. This method is perfect for small surfaces.
- Very carefully remove the dust before applying the selected finishing layer. It is recommended to use a dust mask, as the product is very likely to become a dust.
- The White Patina preparation can be applied onto surfaces coated with Grey Wood Reactive in order to strengthen the effect of ageing wood and highlight the wood structure.
- For the best end result, it is recommended to use water-based finishing products, which ensure that the wood will retain the brightest colour. The surface should be blocked with Prim'Oil™ Blanchon, then covered with Original Wood™ Environment Blanchon or S.O. Primer. Next, apply Intensiv®, Initial or Blumor SD Blanchon (see sample realisation in the brochure).

Cleaning of tools

- Rinse thoroughly with water immediately after use. Do not reuse used packaging.
- Protecting the environment:
 - Wring out cloths and wipe tools thoroughly after application.
 - Rinse with a little water in a container and allow the water to evaporate.
 - The dry residue can then be discarded in the waste bin.
 - Seal the container properly after use.
 - Dispose of containers at a waste reception centre.
 - Refer to the local authorities for advice on disposal or collection.
 - Do not discharge the residue into drains.



White patina

DRYING AND COATING

Under normal conditions of use: temperature of 20°C, humidity of 65%, adequate ventilation.

- Dust-dry: about 1 hour.
- Drying "coating": 4 hours.
- Within 12 hours of application, be sure to wipe off White Patina with a buffing machine.
- NOTE: When drying, do not leave metal objects (tools) in contact with the stained wood.

COVERAGE

12 m² from 1 L with one coat.

STORAGE

- Protect against frost (use caution when storing in vehicles).
- Close the packaging tightly after completing the work.

TECHNICAL DATA	
INTENDED USE	DECORATIVE WOOD STAIN FOR RESIN WOOD PARQUETS, FLOORS AND STAIRS
AFNOR CLASSIFICATION	Group 1, Class 7B2
VISCOSITY	75 cP (rod 2, speed 100)
ADDITIONAL INFORMATION	Refer to the relevant Safety Data Sheets (available on www.blanchon.com or www.quickfds.com)
COATING	After 4 hours under normal conditions

^{*}ATTACHMENT: PARQUET SURFACE POLISHING

- *ATTACHMENT: PARQUET SURFACE POLISHING
 It is done with polishing machine, edge polishing machine and corner scraper.
 The polishing machine should be used along the direction of the light and, if possible, the orientation of the fibres.
 It should be moved smoothly so that the surface is sanded evenly.
 The first polishing: coarse abrasive wheel (24, 30 or 36) in order to uncover and even the wood.
 The second polishing: Medium abrasive wheels (50 or 60) to smoothen the surface.
 The third polishing: fine-gained abrasive wheels (100 or 120) to provide a beautiful finish.
 Clean and sand the edges of the whole room (with an edge polishing machine and a corner scraper).
 Smoothing the surface with abrasive wheels (100 or 120) to prefectly prepares the surfaces, especially parquets with alternating arrangement: checkerboard, «arrowhead» herringbone, «zig-zae» herrinobone, French herringbone, etc.
- zag» herringbone, French herringbone, etc. Thoroughly vacuum the entire room: parquet surface, skirting boards, window sills, radiators, etc.

Technical Data Sheet validated by the Technical Service and issued on 31.03.2016Devised, prepared and produced in S1.03.2015.

Devised, prepared and produced in France.

The information provided in this Technical Data Sheet is given in good faith for information purposes only.

Under no circumstances can this information be considered as a guarantee given by us nor incur our liability when our products are used.

This Technical Data Sheet cancels and supersedes all previous versions.