



# WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Bona**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Bona Freshen Up](#)

# Bona Freshen Up

## Technical data sheet

Freshen Up is a ready-to-use waterborne maintenance coating for most finished and pre-finished wooden floors in both commercial and domestic areas. It revives a scratched and dull surface giving a newly finished look and continuing protection against wear.

- Specifically designed for finished wooden floors.
- Based on polyurethane = superb protective qualities.
- Contains no waxes.
- Allows for future applications of professional finish.
- Meets EN 14904:2006 and DIN 18032:2 for slip resistance.

### Technical data

Binding agent:	Polyurethane
Dilution:	Do not dilute - the product is ready-to-use
Drying time:	Approx.. 2 hours (20°C/60% RH)
Application tools:	Bona Microfibre Applicator Pad
Coverage:	Ca. 30-50 m <sup>2</sup> /litre
Safety:	Unclassified
Shelf life:	2 years, from date of production, in unopened original container
Storage/Transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Pack size:	3 x 5 litres (44 boxes per pallet) 10 x 1 litre (50 boxes per pallet)


### Preparations

Remove loose dirt and grit from your floor. Clean floor thoroughly with Bona Cleaner. Repeat to ensure that dirt will not be trapped in the coating. Make sure the floor is completely dry before applying Bona Freshen Up. Do not use over any floor that has been waxed or oiled. Wax and oil residues will prevent the proper adhesion of Freshen Up to the floor. **Always test floors for appearance and adhesion in an inconspicuous area before use.**

### Application



1. Rock container back & forth several times before opening. Apply Freshen Up with the Bona Microfiber applicator pad. Prepare the applicator pad by slightly dampening it with water. Apply Freshen Up in a 3-4 cm wide wavy line on the floor. Work on a small section at a time, about 3 m<sup>2</sup>.



2. Spread Freshen Up over entire small section making sure all wood is covered. Freshen Up should be applied at 30-50 m<sup>2</sup> per litre. For best results, apply a thin consistent coat. Keep airborne dust and airflow to a minimum while floor is wet.


Floor Care



# Bona Freshen Up

## Technical data sheet

Floor Care



3. Smooth out Freshen Up, going with the grain of the wood. Continue the process until the entire floor is coated. Allow to dry a minimum of 2 hours before walking on coated floors. If needed, a second coat may be applied after this time. Always coat the entire floor to ensure an even appearance and sheen.

**Note:** Avoid heavy traffic and replacement of furniture and rugs for 24 hours after the final coat. Clean tools with soap and water.

### Maintenance

Wetcleaning of the floor may be resumed after one week. For regular cleaning use Bona Cleaner. Do not use strongly alkaline cleaning agents as they may damage the floor.

In contrast to floors treated with polish, wax or similar material, a floor maintained with Freshen Up can still be overcoated with professional finish. Prior to application of finish, the surface must be treated with the Prep System using screen P150 to remove build up from previous applications of Freshen Up. Complement the screen by going in afterwards with the Bona Scrad System P220 to smooth out scratches. For more overcoating instructions see the product data for Bona Prep at [www.bona.com](http://www.bona.com).

**Bona**<sup>®</sup>