

The following Safety Datasheet is provided by Bona

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: Bona R540

# **SAFETY DATA SHEET**



Bona R540

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

**1.1 Product identifier** 

Product name

: Bona R540

Product description : adhesive Primer

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** 

Not applicable.

Uses advised against Not applicable.

#### 1.3 Details of the supplier of the safety data sheet

Bona AB Box 210 74 SE-200 21 MALMÖ SWEDEN Tel. +46-(0)40-38 55 00

e-mail address of person : Environment@bona.com

#### responsible for this SDS National contact

Bona Limited 8 Thornton Chase, Linford Wood Milton Keynes, MK14 6FD Phone 01908 525150

#### 1.4 Emergency telephone number

Emergency telephone : +44 1235 239670 number

#### **Supplier**

Telephone number	: +46 (0)40 385500
Hours of operation	: 8:00 - 16:00 (CET +1:00)
Information limitations	: Information in English only!

### **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS Acute Tox. 4, H332

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended. See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision : 11/16/2022 Date	ate of previous issue : No previous validation	Version	:1	1/16
--	--	---------	----	------

# **SECTION 2: Hazards identification**

2.2 Label elements		
Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements		
Prevention	1	Wear protective gloves: > 8 hours (breakthrough time): nitrile rubber Wear eye or face protection. Avoid breathing vapour.
Response	:	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF ON SKIN: Gently wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention.
Storage	4	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	Contains isocyanates. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	As from August 24 2023 adequate training is required before industrial or professional use.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.
<b>SECTION 3: Compos</b>	iti	on/information on ingredients

3.2 Mixtures

: Mixture

2/16

<b>SECTION 3: Composition</b>	n/information on i	ngredients		
Product/ingredient name	Identifiers	%	Classification	Туре
4,4'-methylenediphenyl diisocyanate	REACH #: 01-2119457014-47 EC: 202-966-0 CAS: 101-68-8 Index: 615-005-00-9	≥25 - ≤50	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	[1] [2]
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, methyloxirane and 1,2-propanediol	CAS: 67815-87-6	≥10 - ≤25	Resp. Sens. 1, H334 Skin Sens. 1, H317	[1]
o-(p-isocyanatobenzyl)phenyl isocyanate	REACH #: 01-2119480143-45 EC: 227-534-9 CAS: 5873-54-1 Index: 615-005-00-9	≥10 - ≤25	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	[1] [2]
1,2-Propanediol, polymer with 1-isocyanato-2-[ (4-isocyanatophenyl)methyl] benzene, 1,1'.methylenebis [4-isocyanatobenzene], methyloxirane and oxirane	CAS: 72088-97-2	≥10 - ≤25	Resp. Sens. 1, H334 Skin Sens. 1, H317	[1]
MDI, prepolymer	CAS: 9016-87-9	≥10 - ≤25	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 (inhalation) STOT SE 3, H335 STOT RE 2, H373 (inhalation)	[1] [2]
Hydrocarbons, C9-unsaturated, polymerized	REACH #: 01-2119555292-40 CAS: 71302-83-5	≤10	Skin Sens. 1A, H317 Aquatic Chronic 3, H412	[1]
2,2'-methylenediphenyl diisocyanate	EC: 219-799-4 CAS: 2536-05-2 Index: 615-005-00-9	≤3	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 See Section 16 for	[1] [2]
			the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

4.1 Description of first aid measures				
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.			
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. In the event of any complaints or symptoms, avoid further exposure.			
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.			
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.			
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.			

### 4.2 Most important symptoms and effects, both acute and delayed

<u>Over-exposure signs/s</u>	<u>ymptoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing wheezing and breathing difficulties asthma
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
4.3 Indication of any imr	nediate medical attention and special treatment needed
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

5/16

### SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.

#### Examination of lung function should be carried out on a regular basis on persons spraying this mixture.

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitisation problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

information on hygiene measures.

#### 7.3 Specific end use(s)

: Not available.

**Recommendations** Industrial sector specific : Not available. solutions

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
4,4'-methylenediphenyl diisocyanate	EH40/2005 WELs (United Kingdom (UK), 1/2020). [cyanides, except HCN, cyanogen and cyanogen chloride] Absorbed through skin.
	TWA: 5 mg/m³, (as CN) 8 hours. STEL: 0.07 mg/m³, (as -NCO) 15 minutes.
o-(p-isocyanatobenzyl)phenyl isocyanate	EH40/2005 WELs (United Kingdom (UK), 1/2020). [isocyanates,
	all, except methyl isocyanate] Inhalation sensitiser.
	STEL: 0.07 mg/m <sup>3</sup> , (as -NCO) 15 minutes.
	TWA: 0.02 mg/m <sup>3</sup> , (as -NCO) 8 hours.
MDI, prepolymer	EH40/2005 WELs (United Kingdom (UK), 1/2020). [isocyanates,
	all, except methyl isocyanate] Inhalation sensitiser.
	STEL: 0.07 mg/m <sup>3</sup> , (as -NCO) 15 minutes.
	TWA: 0.02 mg/m³, (as -NCO) 8 hours.
2,2'-methylenediphenyl diisocyanate	EH40/2005 WELs (United Kingdom (UK), 1/2020). [isocyanates,
	all, except methyl isocyanate] Inhalation sensitiser.
	STEL: 0.07 mg/m <sup>3</sup> , (as -NCO) 15 minutes.
	TWA: 0.02 mg/m³, (as -NCO) 8 hours.

Date of issue/Date of revision

: 11/16/2022

## **SECTION 8: Exposure controls/personal protection**

No exposure indices known.

Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
4,4'-methylenediphenyl diisocyanate	DNEL	Long term	0.025 mg/	General	Local
		Inhalation	m³	population	
	DNEL	Short term	0.05 mg/m <sup>3</sup>	General	Local
		Inhalation		population	
	DNEL	Long term	0.05 mg/m <sup>3</sup>	Workers	Local
		Inhalation			
	DNEL	Short term	0.1 mg/m³	Workers	Local
		Inhalation			
o-(p-isocyanatobenzyl)phenyl	DNEL	Long term	0.025 mg/	General	Local
isocyanate		Inhalation	m³	population	
	DNEL	Short term	0.05 mg/m <sup>3</sup>		Local
		Inhalation		population	
	DNEL	Long term	0.05 mg/m³	Workers	Local
		Inhalation			
	DNEL	Short term	0.1 mg/m³	Workers	Local
		Inhalation			
2,2'-methylenediphenyl diisocyanate	DNEL	Long term	0.025 mg/	General	Local
		Inhalation	m <sup>3</sup>	population	
	DNEL	Short term	0.05 mg/m <sup>3</sup>		Local
		Inhalation	0.05	population	
	DNEL	Long term	0.05 mg/m <sup>3</sup>	Workers	Local
		Inhalation	0.1 ma ar/ma3	\\/ a #k a #a	
	DNEL	Short term	0.1 mg/m <sup>3</sup>	Workers	Local
		Inhalation			

#### **PNECs**

No PNECs available

8.2 Exposure controls	
Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): nitrile rubber
Date of issue/Date of revision	: 11/16/2022 Date of previous issue : No previous validation Version : 1 7/16

# **SECTION 8: Exposure controls/personal protection**

•	· ·	
Body protection	Personal protective equipment for the body should be selected based on the being performed and the risks involved and should be approved by a special before handling this product.	
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and shou approved by a specialist before handling this product.	
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that mee appropriate standard or certification. Respirators must be used according to respiratory protection program to ensure proper fitting, training, and other im aspects of use.	ba
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legisla In some cases, fume scrubbers, filters or engineering modifications to the pr equipment will be necessary to reduce emissions to acceptable levels.	ation.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

···· ···· ···· ··· ··· ··· ··· ··· ···		
<u>Appearance</u>		
Physical state	: L	_iquid.
Colour	: E	Brown. Clear.
Odour	: /	Aromatic. [Slight]
Odour threshold	: 1	Not applicable.
Melting point/freezing point	: 1	Not available.
Initial boiling point and boiling range	: >	>350°C (>662°F)
Flammability (solid, gas)	: 1	Not applicable.
Upper/lower flammability or explosive limits	: 1	Not applicable.
Flash point	: (	Closed cup: >210°C (>410°F)
Auto-ignition temperature	: >	>400°C (>752°F)
Decomposition temperature	: 1	Not applicable.
рН		Not applicable.
Viscosity	: [	Dynamic: 220 mPa⋅s
Solubility(ies)	1	
Media		Result
cold water		Not soluble
hot water methanol		Not soluble Partially soluble
diethyl ether		Partially soluble
n-octanol		Partially soluble
acetone		Partially soluble
Solubility in water	: 1	Not available.
Partition coefficient: n-octanol/ water	: 1	Not applicable.
Vapour pressure	: 1	Not available.
Relative density	: 1	l.17
Density	: 1	I.17 g/cm³ [20°C (68°F)]
Vapour density	: 1	Not available.
Explosive properties	: 1	Not available.
Oxidising properties	: 1	Not available.
Particle characteristics		

Date of issue/Date of revision

8/16

## **SECTION 9: Physical and chemical properties**

Median particle size

: Not applicable.

# **SECTION 10: Stability and reactivity**

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.	
10.2 Chemical stability	: The product is stable.	
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	: No specific data.	
10.5 Incompatible materials	: No specific data.	
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
4,4'-methylenediphenyl	LD50 Dermal	Rabbit - Male,	>9400 mg/kg	-
diisocyanate		Female		
	LD50 Oral	Rat	9200 mg/kg	-
Isocyanic acid,	LD50 Oral	Rat	>5000 mg/kg	-
polymethylenepolyphenylene				
ester, polymer with				
1,2-ethanediamine,				
methyloxirane and				
1,2-propanediol				
o-(p-isocyanatobenzyl)	LD50 Dermal	Rabbit	>9400 mg/kg	-
phenyl isocyanate				
	LD50 Oral	Rat	>2000 mg/kg	-
1,2-Propanediol, polymer	LD50 Oral	Rat	5000 mg/kg	-
with 1-isocyanato-2-[				
(4-isocyanatophenyl)methyl]				
benzene, 1,1'.methylenebis				
[4-isocyanatobenzene],				
methyloxirane and oxirane				
MDI, prepolymer	LC50 Inhalation Vapour	Rat	490 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	>9400 mg/kg	-
	LD50 Oral	Rat	49 g/kg	-
Hydrocarbons,	LD50 Dermal	Rat	>2000 mg/kg	-
C9-unsaturated,				
polymerized				
	LD50 Oral	Rat	>2000 mg/kg	

**Conclusion/Summary** 

: Not available.

Acute toxicity estimates

# **SECTION 11: Toxicological information**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Bona R540 4,4'-methylenediphenyl diisocyanate o-(p-isocyanatobenzyl)phenyl isocyanate 1,2-Propanediol, polymer with 1-isocyanato-2-[ (4-isocyanatophenyl)methyl]benzene, 1,1'. methylenebis[4-isocyanatobenzene], methyloxirane and oxirane	N/A 9200 N/A 5000	N/A N/A N/A N/A	N/A N/A N/A N/A	98.3 N/A N/A N/A	3.1 1.5 1.5 N/A
MDI, prepolymer 2,2'-methylenediphenyl diisocyanate	49000 N/A	N/A N/A	N/A N/A	11 N/A	N/A 1.5

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
4,4'-methylenediphenyl diisocyanate	Eyes - Moderate irritant	Rabbit	-	100 mg	-
MDI, prepolymer	Eyes - Mild irritant	Rabbit	-	100 mg	-
Conclusion/Summary	: Not available.	·			
Sensitisation					
Conclusion/Summary	: Not available.				
<u>Mutagenicity</u>					
Conclusion/Summary	: Not available.				
Carcinogenicity					
Conclusion/Summary	: Not available.				
Reproductive toxicity					
Conclusion/Summary	: Not available.				
Teratogenicity					
Conclusion/Summary	: Not available.				
Specific target organ toxicit	<u>y (single exposure)</u>				
Product/ing	edient name	Category	Po	ute of	Target organs

Product/ingredient name	Category	Route of exposure	Target organs
4,4'-methylenediphenyl diisocyanate	Category 3	-	Respiratory tract irritation
o-(p-isocyanatobenzyl)phenyl isocyanate	Category 3	-	Respiratory tract irritation
MDI, prepolymer	Category 3	-	Respiratory tract irritation
2,2'-methylenediphenyl diisocyanate	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
4,4'-methylenediphenyl diisocyanate o-(p-isocyanatobenzyl)phenyl isocyanate MDI, prepolymer 2,2'-methylenediphenyl diisocyanate	Category 2 Category 2 Category 2 Category 2	- - inhalation -	- - -

#### Aspiration hazard

Not available.

# Information on likely routes : Not available. of exposure

#### Potential acute health effects

Date of issue/Date of revision

<b>SECTION 11: Toxico</b>	logical information
Eye contact	: Causes serious eye irritation.
Inhalation	: Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the phy	vsical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing wheezing and breathing difficulties asthma
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Delayed and immediate effe	cts as well as chronic effects from short and long-term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects

N ailabl

Not available.	
Conclusion/Summary	: Not available.
General	: May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

#### Other information

: Not available.

# **SECTION 12: Ecological information**

### 12.1 Toxicity

Result	Species	Exposure
Acute EC50 >1640 mg/l	Algae	72 hours
Acute LC50 >1000 mg/l Chronic NOEC >10 mg/l	Fish Daphnia	96 hours 21 days
Acute EC50 >1640 mg/l	Algae	96 hours
	Acute EC50 >1640 mg/l Acute LC50 >1000 mg/l Chronic NOEC >10 mg/l	Acute EC50 >1640 mg/lAlgaeAcute LC50 >1000 mg/lFishChronic NOEC >10 mg/lDaphnia

# **SECTION 12: Ecological information**

SECTION 12. ECOlog			
methyloxirane and			
1,2-propanediol			
	Acute EC50 >1000 mg/l	Daphnia	48 hours
	Acute LC50 >1000 mg/l	Fish	96 hours
o-(p-isocyanatobenzyl)	Acute EC50 >1640 mg/l	Algae	72 hours
phenyl isocyanate	_	-	
	Chronic LC50 >1000 mg/l	Fish	96 hours
	Chronic NOEC >10 mg/l	Daphnia	21 days
MDI, prepolymer	Acute EC50 >1640 mg/l	Algae	72 hours
	Acute EC50 1640 mg/l	Aquatic plants	72 hours
	Acute LC50 >1000 mg/l	Fish	96 hours
	Chronic NOEC >10 mg/l	Daphnia	21 days
Hydrocarbons,	Acute EC50 >100 mg/l	Algae	72 hours
C9-unsaturated, polymerized			
	Acute EC50 54 mg/l	Daphnia	48 hours
	Acute LC50 25.8 mg/l	Fish	96 hours
Conclusion/Summary	: Not available.		

#### **12.2 Persistence and degradability**

Conclusion/Summary : Not available.			
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
4,4'-methylenediphenyl diisocyanate	-	-	Not readily
o-(p-isocyanatobenzyl) phenyl isocyanate	-	-	Not readily
1,2-Propanediol, polymer with 1-isocyanato-2-[ (4-isocyanatophenyl)methyl]	-	-	Not readily
benzene, 1,1'.methylenebis [4-isocyanatobenzene],			
methyloxirane and oxirane MDI, prepolymer	-	-	Not readily

#### **12.3 Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
4,4'-methylenediphenyl diisocyanate	4.51	200	low
o-(p-isocyanatobenzyl) phenyl isocyanate	4.51	200	low
Hydrocarbons, C9-unsaturated, polymerized	3.627	-	low
2,2'-methylenediphenyl diisocyanate	5.22	200	low

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

Date of issue/Date of revision

# SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### **13.1 Waste treatment methods**

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
<u>Waste catalogue</u>	
Waste code	Waste designation
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances

**Special precautions** 

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

	-			
	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture **UK (GB)/REACH** 

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

#### Substances of very high concern

Date of issue/Date of revision

## **SECTION 15: Regulatory information**

None of the components are listed

None of the components a	re listed.
Ozone depleting substance	es
Not listed.	
Prior Informed Consent (PI	<b>C</b> )
Not listed.	
Not listed.	
Persistent Organic Pollutar Not listed.	<u>nts</u>
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: As from August 24 2023 adequate training is required before industrial or professional use.
Seveso Directive	
This product is not controlled	under the Seveso Directive.
EU regulations	Listed
Industrial emissions (integrated pollution prevention and control) - Air	: Listed
Industrial emissions (integrated pollution prevention and control) - Water	: Listed
International regulations	
Chemical Weapon Convention	on List Schedules I, II & III Chemicals
Not listed.	
Montreal Protocol Not listed.	
Stockholm Convention on P	versistent Organic Pollutants
Not listed.	
Rotterdam Convention on P	rior Informed Consent (PIC)
Not listed.	<u>Hor mornied Consent (FIC)</u>
UNECE Aarhus Protocol on	POPs and Heavy Metals
Not listed.	
Inventory list	
Australia	: Not determined.
Canada	: All components are listed or exempted.
China	: Not determined.
Eurasian Economic Union	2
Japan	: Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	: All components are listed or exempted.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
Thailand	: Not determined.
Turker	. Not determined

Turkey

: Not determined.

# **SECTION 15: Regulatory information**

#### United States Viet Nam 15.2 Chemical safety assessment

Not determined.Not determined.

: This product contains substances for which Chemical Safety Assessments are still required.

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative</li> </ul>
-------------------------------	--

#### Procedure used to derive the classification

Classification	Justification
Acute Tox. 4, H332	Calculation method
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Resp. Sens. 1, H334	Calculation method
Skin Sens. 1, H317	Calculation method
Carc. 2, H351	Calculation method
STOT SE 3, H335	Calculation method
STOT RE 2, H373	Calculation method

#### Full text of abbreviated H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### Full text of classifications

Acute Tox. 4 Aquatic Chronic 3 Carc. 2 Eye Irrit. 2 Resp. Sens. 1 Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1 Skin Sens. 1A	ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 RESPIRATORY SENSITISATION - Category 1 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1A
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of printing	: 11/18/2022
Date of issue/ Date of revision	: 11/16/2022
Date of previous issue	e : No previous validation
Version	: 1
Notice to reader	

### **SECTION 16: Other information**

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

BR540000