



**WOOD
FINISHES
DIRECT**



Finish. Finished.

The following Product Datasheet is provided by **Colron**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Colron Refined Beeswax](#)

PRODUCT DATA SHEET

No. 111171

OCTOBER 2005

COLRON REFINED BEESWAX

Colron Refined Beeswax is specially formulated to enrich the colour of fine interior wood and give a sheen finish while enriching the woods natural patina. Colron Refined Beeswax is a traditional paste formulation available in a range of colours to complement any fine interior wood or furniture.

INTRODUCTION

Colron Refined Beeswax nourishes, feeds and protects fine interior wood specially formulated to enrich the colour of wood and give a sheen finish. It is ideally suited for use on wood which may have faded with time or where the current depth of colour is not as rich as required. Colron Refined Beeswax is particularly suitable for fine interior wood or furniture, which requires reviving to replenish the lustre of the finish.

COMPOSITION

An emulsified blend of waxes, containing light fast pigments.

PROPERTIES

Appearance-Smooth Paste.
Colour -Dependant of individual Shade.
Odour-Low inoffensive.
Solubility-Partly miscible with water.
VOC Content-Low (<8%w/v).
Flash Point-<61°C.

FIELDS OF APPLICATION

Colron Refined Beeswax can be applied directly over previously waxed or polished surfaces but for best results old finishes should be removed. Colron Refined Beeswax cannot be used over sealed surfaces such as varnish or paint.

For interior use only.

PREPARATION

Previous coatings such as wax, polish or lacquer should be removed using Colron Wax Remover. Paint or varnish must be removed using Colron Furniture Stripper prior to application.

In both cases the bare wood should be treated with Colron Wood Reviver to feed and nourish the wood.

Ensure all surfaces are clean and dry. Lightly sand and wipe with white spirit.

APPLICATION

Shake well prior to use. If the wax appears solid allow it to reach room temperature before use.

Apply a thin coat onto the surface by rubbing along the direction of the grain. Leave to dry for at least 15 minutes. Buff the surface with a lint free, soft cloth along the wood grain.

Leave for 2 hours before applying a second coat. Further coats will provide a deeper intensity of colour.

CLEAN-UP

Dispose of application cloths safely.

MAINTENANCE

Apply further coats as required as directed above.

IMPORTANT NOTES

Refer to instructions on the pack prior to use.

For best results apply to bare wood.

Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood as they may contain harmful lead. For further advice contact Ronseal Technical Services.

Do not use paste wax over Liquid Wax as this can result in colour removal.

STORAGE

Store upright in a cool, dry, well ventilated area away from heat and sources of ignition.

Ensure container is fully resealed after use.

Always store in ambient conditions away from temperature extremes. Protect from frost. Store above 5°C.

To avoid the risk of spillage, always store and transport in a secure and upright position.

The shelf life of the product in airtight containers will be at least 3 years.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Ensure good ventilation during application and drying.

Avoid contact with the skin and eyes.

Wear suitable gloves.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvents or thinners/white spirit.

Keep out of reach of children.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Flashpoint <61°C

SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

SIZES

Available in a 400ml resealable container.

DISPOSAL

Some local authorities have special facilities for disposal of waste products.

Do not empty product into drains or watercourses.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Colron products are available on request from our Technical Services Department.

Ronseal Ltd. has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd. operates an Environmental Management System that complies with the requirements of BS 7750:1994, certificate No. EMS 35924.

Ronseal Ltd. has achieved Investors in People certification, (certificate number 59586).

©RONSEAL LTD.,

**Thornccliffe Park,
Chapelton,
Sheffield.
S35 2YP**

Tel:

+44 (0114) 240 9469 (Technical Services)

+44 (0114) 246 7171 (Main Switch board)

Fax:

+44 (0114) 245 5629

E. Mail: enquiry@ronseal.co.uk

Website: www.ronseal.co.uk

Ronseal and Colron are registered trademarks of the Sherwin Williams Company.

OCTOBER 2005. ISSUE 1