



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Colron**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Colron Refined Danish Oil](#)

PRODUCT DATA SHEET

COLRON REFINED DANISH OIL

Colron Refined Danish Oil is a blend of resins and natural oils which penetrate the wood to nourish and feed, giving a low sheen lustre, durable, water resistant finish. Colron Refined Danish Oil is easy to maintain and is suitable for exterior and interior applications. Colron Refined Danish Oil is available in a range of colours including a clear.

INTRODUCTION

Colron Refined Danish Oil is a blend of resins and pure natural oils which combine to provide a durable and water resistant finish. The oils penetrate the wood to nourish and feed, whilst providing a low sheen finish. Colron Refined Danish Oil contains alkyd resin, which provides flexibility and durability for exterior applications but can also be used for most interior applications.

COMPOSITION

A blend of resins and pure oils in white spirit.

PROPERTIES

Appearance-Low viscosity liquid.
Colour -Colour varies depending on individual shade.
Odour-Characteristic solvent type.
Solubility-Immiscible with water.
VOC Content-High (25-50%w/v).
Flammable.

FIELDS OF APPLICATION

Colron Refined Danish Oil is suitable for use on previously oiled and bare wood.

PREPARATION

Previous coatings such as wax, polish or lacquer should be removed using Colron Wax Remover. Paint or varnish must be removed using Colron Furniture Stripper prior to application.

Ensure all surfaces are clean and dry. Lightly sand and wipe with white spirit.

APPLICATION

Shake well prior to use. Pour a generous amount of Colron Refined Danish Oil onto a clean, lint free cloth and wipe over the surface to be oiled. Rub the oil well into the grain of the wood. Alternatively, Colron Refined Danish Oil can be applied sparingly using a paint brush. If treating bare wood, apply 3 coats allowing 6 hours drying time between coats.

When the final coat has dried, an improved sheen can be achieved by buffing with a clean, lint free cloth.

DRYING TIME

Recoat after 6 hours.

CLEAN-UP

Cloths and soiled rags may self-ignite without warning. Wash out well in warm soapy water before disposal.

Remove as much product as possible from cloths and brushes prior to cleaning.

MAINTENANCE

Apply further coats as required as directed above.

IMPORTANT NOTES

Refer to instructions on the pack prior to use.

For best results apply to bare wood.

Cloths and soiled rags may self-ignite without warning. Wash out well in warm soapy water before disposal.

Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood as they may contain harmful lead. For further advice contact Ronseal Technical Services.

STORAGE

Store upright in a cool, dry, well ventilated area away from heat and sources of ignition.

Ensure container is fully resealed after use.

Always store in ambient conditions away from temperature extremes. Protect from frost. Store above 5°C.

To avoid the risk of spillage, always store and transport in a secure and upright position.

The shelf life of the product in airtight containers will be at least 3 years.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Flammable.
Flashpoint ~40°C

SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

SIZES

Available in a 500ml resealable container.

DISPOSAL

Some local authorities have special facilities for disposal of waste products.

Do not empty product into drains or watercourses.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Colron products are available on request from our Technical Services Department.

Sherwin-Williams Diversified Brands Ltd operates a quality management system that complies with the requirements of ISO 9000:2008 (Certificate No. FM 01669).

Sherwin-Williams Diversified Brands Ltd operates an Environmental Management System that complies with the requirements of ISO 14001:2004 (Certificate No. EMS 35924).

Sherwin-Williams Diversified Brands Ltd
Thorncliffe Park
Chapeltown
Sheffield
S35 2YP

Tel: +44(0)114 246 7171
Fax: +44(0)114 245 5629

Registered in England 2968830

E. Mail: enquiry@ronseal.co.uk
Website: www.ronseal.co.uk

Ronseal is a Registered Trademark of the Sherwin-Williams Company.