



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Colron**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Colron Refined Liming Wax](#)

PRODUCT DATA SHEET

COLRON REFINED LIMING WAX

Colron Refined Liming Wax is a blend of natural wax ingredients and soft white pigments that give a traditional limed finish to furniture and most interior woodwork. Colron Refined Liming Wax also enriches, feeds and protects the wood.

INTRODUCTION

Colron Refined Liming Wax provides a limed effect to interior wood and furniture. Containing a blend of natural waxes, including beeswax, it feeds and enriches the wood enhancing the natural beauty of the wood grain.

COMPOSITION

A blend of natural waxes, colouring agents, film formers and perfume as an oil in water emulsion.

PROPERTIES

Appearance : An opaque, smooth cream.
Colour : Off-white.
Odour: Floral.
Solubility : Partly miscible with water.
VOV Content: Medium (8% to 24.99% w/v)

FIELDS OF APPLICATION

Colron Refined Liming Wax is suitable for use on any type of wood. Best results are obtained on open grained and darker woods such as oak.

Colron Refined Liming Wax is not recommended for the treatment of floors, tables or seating areas or in areas of high humidity such as kitchens or bathrooms. Not recommended for areas where there is direct contact with water.

PREPARATION

All existing coatings should be removed prior to application. Sand the wood thoroughly, to avoid the inhalation of dust wear a suitable face mask when sanding.

Wipe over with white spirit and allow to dry thoroughly.

Test the finish on a small area before application.

APPLICATION

Stir the product well prior to use. Apply a thick coat of wax using a soft, lint free cloth and finish in the direction of the grain. Do not pay too much attention to obtaining a streak-free finish at this stage as any brush marks will disappear when the wax has been buffed.

Leave for 10 minutes then buff with a soft cloth along the grain of the wood.

Additional coats may be applied to increase the limed effect, allow 1 hour between each coat.

If the wax is left longer than 20 minutes, buffing will require slightly more effort but will result in a glossier finish.

COVERAGE

Approximately 8 m² per tin per coat. Coverage will vary with the absorbency and type of wood. Apply in accordance with the coverage guidelines or performance may be reduced.

CLEAN UP

Dispose of application cloths safely.

MAINTENANCE

The best way of maintaining the finish is to periodically apply additional coats of Colron Refined Liming Wax. Dust with dry cloths as required.

The use of other maintenance products such as aerosol polishes may result in some removal of Colron Refined Liming Wax thereby giving an uneven colouration to the finish.

Any marks or scratches can be easily covered up by further application of the product to the damaged areas.

If water is spilt onto the surface, gently dab with an absorbent dry cloth or tissue; do not rub the wet surface. Allow to dry, and reapply.

Do not use damp cloths to clean areas treated with Colron Refined Liming Wax.

IMPORTANT NOTES

Refer to instructions on the pack prior to use.

Protect from frost.

This product is not recommended for use in areas where it will come into contact with excessive amounts of water.

Always test for colour suitability on an inconspicuous area prior to use.

Certain tropical hardwoods have surface characteristics which may prevent full absorbency.

Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood as they may contain harmful lead. For further advice contact Ronseal Technical Services.

STORAGE

Store upright in a cool, dry, well ventilated area away from heat and sources of ignition.

Ensure container is fully resealed after use.

Always store in ambient conditions away from temperature extremes. Protect from frost. Store above 5°C.

The shelf life of the product in airtight containers will be at least 3 years.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Flammable.

Harmful to aquatic organisms, may cause long term adverse effects on the aquatic environment.

Keep out of reach of children.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of water.

Wear suitable gloves.

If swallowed seek medical advice immediately and show container label.

Use only in well ventilated areas.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Flammable.

Flashpoint 44°C

SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

SIZES

Obtainable in a 400g resealable container.

DISPOSAL

Some local authorities have special facilities for disposal of waste products.

Do not empty product into drains or watercourses.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Ronseal products are available on request from our Technical Services Department.

Ronseal Ltd. has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd. operates an Environmental Management System that complies with the requirements of BS 7750:1994, certificate No. EMS 35924.

Ronseal Ltd. has achieved Investors in People certification, (certificate number 59586).

©RONSEAL LTD.,
Thorncliffe Park,
Chapelton,
Sheffield.
S35 2YP

Tel:
+44 (0114) 240 9469 (Technical Services)
+44 (0114) 246 7171 (Main Switch board)
Fax:
+44 (0114) 245 5629

E. Mail: enquiry@ronseal.co.uk
Website: www.ronseal.co.uk

Ronseal & Colron are registered trademarks of the Sherwin Williams Company.

July 2013. ISSUE 1