



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Colron**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Colron Wood Filler](#)

PRODUCT DATA SHEET

No.11037

JANUARY 2003

COLRON WOOD FILLER

Colron Wood Filler is a one pack wood filler designed to repair minor damage in interior woodwork. It is available in natural colour which resists shrinking and cracking.

INTRODUCTION

Colron Wood Filler is ideal for repairing minor damage or imperfections in wood. The superior quality one pack Wood Filler is available for interior use which when dry forms a hard knock resistant finish. Colron Wood Filler can be nailed, sawn, screwed and planed before finishing with varnish, wax or oil.

COMPOSITION

A water based, acrylic polymer incorporating inert fillers, emulsifiers, viscosity modifiers.

PROPERTIES

Appearance – Cream to light brown smooth paste.
VOC Content – Minimal
Odour - Slightly sweet.

FIELDS OF APPLICATION

Colron Wood Filler is ideal crack and holes in furniture and other wood surfaces. Not suitable for filling the gaps between floor boards.

APPLICATION PROCEDURE

The wood should be clean and dry. Lightly sand in the direction of the grain.

Apply directly to the damaged area using a suitable knife. Work the filler well in. When filling deeper holes, the Wood Filler should be filled in layers of approximately 5mm and allowed to dry between layers. Do not apply in temperatures below 5°C. Always leave the filler proud of the surface to allow for sanding. Smooth over with a wet knife, prior to drying, to ensure an even finish. Sand smooth and wipe with a damp cloth.

DRYING TIME

At 20°C Colron Wood Filler dries in approximately 2 hours. Low temperatures, high humidity and poor ventilation will increase drying times.

CLEANING OF EQUIPMENT

Tools should be washed in water and detergent immediately after use.

Remove as much product as possible from equipment prior to cleaning.

IMPORTANT NOTES

Do not use Colron Wood Filler in temperatures below 5°C or in areas of high humidity.

Not suitable for filling the gaps between floor boards.
Colron Wood Filler may accept oils, waxes or varnishes differently to surrounding wood. Fill and finish a small test area to ensure final result is acceptable.

STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Store upright and carefully reseal partly used containers.
The shelf life of the product in airtight containers is 3 years. Protect from frost. Store above 5°C.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Keep out of reach of children.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of water.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Flash point above 61°C.
Non-flammable product.

SUPPLY

Obtainable from most D.I.Y. outlets and builders' merchants.

SIZES

125ml resealable container.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Ronseal products are available on request from our Technical Services Department.

Ronseal has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd operate an Environmental Management System that complies with the requirements of BS 7750:1994, Certificate No. EMS 35924.

Ronseal Ltd has achieved Investors In People certification (certificate no. 59586).

©RONSEAL LTD.,

Thornclyffe Park
Chapelton
Sheffield
S35 2YP

Tel: +44 (0114) 240 9469

(Technical Services)

+44 (0114) 246 7171 (Main
Switchboard)

Fax: +44 (0114) 245 5629

E. Mail: enquiry@ronseal.co.uk

Website: www.ronseal.co.uk

Ronseal & Colron are registered trademarks of the Sherwin William's Company.

JANUARY, 2003
ISSUE 1

