

The following Technical Datasheet is provided by Crown Trade

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

Crown Trade Clean Extreme Anti Bacterial Scrubbable Matt

TECHNICAL DATA SHEET



CLEAN EXTREME ANTI BACTERIAL SCRUBBABLE MATT

A water based dual purpose solution that is stain resistant and defends against bacteria such as MRSA and E.coli, using independently tested Steritouch® Silver Ion Technology. With 10,000 scrubs durability the superior cleaning capabilities of the formulation do not compromise the integrity or appearance of the paint film. New and aged stains can be easily cleaned away, returning walls to an "as new" condition – reducing the need for costly redecoration. Independently tested to ISO 11998 class 1 scrub rating for guaranteed results.

AVAILABILITY		
Colour Range	Refer to current Crown Trade Literature	
Packaging	5L	
PROPERTIES		
Suitable Surfaces	Internal Walls and Ceilings	
Drying Time @20*C/65%RH	Under normal drying conditions touch dry in 1-2 hours and recoat after 4 hours. Allow for adequate ventilation during the drying period	
Finish	Matt	
Composition	Pigment: Titanium dioxide, coloured pigments and extenders	
	Binder: Acrylic polymer	
	Solvent: Water	
Spreading Rate	Up to 14m² per litre on smooth surfaces	
Wet Film Thickness	70 micrometres at 14m² per litre	
Dry Film Thickness	25 micrometres at 14m² per litre.	
Volume Solids	35% White. Other colours will vary.	
Flash Point	Not applicable	
VOC Content	EU limit value for this product (cat.A/a): 30 g/l (2010). This product contains max. 29 g/l VOC.	
Limitations	For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.	
PREPARATION		
New Surfaces	All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Porous surfaces should be coated with a 'mist' coat of Crown Trade Clean Extreme Anti-Bacterial Scrubbable Matt diluted with 40% clean water by volume. Where clean water is not available, apply one coat of Crown Trade Covermatt Drywall Primer. Any areas of surface filling after priming should be touched in with the priming or mist coat diluted as for main areas. Powdery surfaces should be primed with one coat of Sandtex Trade Water Based Stabilising Solution. Polished or dense surfaces should be primed with Crown Trade PX3 Primer or where a water-based alternative is required Crown Trade PX4 Primer.	
Previously Decorated Surfaces	All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied e.g. dirt, grease etc. Remove all loose, failing or suspect paint. Feather edges of sound paint. Organic growth must be treated with Sandtex Trade Fungicidal Solution and removed. Fill any fixing holes, cracks and shallow surface defects with Sandtex Ready Mixed Filler . Patch prime bare, filled and powdery areas as for new surfaces above. Wash remaining sound paint with hot water and liquid detergent solution to remove any contaminants, frequently changing the water. Any glossy or eggshell surfaces should be wet abraded to provide a key. Rinse with clean water to remove all residues. Allow to dry. If after cleaning any areas are still contaminated with substances likely to cause staining and / or bleeding, patch prime with one coat of Crown Trade PX4 Primer .	



TECHNICAL DATA SHEET



COATING SYSTEM	Apply two coats as required. Certain colours may require additional coats to give complete
	obliteration.
APPLICATION	Stir well before and during use. Apply using good quality tools – synthetic brush or medium pile roller. For airless spray dilution may be required. For further information follow the spray manufacturer's guidelines. Always intermix (box) packs for colour consistency. Please check for colour accuracy prior to application. Crown Paints is not liable for decorating costs caused as a result of an incorrect colour being applied.
CLEANING	Return surplus material to container. Wash tools & equipment with clean water or a warm
	soapy solution & rinse immediately after use.
STORAGE	Store upright and secure. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not store below 5°C or above 40°C.
MAINTENANCE INFORMATION	Between maintenance redecoration, surfaces may be washed with a warm water and liquid
	detergent solution to remove surface dirt.
	Note: The Crown Trade Anti-Bacterial range of paints has been developed to assist you in
	your fight against bacteria. They are <u>not</u> a replacement to normal hygiene and cleaning
	regimes.
	A small residue of colour may be wiped away when the painted surface is first cleaned.
	This is entirely normal and in no way compromises the integrity or finished appearance of
	the paint film. Marks on the painted surface can be wiped away with a damp cloth. The
	product will take 1 week to become fully cured and scrubbable.
HEALTH AND SAFETY	Please refer to the Safety, Health and Environmental Information on the container. Take
	special precautions during the surface preparation of pre 1960's painted surfaces as they
	may contain harmful lead. For further information contact the Crown Trade Customer
	Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal
	particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other
	Crown Paints products are freely available from the place of purchase or the address below.
	Do not empty into drains, watercourses or access routes to septic tanks.
GENERAL INFORMATION	Apply all products in accordance with BS 6150: Code of practice for painting of buildings
	and BS 8000: Part 12: Code of practice for decorative wallcoverings and painting.
	Every care is taken to ensure that all information provided on this Technical Data Sheet is
	accurate. Crown Paints is unable to guarantee results as it has no control over the
	conditions under which its products are applied.
	Before using this product please ensure you have the latest information. For help or more
	information contact the Crown Trade Customer Relations Team on:
	Tel: 0330 0240297
	Fax: 0330 0240278
	e-mail: info@crowntrade.co.uk
	website: www.crowntrade.co.uk
	This information is correct at date of issue November 2021
	1

