



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Earthborn**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Earthborn Multi Purpose Primer](#)

Earthborn Multi Purpose Primer provides a perfect base coat to interior wood, melamine and MDF surfaces. Once primed the surface can be over painted with any of our Earthborn interior paints. It is a low odour, water based formulation so is ideal for updating any woodwork, cupboards and furniture around the home.

1. Coverage

Up to 12m² per litre

2. Colour

White (matt)

3. Drying Time

Touch dry in approximately 30 minutes, a second coat may be applied after 4 hours. Allow longer in cool or damp conditions.

4. Preparation

Do not apply at temperatures below 10°C. This product is not suitable for use on kitchen worktops or flooring. All surfaces must be clean, dry and free from grease, dust, wax or other contamination. Remove any fungal growth or mould and treat with a fungicidal wash. Melamine and bare wood surfaces can be directly primed. Previously painted wood surfaces should be lightly sanded before application.

5. Application:

Stir well before use. Apply liberally and evenly with a good quality synthetic brush or foam roller. Allow primer to harden for 2-3 days before applying a top coat of paint.

6. Tools

Synthetic brush or foam roller.

7. Cleaning

Remove as much product as possible from application equipment before cleaning. Clean all your decorating equipment immediately after use with warm soapy water and rinse thoroughly.

8. Storage

Keep containers tightly sealed and store in a cool but frost-free place.

9. Ingredients

Water, acrylic binder, titanium dioxide, chalk, dolomite, coalescent, polyurethane thickener, inhibitor, amine, defoaming agent, synthetic preservative.

10. Safety

Please refer to Material Safety Data Sheet for further information.

11. Disposal

Dispose of any surplus product safely and in accordance with local authority disposal guidelines.

12. Low VOC content

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (Cat A/d): 130g/L (2010). This product contain max 0.5g/L VOC.

The user is recommended to test the product on the intended surface to ensure its suitability