



WOOD FINISHES DIRECT

The following Safety Datasheet is provided by **Fiddes**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Fiddes Clear Glaze](#)



SAFETY DATA SHEET

Page 1 of 3

Clear Glaze

Revision 15
Revision date 3-Nov-2010

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name Clear Glaze
Company Fiddes & Son Ltd
Florence Works, Brindley Road, Cardiff, South Glamorgan, CF11 8TX
info@fiddes.co.uk
www.fiddes.co.uk
Telephone +44 (0)29 2034 0323
Fax +44 (0)29 2034 3235

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
POLYURETHANE RESIN	30-40%			Xn;R65
Dearomatised White Spirit	50-60%	64742-48-9	265-150-3	Xn; R65 R10-66

3. HAZARDS IDENTIFICATION

Main hazards Flammable Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.
Other hazards In use, may form flammable/explosive vapour-air mixture.

4. FIRST AID MEASURES

Skin contact Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.
Inhalation Move the exposed person to fresh air. Seek medical attention.
Ingestion DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water. Seek medical attention.
General information If you feel unwell, seek medical advice (show the label where possible). Keep the affected person warm and at rest. Remove contaminated clothing. Wash all contaminated clothing before reuse.

5. FIRE FIGHTING MEASURES

Extinguishing media Use extinguishing media appropriate to the surrounding fire conditions.
Do NOT use ... Water jet.
Protective equipment Wear: Self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Ensure adequate ventilation of the working area. Keep personnel away from spill. Evacuate personnel to a safe area. Eliminate all sources of ignition.
Environmental precautions Do not allow product to enter drains.
Clean up methods Clean spillage area thoroughly with plenty of water. Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal.

Print date 3-Nov-2010

Clear Glaze

Revision 15
Revision date 3-Nov-2010

7. HANDLING AND STORAGE

Handling	Wear suitable protective equipment. Do not breathe gas/fumes/vapour/spray. Use in a well ventilated area. Vapours are heavier than air. Avoid contact with eyes and skin.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures	Ensure adequate ventilation of the working area.
Respiratory protection	Wear: Suitable respiratory equipment. Self-contained breathing apparatus.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	Approved safety goggles. Avoid contact with eyes.
Protective equipment	Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing. Apron (Plastic or rubber) Rubber boots.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	Amber.
Odour	Characteristic.
Flash point	42°C
Water solubility	Soluble in alcohol & ether. Immiscible in water.
Benzene Content	0
VOC (Volatile organic compounds)	523 g/l

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to avoid	Heat, sparks and open flames.
Materials to avoid	Oxidising agents. Acids.
Hazardous decomposition products	Carbon oxides. Nitrogen oxides.

11. TOXICOLOGICAL INFORMATION

Acute toxicity	Headache, nausea and vomiting. In severe cases, may cause loss of consciousness. Harmful if absorbed through the skin.
Corrosivity	May cause irritation to skin.
Repeated or prolonged exposure	Prolonged or repeated exposure may cause irritation to skin and mucous membranes. Repeated or prolonged exposure may cause dermatitis.

12. ECOLOGICAL INFORMATION

Ecotoxicity	No data is available on this product.
--------------------	---------------------------------------

13. DISPOSAL CONSIDERATIONS

General information	Can be incinerated if in compliance with local and national regulations. Dispose of in compliance with all local and national regulations.
Disposal of packaging	Empty containers can be sent for disposal or recycling.

Clear Glaze

Revision 15
Revision date 3-Nov-2010

14. TRANSPORT INFORMATION

ADR/RID

UN 1263	Packing group III
Class 3	Hazard ID 33
Proper Shipping Name	


IMDG

UN 1263	Packing group III
Class 3	Marine pollutant .
EmS Code F-E S-E	

IATA

UN 1263	Packing group III
Class 3	Subsidiary risk -
Packing Instruction 310 (Cargo)	Maximum quantity 220 L
Packing Instruction 309 (Passenger)	Maximum quantity 60 L

15. REGULATORY INFORMATION

Labelling	The product is classified in accordance with 67/548/EEC.
Symbols	Xn - Harmful 
Risk phrases	R10 - Flammable. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking.
Safety phrases	S16 - Keep away from sources of ignition - No smoking. S23 - Do not breathe gas/fumes/vapour/spray. S25 - Avoid contact with eyes. S1/2 - Keep locked up and out of the reach of children. S13 - Keep away from food, drink and animal feedingstuffs. S46 - If swallowed, seek medical advice immediately and show this container or label. S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

16. OTHER INFORMATION

Text of risk phrases in Section 2	R10 - Flammable. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking.
Revision	This document differs from the previous version in the following areas: 9 - description. 9 - water solubility.
Product Subcategory	Interior/exterior trim varnishes and woodstains, including opaque woodstains. 500 g/l
Maximum content of VOC	523 g/l