




WOOD FINISHES DIRECT

The following Safety Datasheet is provided by **Fiddes**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Fiddes Door Oil](#)



SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/4

Fiddes Door Oil

Revision 31

Revision date 2011-03-24

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Fiddes Door Oil
--------------	-----------------

1.3. Details of the supplier of the safety data sheet


Company	Fiddes & Son Ltd
Address	Florence Works, Brindley Road, Cardiff, South Glamorgan, CF11 8TX
Web	www.fiddes.co.uk
Telephone	+44 (0)29 2034 0323
Fax	+44 (0)29 2034 3235
Email	info@fiddes.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xn; R65 R10-66 Symbols: Xn: Harmful.
Main hazards	Flammable. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Symbols	The product is classified in accordance with 67/548/EEC. Xn: Harmful. 
Risk phrases	R10 - Flammable. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking.
Safety phrases	S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

2.3. Other hazards

Other hazards	The product is classified in accordance with 67/548/EEC.
---------------	--

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Dearomatised White Spirit		64742-48-9	265-150-3		50 - 60%	Xn; R65 R10-66

Fiddes Door Oil

Revision 31

Revision date 2011-03-24

Further information

ADDITIONAL INFORMATION	The product does not require a hazard warning label in accordance with EC Directives.
-------------------------------	---

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Seek medical attention.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water. Seek medical attention.

General information

	If you feel unwell, seek medical advice (show the label where possible). Keep the affected person warm and at rest. Remove contaminated clothing. Wash all contaminated clothing before reuse.
--	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions. Do NOT use .. Water jet.
--	---

5.3. Advice for firefighters

	Wear:.. Self-contained breathing apparatus.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Keep personnel away from spill. Evacuate personnel to a safe area. Eliminate all sources of ignition.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains.
--	---------------------------------------

6.3. Methods and material for containment and cleaning up

	Clean spillage area thoroughly with plenty of water. Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal.
--	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Wear suitable protective equipment. Do not breathe gas/fumes/vapour/spray. Use in a well ventilated area. Vapours are heavier than air. Avoid contact with eyes and skin.
--	---

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

SECTION 8: Exposure controls/personal protection

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing. Apron (Plastic or rubber). Rubber boots.
Eye / face protection	Approved safety goggles. Avoid contact with eyes.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear:.. Suitable respiratory equipment. Self-contained breathing apparatus.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Fiddes Door Oil

Revision 31

Revision date 2011-03-24

9.1. Information on basic physical and chemical properties

State	Liquid
Colour	Amber
Odour	Mild
Flash point	43

Water solubility

	Insoluble.
--	------------

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents. Acids.
--	--------------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

10.6. Hazardous decomposition products

	Carbon oxides. Nitrogen oxides.
--	---------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	Headache, nausea and vomiting. In severe cases, may cause loss of consciousness. Harmful if absorbed through the skin.
Skin corrosion/irritation	May cause irritation to skin.
Repeated or prolonged exposure	Prolonged or repeated exposure may cause irritation to skin and mucous membranes. Repeated or prolonged exposure may cause dermatitis.

SECTION 12: Ecological information

12.1. Toxicity

	No data is available on this product.
--	---------------------------------------

SECTION 13: Disposal considerations

General information


	Can be incinerated if in compliance with local and national regulations. Dispose of in compliance with all local and national regulations.
--	--

Disposal of packaging

	Empty containers can be sent for disposal or recycling.
--	---

SECTION 14: Transport information

Hazard pictograms

	
--	---

14.1. UN number

	UN1263
--	--------

14.2. UN proper shipping name

	PAINT RELATED MATERIAL
--	------------------------

14.3. Transport hazard class(es)

Fiddes Door Oil

Revision 31

Revision date 2011-03-24

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group	III
---------------	-----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-E
----------	---------

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 14 - ADR/RID.
Text of risk phrases in Section 3	R10 - Flammable R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking.
Product Subcategory	Interior/exterior trim varnishes and woodstains, including opaque woodstains - 400 g/l.

General information

	S1/2 - Keep locked up and out of the reach of children. S13 - Keep away from food, drink and animal feedingstuffs. S7/9 - Keep container tightly closed and in a well-ventilated place. S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S37/39 - Wear suitable gloves and eye/face protection.
--	--

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. The product is classified in accordance with 67/548/EEC.
--	---