



**WOOD
FINISHES
DIRECT**



Finish. Finished.

The following Safety Datasheet is provided by **Fiddes**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Fiddes Supreme Wax Polish](#)



SAFETY DATA SHEET

Page 1 of 4

Supreme Wax

Revision 0
Revision date 11-May-2010

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name Supreme Wax
Company Fiddes & Son Ltd
Florence Works, Brindley Road, Cardiff, South Glamorgan, CF11 8TX
info@fiddes.co.uk
www.fiddes.co.uk
Telephone +44 (0)29 2034 0323
Fax +44 (0)29 2034 3235

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Naphtha (petroleum), hydrotreated light	40 - 50%	64742 49-0		N;R51/53 Xn;R65
n-Hexane	10 - 20%	110-54-3	203-777-6	F; R11 Repr Cat 3; R62 Xn; R65-48/20 Xi; R38 R67 N; R51/53
Cyclohexane	1 - 10%	110-82-7	203-806-2	F; R11 Xn; R65 Xi; R38 R67 N; R50/53
Methylcyclohexane	10 - 20%	108-87-2	203-624-3	F; R11 Xn; R65 Xi; R38 R67 N; R51/53

3. HAZARDS IDENTIFICATION

Main hazards Highly flammable. Irritating to skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Possible risk of impaired fertility. Harmful: may cause lung damage if swallowed.

4. FIRST AID MEASURES

Skin contact Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.
Inhalation Move the exposed person to fresh air. Seek medical attention.
Ingestion DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water. Seek medical attention.
General information If you feel unwell, seek medical advice (show the label where possible). Keep the affected person warm and at rest. Remove contaminated clothing. Wash all contaminated clothing before reuse.

5. FIRE FIGHTING MEASURES

Extinguishing media Use extinguishing media appropriate to the surrounding fire conditions.
Fire hazards Burning produces irritating, toxic and obnoxious fumes.
Protective equipment Wear: Self-contained breathing apparatus.

Print date 14-May-2010

Supreme Wax

Revision 0
Revision date 11-May-2010

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Avoid raising dust. Ensure adequate ventilation of the working area. Keep personnel away from spill. Evacuate personnel to a safe area.
Environmental precautions	Do not allow product to enter drains.
Clean up methods	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling	Appropriate local exhaust ventilation is required. Wear suitable protective equipment.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

n-Hexane	WEL 8-hr limit ppm: 20 WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: 72 WEL 15 min limit mg/m3: -
Cyclohexane	WEL 8-hr limit ppm: 100 WEL 15 min limit ppm: 300	WEL 8-hr limit mg/m3: 350 WEL 15 min limit mg/m3: 1050

Engineering measures	Ensure adequate ventilation of the working area.
Respiratory protection	Wear: Suitable respiratory equipment. Suitable half mask respirator with filter P3 (EN 143)
Hand protection	Chemical resistant gloves (PVC)
Eye protection	Approved safety goggles.
Protective equipment	Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Solid.
Odour	Characteristic.
Flash point	16°C
Water solubility	insoluble in water.

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to avoid	Heat, sparks and open flames.
Materials to avoid	Combustible materials. Oxidising agents.
Hazardous decomposition products	Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Acute toxicity	Harmful if swallowed.
Corrosivity	May cause irritation to skin.
Repeated or prolonged exposure	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.

12. ECOLOGICAL INFORMATION

Ecotoxicity	No data is available on this product.
--------------------	---------------------------------------

Supreme Wax

Revision 0
Revision date 11-May-2010

13. DISPOSAL CONSIDERATIONS

General information Can be incinerated if in compliance with local and national regulations. Dispose of in compliance with all local and national regulations.

14. TRANSPORT INFORMATION

ADR/RID

UN 1263	Packing group II
Class 3	Hazard ID 33
Proper Shipping Name PAINT .	

IMDG

UN 1263	Packing group II
Class 3	Marine pollutant .
EmS Code F-E S-E	

IATA

UN 1263	Packing group II
Class 3	Subsidiary risk -
Packing Instruction 307 (Cargo)	Maximum quantity 60 L
Packing Instruction 305 (Passenger)	Maximum quantity 5 L

15. REGULATORY INFORMATION

Labelling The product is classified in accordance with 67/548/EEC.

Symbols F - Highly flammable; Xn - Harmful; N - Dangerous for the environment



Risk phrases

R11 - Highly flammable.
R38 - Irritating to skin.
R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62 - Possible risk of impaired fertility.
R65 - Harmful: may cause lung damage if swallowed.

Safety phrases

S1/2 - Keep locked up and out of the reach of children.
S13 - Keep away from food, drink and animal feedingstuffs.
S23 - Do not breathe gas/fumes/vapour/spray.
S25 - Avoid contact with eyes.
S16 - Keep away from sources of ignition - No smoking.
S29 - Do not empty into drains.
S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Supreme Wax

Revision 0
Revision date 11-May-2010

16. OTHER INFORMATION

Text of risk phrases in Section 2	R11 - Highly flammable. R38 - Irritating to skin. R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R62 - Possible risk of impaired fertility. R65 - Harmful: may cause lung damage if swallowed. R67 - Vapours may cause drowsiness and dizziness.
Revision	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.