



WOOD FINISHES DIRECT

The following Safety Datasheet is provided by **Fiddes**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Fiddes Wood Filler Gel](#)



SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

Filler Gel

Revision 14

Revision date 2012-08-17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Filler Gel

1.3. Details of the supplier of the safety data sheet

Company Fiddes & Son Ltd
Address Florence Works, Brindley Road, Cardiff, South Glamorgan, CF11 8TX
Web www.fiddes.co.uk
Telephone +44 (0)29 2034 0323
Fax +44 (0)29 2034 3235
Email info@fiddes.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC
Xn; R48/20-63-65 Xi; R36/38 R66-67
Symbols: Xn: Harmful.

Main hazards
Flammable. Harmful by inhalation and in contact with skin. Irritating to eyes and skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

2.2. Label elements

Symbols
The product is classified in accordance with 67/548/EEC.
Xn: Harmful.



Risk phrases
R10 - Flammable.
R20/21 - Harmful by inhalation and in contact with skin.
R36/38 - Irritating to eyes and skin.
R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63 - Possible risk of harm to the unborn child.
R65 - Harmful: may cause lung damage if swallowed.
R66 - Repeated exposure may cause skin dryness or cracking.
R67 - Vapours may cause drowsiness and dizziness.

Safety phrases
S36/37 - Wear suitable protective clothing and gloves.
S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

2.3. Other hazards

Other hazards
In use, may form flammable/explosive vapour-air mixture.

SECTION 3: Composition/information on ingredients

Filler Gel

Revision 14
Revision date 2012-08-17

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Ethyl acetate	607-022-00-5	141-78-6	205-500-4			F; R11 Xi; R36 R66 R67
Acetone	606-001-00-8	67-64-1	200-662-2			F; R11 Xi; R36 R66 R67
Toluene	601-021-00-3	108-88-3	203-625-9			F; R11 Repr. Cat. 3; R63 Xn; R48/20-65 Xi; R38 R67
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7			F; R11 Xi; R36 R67

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Seek medical attention.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water. Seek medical attention.

General information

	If you feel unwell, seek medical advice (show the label where possible). Keep the affected person warm and at rest. Remove contaminated clothing. Wash all contaminated clothing before reuse.
--	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions. Do NOT use .. Water jet.
--	---

5.3. Advice for firefighters

	Wear: Self-contained breathing apparatus.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Keep personnel away from spill. Evacuate personnel to a safe area. Eliminate all sources of ignition.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains.
--	---------------------------------------

6.3. Methods and material for containment and cleaning up

	Clean spillage area thoroughly with plenty of water. Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal.
--	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Wear suitable protective equipment. Do not breathe gas/fumes/vapour/spray. Use in a well ventilated area. Vapours are heavier than air. Avoid contact with eyes and skin.
--	---

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Filler Gel

Revision 14

Revision date 2012-08-17

8.1.1. Exposure Limit Values

Acetone	WEL 8-hr limit ppm: 500	WEL 8-hr limit mg/m3: 1210
	WEL 15 min limit ppm: 1500	WEL 15 min limit mg/m3: 3620
Ethyl acetate	WEL 8-hr limit ppm: 200	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: 400	WEL 15 min limit mg/m3: -
Isopropanol (Propan-2-ol)	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m3: 999
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m3: 1250
Toluene	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 191
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 384

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing. Apron (Plastic or rubber). Rubber boots.
Eye / face protection	Approved safety goggles. Avoid contact with eyes.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear: Suitable respiratory equipment. Self-contained breathing apparatus.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State	Gel
Colour	Clear
Odour	Characteristic

Description

	Liquid.
--	---------

Water solubility

	Slightly soluble in water. Soluble in alcohol & ether. Slightly soluble in water.
--	---

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents. Acids.
--	--------------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

10.6. Hazardous decomposition products

	Carbon oxides. Nitrogen oxides.
--	---------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	Headache, nausea and vomiting. In severe cases, may cause loss of consciousness. Harmful if absorbed through the skin.
Skin corrosion/irritation	May cause irritation to skin.
Repeated or prolonged exposure	Prolonged or repeated exposure may cause irritation to skin and mucous membranes. Repeated or prolonged exposure may cause dermatitis.

SECTION 12: Ecological information

12.1. Toxicity

Filler Gel

Revision 14

Revision date 2012-08-17

12.1. Toxicity

	No data is available on this product.
--	---------------------------------------

SECTION 13: Disposal considerations

General information

	Can be incinerated if in compliance with local and national regulations. Dispose of in compliance with all local and national regulations.
--	--

Disposal of packaging

	Empty containers can be sent for disposal or recycling.
--	---

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

	UN1263
--	--------

14.2. UN proper shipping name

	PAINT RELATED MATERIAL
--	------------------------

14.3. Transport hazard class(es)

ADR/RID	3
---------	---

Subsidiary risk	-
-----------------	---

IMDG	3
------	---

Subsidiary risk	-
-----------------	---

IATA	3
------	---

Subsidiary risk	-
-----------------	---

14.4. Packing group

Packing group	II
---------------	----

14.5. Environmental hazards

Environmental hazards	No
-----------------------	----

Marine pollutant	No
------------------	----

ADR/RID

Hazard ID	33
-----------	----

Tunnel Category	(D/E)
-----------------	-------

IMDG

EmS Code	F-E S-E
----------	---------

IATA

Packing Instruction (Cargo)	364
-----------------------------	-----

Maximum quantity	60 L
------------------	------

Packing Instruction (Passenger)	353
---------------------------------	-----

Maximum quantity	5 L
------------------	-----

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations

	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of
--	--

Filler Gel

Revision 14

Revision date 2012-08-17

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

SECTION 16: Other information

Other information

Revision	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This document differs from the previous version in the following areas:</p> <ul style="list-style-type: none"> 15 - Labelling. 15 - Symbols.
Text of risk phrases in Section 3	<ul style="list-style-type: none"> R11 - Highly flammable. R36 - Irritating to eyes. R38 - Irritating to skin. R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation. R63 - Possible risk of harm to the unborn child. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.