



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Morrells**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Holzol Anti Slip Floor Oil](#)

Product Data Sheet



holzöl Antislip Floor-Oil

Code	Description
7AS/00/10	holzöl Antislip Floor-Oil 10% Sheen
Technical Data	holzöl Antislip Floor-Oil is a natural oil / resins formulation offering a tough, antislip finish for floors.
Properties	holzöl Antislip Floor-Oil is a natural oil / resins blend designed to achieve a tough antislip floor finish and enhance grain definition. Water & dirt repellent, soft to the touch yet supremely durable. Suitable for all domestic and commercial floors.
Mixing Guidelines	Supplied ready for use (RFU).
Typical Handling	<p>Drying Time: 8 - 12 hours, Recoat Time 8 - 12 hours</p> <p>These times are dependant amounts applied, the absorbency of the wooden substrate and application conditions.</p>
Cleaning	R047 - White Spirit should be used for cleaning equipment.
Coverage	Approximately 8-12m ² per litre depending upon the application method, absorbency and surface quality of the timber being coated.
System Guidelines	<p>Morrells recommends the following guidance for use of this product:</p> <p>Typical Finish:</p> <ul style="list-style-type: none"> ○ The surfaces of the timber to be coated should be clean, dry and free from oils, greases, waxes, silicones, old finishes etc. ○ Apply an even film of holzöl Antislip Floor-Oil with a brush, rag or roller over the surface of the timber. ○ Allow to dry for 8 - 12 hours, then lightly abrade with 220/240 silicon carbide abrasive. ○ Apply a second coat of holzöl Antislip Floor-Oil, as above. ○ Allow 12 hours to completely dry. <p>Using this product in systems outside these guidelines can lead to immediate and latent problems with the integrity of the finish.</p>
Maintenance	The holzöl Antislip Floor-Oil should be maintained using a clean, lightly dampened cloth.



	If the finish becomes "tired" looking or damaged, abrade with 240/320 silicon carbide abrasive and apply a further coat of holzöl Antislip Floor-Oil.
Important Information	<ul style="list-style-type: none"> ➤ Designed for manual (brush, roller or rag) application. ➤ Always test the product on a spare surface or inconspicuous area to assess compatibility, colour and finish. ➤ Sawdust, cloths, brushes, papers and similar products containing wet product may cause spontaneous combustion. Either allow to fully dry or drench in water before disposal. ➤ Product should be stored above 5°C and protected from frost. ➤ Optimum application is achieved between 20°C and 25°C with good air movement and ventilation. ➤ Meets the VOC requirements of 2004/42/EC, Annex II (cat A/i).
Health & Safety	<p>Reference should be made to the appropriate MSDS for this product, which can be found at www.morrells.co.uk</p> <p>The use of appropriate personal protection equipment (PPE) is recommended.</p>

The information provided on this information sheet is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.

For further technical information contact our Technical Support Team on 0161 406 5300.



Morrells Woodfinishes Ltd. Wellington Works, Mill Lane, Woodley, Stockport, Cheshire. SK6 1RN
 Tel: 08705 60 61 62 Fax: 08705 604 604 Email: enquiries@morrells.co.uk Web: www.morrells.co.uk
 Registered Office: Morrells Woodfinishes Limited. Company no. 785935 VAT. Reg No GB 712 5048 66

