



**WOOD
FINISHES
DIRECT**



Finish. Finished.

The following Safety Datasheet is provided by **Morrells**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Holzol Anti Slip Floor Oil](#)

SAFETY DATA SHEET
HOLZOL Anti Slip Oil
1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	HOLZOL Anti Slip Oil
PRODUCT NO.	7AS/00/10
APPLICATION	Oil finish for wood
SUPPLIER	Morrells Woodfinishes Ltd Wellington Works Mill Lane, Woodley Stockport England SK6 1RN 0161 406 5300 0161 406 6276 enquiries@morrells.co.uk
EMERGENCY TELEPHONE	0161 406 5300 DURING OFFICE HOURS

2 HAZARDS IDENTIFICATION

CLASSIFICATION (1999/45)	R66.	
CLASSIFICATION (EC 1272/2008)	Physical	Not classified.
	Health	EUH066
	Environmental	Not classified.
CONTAINS	NAPHTHA PETROLEUM TREATED HEAVY	
PRECAUTIONARY STATEMENTS	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.

3 COMPOSITION/INFORMATION ON INGREDIENTS

naphtha (petrol) hydrotreated heavy	5-10%
CAS-No.: 64742-48-9	EC No.: 927-241-2
Classification (EC 1272/2008) Flam. Liq. 3 - H226 STOT Single 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412	Classification (67/548) Xn;R65. R10,R52/53,R67.
NAPHTHA PETROLEUM TREATED HEAVY	30-60%
CAS-No.: 64742-48-9	EC No.: 265-150-3
Classification (EC 1272/2008) EUH066 Asp. Tox. 1 - H304	Classification (67/548) Xn;R65. R66.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

4 FIRST-AID MEASURES
INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

HOLZOL Anti Slip Oil

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Extinguish with foam, carbon dioxide or dry powder.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray should be used to cool containers. Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

If heated, volume and pressure increases strongly, resulting in explosion of container.

PROTECTIVE MEASURES IN FIRE

Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses. Contain spillages with sand, earth or any suitable adsorbent material.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Risk of vapour concentration on the floor and in low-lying areas. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from heat, sparks and open flame.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
naphtha (petrol) hydrotreated heavy	WEL		1595 mg/m3			
NAPHTHA PETROLEUM TREATED HEAVY	WEL	148 ppm	1200 mg/m3			

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level.

ENGINEERING MEASURES

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HOLZOL Anti Slip Oil**HAND PROTECTION**

Use suitable protective gloves if risk of skin contact. Protective gloves should be used if there is a risk of direct contact or splash. For prolonged or repeated skin contact use suitable protective gloves.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield. Wear splash-proof eye goggles to prevent any possibility of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
FLASH POINT (°C)	>60
VOLATILE ORGANIC COMPOUND (VOC)	282 g/litre

10 STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

TOXIC DOSE 1 - LD 50	5000 mg/kg (oral rat)
-----------------------------	-----------------------

INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

Repeated exposure may cause skin dryness or cracking.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

Not regarded as dangerous for the environment.

LC 50, 96 Hrs, FISH mg/l	8.2
EC 50, 48 Hrs, DAPHNIA, mg/l	4.5
IC 50, 72 Hrs, ALGAE, mg/l	3.1

DEGRADABILITY

The product is biodegradable, but it must not be discharged into drains without permission from the authorities.

13 DISPOSAL CONSIDERATIONS**GENERAL INFORMATION**

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

Road Transport Notes	Not Classified
Rail Transport Notes	Not classified.
Sea Transport Notes	Not classified.
Air Transport Notes	Not classified.

HOLZOL Anti Slip Oil**15 REGULATORY INFORMATION****STATUTORY INSTRUMENTS**

The Classification, Labelling and Packaging of substances and mixtures Regulations EC 1272/2008 (CLP) and amendments

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

REVISION DATE 17/09/2015

REV. NO./REPL. SDS 1

GENERATED**RISK PHRASES IN FULL**

R10 Flammable.
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

HAZARD STATEMENTS IN FULL

EUH066 Repeated exposure may cause skin dryness or cracking.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.