



**WOOD
FINISHES
DIRECT**



Finish. Finished.

The following Safety Datasheet is provided by **Morrells**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Holzol Decking Oil](#)

SAFETY DATA SHEET

HOLZOL Decking Oil

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name HOLZOL Decking Oil
Product No. 7DO/0*/30 Range

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Oil finish for wood

1.3. Details of the supplier of the safety data sheet

Supplier: Morrells Woodfinishes Ltd
 Wellington Works
 Mill Lane, Woodley
 Stockport
 England
 SK6 1RN
 0161 406 5300
 0161 406 6276
 enquiries@morrells.co.uk

1.4. Emergency telephone number

0161 406 5300 DURING OFFICE HOURS

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical	Not classified.
Health	EUH066
Environmental	Not classified.

Classification (1999/45)

R66.

2.2. Label elements

Contains: NAPHTHA PETROLEUM TREATED HEAVY

Supplemental Label Information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

naphtha (petrol) hydrotreated heavy	1-5%
CAS-No.: 64742-48-9	EC No.: 927-241-2
Classification (EC 1272/2008) Flam. Liq. 3 - H226 STOT Single 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412	Classification (67/548) Xn;R65. R10,R52/53,R67.

HOLZOL Decking Oil

NAPHTHA PETROLEUM TREATED HEAVY		30-60%
CAS-No.: 64742-48-9	EC No.: 265-150-3	
Classification (EC 1272/2008) EUH066 Asp. Tox. 1 - H304	Classification (67/548) Xn;R65. R66.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation.

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

Ingestion

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

Skin Contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing Media

This product is not flammable. Extinguish with foam, carbon dioxide or dry powder.

Unsuitable Extinguishing Media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

If heated, volume and pressure increases strongly, resulting in explosion of container.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Water spray should be used to cool containers. Keep run-off water out of sewers and water sources. Dike for water control.

Protective Measures In Fire

Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Do not allow to enter drains, sewers or watercourses. Contain spillages with sand, earth or any suitable adsorbent material.

6.3. Methods and material for containment and cleaning up

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

6.4. Reference to other sections

Collect and dispose of spillage as indicated in section 13. Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: HANDLING AND STORAGE

HOLZOL Decking Oil

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Risk of vapour concentration on the floor and in low-lying areas. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
naphtha (petrol) hydrotreated heavy	WEL		1595 mg/m ³			
NAPHTHA PETROLEUM TREATED HEAVY	WEL	148 ppm	1200 mg/m ³			

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective Equipment



Process Conditions

Use engineering controls to reduce air contamination to permissible exposure level.

Engineering Measures

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of vapours.

Respiratory Equipment

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

Hand Protection

Use suitable protective gloves if risk of skin contact. Protective gloves should be used if there is a risk of direct contact or splash. For prolonged or repeated skin contact use suitable protective gloves.

Eye Protection

If risk of splashing, wear safety goggles or face shield. Wear splash-proof eye goggles to prevent any possibility of eye contact.

Other Protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene Measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Flash Point (°C)	>60

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

HOLZOL Decking Oil

10.4. Conditions to avoid

Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxic Dose 1 - Ld 50 5000 mg/kg (oral rat)
Naphtha (Petrol) Hydrotreated heavy

Acute Toxicity (Dermal LD50) 2000 mg/kg Rabbit

Inhalation

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

Ingestion.

May cause discomfort if swallowed.

Skin Contact

Repeated exposure may cause skin dryness or cracking.

Eye Contact

Spray and vapour in the eyes may cause irritation and smarting.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Not regarded as dangerous for the environment.

12.1. Toxicity

LC 50, 96 Hrs, Fish mg/l 8.2

EC 50, 48 Hrs, Daphnia, mg/l 4.5

IC 50, 72 Hrs, Algae, mg/l 3.1

12.2. Persistence and degradability

Degradability:

The product is biodegradable, but it must not be discharged into drains without permission from the authorities.

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

General Information

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

Road Transport Notes Not Classified

Rail Transport Notes Not classified.

Sea Transport Notes Not classified.

Air Transport Notes Not classified.

14.1. UN number

14.2 UN Proper Shipping Name

14.3 Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Classification, Labelling and Packaging of substances and mixtures Regulations EC 1272/2008 (CLP) and amendments

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

Guidance Notes

Workplace Exposure Limits EH40.

Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are noted for this product.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions of use are noted for this product.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Date 17/09/2015

Revision 1

Risk Phrases In Full

R10 Flammable.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

EUH066 Repeated exposure may cause skin dryness or cracking.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.