



**WOOD  
FINISHES  
DIRECT**



Finish. Finished.

The following Safety Datasheet is provided by **Morrells**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Holzol Floor Oil](#)

**SAFETY DATA SHEET**  
**HOLZOL Floor Oil**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

**Product Name** HOLZOL Floor Oil

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

**Supplier:** Morrells Woodfinishes Ltd  
Wellington Works  
Mill Lane, Woodley  
Stockport  
England  
SK6 1RN  
0161 406 5300  
0161 406 6276  
enquiries@morrells.co.uk

**1.4. Emergency telephone number**

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

**Classification (EC 1272/2008)**

Physical	Flam. Liq. 3 - H226
Health	EUH066; Asp. Tox. 1 - H304
Environmental	Not classified.

**Classification (1999/45)**

Xn;R65. R10, R66.

**2.2. Label elements**

**Contains:** NAPHTHA PETROLEUM TREATED HEAVY

**Label In Accordance With (Ec) No. 1272/2008**



**Signal Word** Danger

**Hazard Statements**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.

**Precautionary Statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Supplementary Precautionary Statements**

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

## HOLZOL Floor Oil

P331	Do NOT induce vomiting.
P370+378	In case of fire: Use ... for extinction.
P403+235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to ...

### Supplemental Label Information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

### 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

NAPHTHA PETROLEUM TREATED HEAVY		30-60%
CAS-No.: 64742-48-9	EC No.: 265-150-3	
Classification (EC 1272/2008) EUH066 Asp. Tox. 1 - H304	Classification (67/548) Xn;R65. R66.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

#### General Information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### Inhalation.

Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

#### Ingestion

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Drink plenty of water. Get medical attention immediately! Provide rest, warmth and fresh air.

#### Skin Contact

Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

#### Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Extinguishing Media

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

### 5.2. Special hazards arising from the substance or mixture

### 5.3. Advice for firefighters

#### Special Fire Fighting Procedures

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.2. Environmental precautions

# HOLZOL Floor Oil

## 6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

## 6.4. Reference to other sections

### SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

#### 7.3. Specific end use(s)

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
NAPHTHA PETROLEUM TREATED HEAVY	WEL	148 ppm	1200 mg/m <sup>3</sup>			

WEL = Workplace Exposure Limit.

#### Ingredient Comments

WEL = Workplace Exposure Limits

#### 8.2. Exposure controls

##### Protective Equipment



##### Engineering Measures

Provide adequate general and local exhaust ventilation.

##### Respiratory Equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

##### Hand Protection

Use protective gloves.

##### Eye Protection

Wear approved safety goggles.

##### Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

##### Hygiene Measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Flash Point (°C)	>23 T > 60

#### 9.2. Other information

Volatile Organic Compound (VOC)	435 g/litre
---------------------------------	-------------

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

**10.2. Chemical stability**

Stable under normal temperature conditions.

**10.3. Possibility of hazardous reactions**

**10.4. Conditions to avoid**

Avoid contact with acids and oxidising substances.

**10.5. Incompatible materials**

**10.6. Hazardous decomposition products**

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

**Health Warnings**

INHALATION. Prolonged inhalation of high concentrations may damage respiratory system. SKIN CONTACT. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation. EYE CONTACT. May cause severe irritation to eyes. INGESTION. The product causes irritation of mucous membranes and may cause abdominal discomfort if swallowed.

**Target Organs**

Skin Eyes Respiratory system, lungs

**SECTION 12: ECOLOGICAL INFORMATION**

**Ecotoxicity:**

No data on possible environmental effects have been found.

**12.1. Toxicity**

**12.2. Persistence and degradability**

**12.3. Bioaccumulative potential**

**12.4. Mobility in soil**

**12.5. Results of PBT and vPvB assessment**

**12.6. Other adverse effects**

**SECTION 13: DISPOSAL CONSIDERATIONS**

**General Information**

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

**13.1. Waste treatment methods**

Dispose of waste and residues in accordance with local authority requirements.

**SECTION 14: TRANSPORT INFORMATION**

**14.1. UN number**

UN No. (ADR/RID/ADN) 1263

**14.2 UN Proper Shipping Name**

Proper Shipping Name PAINT or PAINT RELATED PRODUCTS

**14.3 Transport hazard class(es)**

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

**Transport Labels**



**14.4. Packing group**

ADR/RID/ADN Packing group 3(b)

**14.5. Environmental hazards**

Environmentally Hazardous Substance/Marine Pollutant  
No.

**14.6. Special precautions for user**

EMS 3-07  
Emergency Action Code 3[Y]E  
Hazard No. (ADR) 33

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

**SECTION 15: REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Uk Regulatory References**

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

**Environmental Listing**

No listing noted.

**Statutory Instruments**

The Classification, Labelling and Packaging of substances and mixtures Regulations EC 1272/2008 (CLP) and amendments

**Approved Code Of Practice**

Classification and Labelling of Substances and Preparations Dangerous for Supply.

**Guidance Notes**

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37.

**Eu Legislation**

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

**15.2. Chemical Safety Assessment**

**SECTION 16: OTHER INFORMATION**

**Risk Phrases In Full**

R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.

**Hazard Statements In Full**

EUH066 Repeated exposure may cause skin dryness or cracking.  
H304 May be fatal if swallowed and enters airways.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.