



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Morrells**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Holzol Furniture Oil Tints](#)

Product Data Sheet



holzöl Furniture-Oil

Code	Description	Code	Description
7FW/00/10	holzöl Furniture-Oil Clear 10% Sheen	7FW/01/30	holzöl Furniture-Oil Oak 30% Sheen
7FW/00/30	holzöl Furniture-Oil Clear 30% Sheen	7FW/03/30	holzöl Furniture-Oil Mahogany 30% Sheen
7FW/02/30	holzöl Furniture-Oil Teak 30% Sheen	7FW/05/30	holzöl Furniture-Oil Grey 30% Sheen
7FW/04/30	holzöl Furniture-Oil White 30% Sheen	Thinners	R047 - White Spirit
7FW/06/30	holzöl Furniture-Oil Ivory 30% Sheen		

Technical Data	holzöl Furniture-Oil is formulated on a mixture of natural oils with micronized waxes, reinforced with high quality resins.
Properties	holzöl Furniture-Oil a blend of natural oils, hybrid resins and micronized waxes to enhance the intrinsic beauty of all timber surfaces. Water & dirt repellent, soft to the touch yet supremely durable. Suitable for all domestic and commercial furniture. Also available in a soft-feel, dead matte Waxy-oil.
Mixing Guidelines	Supplied ready for use (RFU) but can be thinned up to 15% by volume with the recommended thinner, R047, if required.
Typical Handling	Drying Time: 6 - 8 hours, Recoat Time: 6 - 8 hours Maximum hardness after 12 hours. These times are dependant amounts applied, the absorbency of the wooden substrate and application conditions.
Cleaning	R047 - White Spirit should be used for cleaning equipment.
Coverage	Approximately 10-12m ² per litre depending upon the application method, absorbency and surface quality of the timber being coated.
Colour Matching	Morrells provides a bespoke colour matching service for holzöl Furniture-Oil. All requests for special colours should be accompanied by a sufficient quantity of the timber to be used for the actual job plus details of the application method and the number of coats to be applied.
System Guidelines	Morrells recommends the following guidance for use of these products : Typical Finish: <ul style="list-style-type: none"> o The surfaces of the timber to be coated should be clean, dry and free from oils, greases, waxes, silicones, old finishes etc. o Apply an even film of holzöl Furniture-Oil with a brush or rag over the surface of the timber.



	<ul style="list-style-type: none"> ○ With some exotic timbers, the first coat can be thinned (See Mixing Guidelines). ○ Allow to dry for 6-8 hours, then lightly abrade with 220/240 silicon carbide abrasive. ○ Apply a second coat of holzöl Furniture-Oil, as above. Allow 12 hours to completely dry. <p>Using these products in systems outside these guidelines can lead to immediate and latent problems with the integrity of the finish.</p>
Maintenance	<p>The holzöl Furniture-Oil should be maintained using a clean, lightly dampened cloth.</p> <p>If the finish becomes “fired” looking or damaged, abrade with 240/320 silicon carbide abrasive and apply a further coat of holzöl Furniture-Oil.</p>
Important Information	<ul style="list-style-type: none"> ➤ Designed for manual (brush or rag) application. ➤ Use only the recommended thinner. Use of non-recommended thinner can cause uneven/patchy drying. ➤ Always test the product on a spare surface or inconspicuous area to assess compatibility, colour and finish. ➤ Sawdust, cloths, brushes, papers and similar products containing wet product may cause spontaneous combustion. Either allow to fully dry or drench in water before disposal. ➤ Product should be stored above 5°C and protected from frost. ➤ Optimum application is achieved between 18°C and 22°C with good air movement and ventilation. ➤ Finished products should not be subjected to environments with temperatures of < 2°C. ➤ Meets the VOC requirements of 2004/42/EC, Annex II(cat A/i).
Health & Safety	<p>Reference should be made to the appropriate MSDS for these products, which can be found at www.morrells.co.uk</p> <p>The use of appropriate personal protection equipment (PPE) is recommended.</p>

The information provided on this information sheet is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.

For further technical information contact our Technical Support Team on 0161 406 5300.

