



**WOOD  
FINISHES  
DIRECT**



Finish. Finished.

The following Product Datasheet is provided by **Morrells**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Holzol Furniture Oil](#)

# Product Data Sheet



## holzöl Furniture-Oil

| Code      | Description                                 | Code      | Description                                    |
|-----------|---|-----------|--|
| 7FW/00/10 | <b>holzöl</b> Furniture-Oil Clear 10% Sheen | 7FW/01/30 | <b>holzöl</b> Furniture-Oil Oak 30% Sheen      |
| 7FW/00/30 | <b>holzöl</b> Furniture-Oil Clear 30% Sheen | 7FW/03/30 | <b>holzöl</b> Furniture-Oil Mahogany 30% Sheen |
| 7FW/02/30 | <b>holzöl</b> Furniture-Oil Teak 30% Sheen  | 7FW/05/30 | <b>holzöl</b> Furniture-Oil Grey 30% Sheen     |
| 7FW/04/30 | <b>holzöl</b> Furniture-Oil White 30% Sheen | Thinners  | R047 - White Spirit                            |
| 7FW/06/30 | <b>holzöl</b> Furniture-Oil Ivory 30% Sheen |           |  |

|                          |   |
|--------------------------|---|
| <b>Technical Data</b>    | <b>holzöl</b> Furniture-Oil is formulated on a mixture of natural oils with micronized waxes, reinforced with high quality resins.  |
| <b>Properties</b>        | <b>holzöl</b> Furniture-Oil a blend of natural oils, hybrid resins and micronized waxes to enhance the intrinsic beauty of all timber surfaces. Water & dirt repellent, soft to the touch yet supremely durable. Suitable for all domestic and commercial furniture. Also available in a soft-feel, dead matte Waxy-oil.  |
| <b>Mixing Guidelines</b> | Supplied ready for use (RFU) but can be thinned up to 15% by volume with the recommended thinner, R047, if required.  |
| <b>Typical Handling</b>  | Drying Time: 6 - 8 hours,<br>Recoat Time: 6 - 8 hours<br>Maximum hardness after 12 hours.<br><br>These times are dependant amounts applied, the absorbency of the wooden substrate and application conditions.  |
| <b>Cleaning</b>          | R047 - White Spirit should be used for cleaning equipment.  |
| <b>Coverage</b>          | Approximately 10-12m <sup>2</sup> per litre depending upon the application method, absorbency and surface quality of the timber being coated.   |
| <b>Colour Matching</b>   | Morrells provides a bespoke colour matching service for <b>holzöl</b> Furniture-Oil.<br><br>All requests for special colours should be accompanied by a sufficient quantity of the timber to be used for the actual job plus details of the application method and the number of coats to be applied.   |
| <b>System Guidelines</b> | Morrells recommends the following guidance for use of these products :<br><br><b>Typical Finish:</b> <ul style="list-style-type: none"> <li>o The surfaces of the timber to be coated should be clean, dry and free from oils, greases, waxes, silicones, old finishes etc.</li> <li>o Apply an even film of <b>holzöl</b> Furniture-Oil with a brush or rag over the surface of the timber.</li> </ul> |



|                              |  |
|------------------------------|--|
|                              | <ul style="list-style-type: none"> <li>○ With some exotic timbers, the first coat can be thinned (See Mixing Guidelines).</li> <li>○ Allow to dry for 6-8 hours, then lightly abrade with 220/240 silicon carbide abrasive.</li> <li>○ Apply a second coat of <b>holzöl</b> Furniture-Oil, as above. Allow 12 hours to completely dry.</li> </ul> <p>Using these products in systems outside these guidelines can lead to immediate and latent problems with the integrity of the finish.</p>  |
| <b>Maintenance</b>           | <p>The <b>holzöl</b> Furniture-Oil should be maintained using a clean, lightly dampened cloth.</p> <p>If the finish becomes “fired” looking or damaged, abrade with 240/320 silicon carbide abrasive and apply a further coat of <b>holzöl</b> Furniture-Oil.</p>  |
| <b>Important Information</b> | <ul style="list-style-type: none"> <li>➤ Designed for manual (brush or rag) application.</li> <li>➤ Use only the recommended thinner. Use of non-recommended thinner can cause uneven/patchy drying.</li> <li>➤ Always test the product on a spare surface or inconspicuous area to assess compatibility, colour and finish.</li> <li>➤ Sawdust, cloths, brushes, papers and similar products containing wet product may cause spontaneous combustion. Either allow to fully dry or drench in water before disposal.</li> <li>➤ Product should be stored above 5°C and protected from frost.</li> <li>➤ Optimum application is achieved between 18°C and 22°C with good air movement and ventilation.</li> <li>➤ Finished products should not be subjected to environments with temperatures of &lt; 2°C.</li> <li>➤ Meets the VOC requirements of 2004/42/EC, Annex II(cat A/i).</li> </ul> |
| <b>Health &amp; Safety</b>   | <p>Reference should be made to the appropriate MSDS for these products, which can be found at <a href="http://www.morrells.co.uk">www.morrells.co.uk</a></p> <p>The use of appropriate personal protection equipment (PPE) is recommended.</p>   |

The information provided on this information sheet is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.

For further technical information contact our Technical Support Team on 0161 406 5300.

