



# WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Morrells**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Holzol Quick Oil](#)

# Product Data Sheet



## holzöl Quick-Oil

Code	Description
7QO/00/10	holzöl Quick-Oil 10% Sheen
<b>Technical Data</b>	holzöl Quick-Oil is a fast drying natural oil/resin formulation for site work and painting contractors.
<b>Properties</b>	holzöl Quick-Oil a fast drying natural oil/resin formulation for site work and painting contractors. Water & dirt repellent, extremely durable and easy to apply. Suitable for bar work, counters, panelling, architrave etc.
<b>Mixing Guidelines</b>	Supplied ready for use (RFU).
<b>Typical Handling</b>	Drying Time: 4 - 5 hours, Recoat Time 4 – 5 hours  These times are dependant amounts applied, the absorbency of the wooden substrate and application conditions.
<b>Cleaning</b>	R047 - White Spirit should be used for cleaning equipment.
<b>Coverage</b>	Approximately 8-12m <sup>2</sup> per litre depending upon the application method, absorbency and surface quality of the timber being coated.
<b>System Guidelines</b>	Morrells recommends the following guidance for use of this product:  <b>Typical Finish:</b> <ul style="list-style-type: none"> <li>○ The surfaces of the timber to be coated should be clean, dry and free from oils, greases, waxes, silicones, old finishes etc.</li> <li>○ Apply an even film of <b>holzöl</b> Quick-Oil with a brush, rag or roller over the surface of the timber.</li> <li>○ Allow to dry for 4-5 hours, then lightly abrade with 220/240 silicon carbide abrasive.</li> <li>○ Apply a second coat of <b>holzöl</b> Quick-Oil, as above. Allow 12 hours to completely dry.</li> </ul> <p>Using this product in systems outside these guidelines can lead to immediate and latent problems with the integrity of the finish.</p>
<b>Maintenance</b>	The <b>holzöl</b> Quick-Oil should be maintained using a clean, lightly dampened cloth.  If the finish becomes "tired" looking or damaged, abrade with 240/320 silicon carbide abrasive and apply a further coat of <b>holzöl</b> Quick-Oil.



Morrells Woodfinishes Ltd. Wellington Works, Mill Lane, Woodley, Stockport, Cheshire. SK6 1RN  
Tel: 08705 60 61 62 Fax: 08705 604 604 Email: enquiries@morrells.co.uk Web: www.morrells.co.uk

Registered Office: Morrells Woodfinishes Limited. Company no. 785935 VAT. Reg No GB 712 5048 66



<p><b>Important Information</b></p>	<ul style="list-style-type: none"> <li>➤ Designed for manual (brush, roller or rag) application.</li> <li>➤ Always test the product on a spare surface or inconspicuous area to assess compatibility, colour and finish.</li> <li>➤ Sawdust, cloths, brushes, papers and similar products containing wet product may cause spontaneous combustion. Either allow to fully dry or drench in water before disposal.</li> <li>➤ Product should be stored above 5°C and protected from frost.</li> <li>➤ Optimum application is achieved between 20°C and 25°C with good air movement and ventilation.</li> <li>➤ Meets the VOC requirements of 2004/42/EC, Annex II(cat A/i).</li> </ul>
<p><b>Health &amp; Safety</b></p>	<p>Reference should be made to the appropriate MSDS for this product, which can be found at <a href="http://www.morrells.co.uk">www.morrells.co.uk</a></p> <p>The use of appropriate personal protection equipment (PPE) is recommended.</p>

The information provided on this information sheet is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.

For further technical information contact our Technical Support Team on 0161 406 5300.

