



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Morrells**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Holzol Waxy Oil](#)

Product Data Sheet



holzöl Waxy-Oil

Code	Description	
7WO/00/10	holzöl Waxy-Oil Dead matt	

Technical Data	holzöl Waxy-Oil is a unique oil that contains a fine dispersion of natural waxes.	
Properties	<p>holzöl Waxy-Oil is a unique oil that contains a fine dispersion of natural waxes, ideal for internal furniture, beams and wall panelling.</p> <p>holzöl Waxy-Oil offers superior protection, while the waxes offer excellent water repellence along with a smooth soft touch, dead matt finish.</p>	
Mixing Guidelines	Supplied ready for use (RFU).	
Typical Handling	<p>Drying Time: 8 - 12 hours, Recoat Time 8 - 12 hours</p> <p>These times are dependant amounts applied, the absorbency of the wooden substrate and application conditions.</p>	
Cleaning	R047 - White Spirit should be used for cleaning equipment.	
Coverage	Approximately 8 -12 m ² per litre depending upon the application method, absorbency and surface quality of the timber being coated.	
System Guidelines	<p>Morrells recommends the following guidance for use of this product:</p> <p>Typical Finish:</p> <ul style="list-style-type: none"> ○ The surfaces of the timber to be coated should be clean, dry and free from oils, greases, waxes, silicones, old finishes etc. ○ Apply an even film of holzöl Waxy-Oil with a brush or rag over the surface of the timber. ○ Allow to dry for 6-8 hours, then lightly abrade with 220/240 silicon carbide abrasive. ○ Apply a second coat of holzöl Waxy-Oil, as above. Allow 12 hours to completely dry <p>Using this product in systems outside these guidelines can lead to immediate and latent problems with the integrity of the finish.</p>	
Maintenance	<p>The holzöl Waxy Oil should be maintained using a clean, lightly dampened cloth.</p> <p>If the finish becomes "tired" looking or damaged, abrade with 240/320 silicon</p>	



	carbide abrasive and apply a further coat of holzöl Waxy Oil.
Important Information	<ul style="list-style-type: none"> ➤ Designed for manual (brush or rag) application. ➤ Always test the product on a spare surface or inconspicuous area to assess compatibility, colour and finish. ➤ Sawdust, cloths, brushes, papers and similar products containing wet product may cause spontaneous combustion. Either allow to fully dry or drench in water before disposal. ➤ Product should be stored above 5°C and protected from frost. ➤ Optimum application is achieved between 20°C and 25°C with good air movement and ventilation. ➤ Meets the VOC requirements of 2004/42/EC, Annex II(cat A/i).
Health & Safety	<p>Reference should be made to the appropriate MSDS for this product, which can be found at www.morrells.co.uk</p> <p>The use of appropriate personal protection equipment (PPE) is recommended.</p>

The information provided on this information sheet is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.

For further technical information contact our Technical Support Team on 0161 406 5300.

