



**WOOD  
FINISHES  
DIRECT**



Finish. Finished.

The following Product Datasheet is provided by **Morrells**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Holzol Worktop Oil](#)

# Product Data Sheet



## holzöl Worktop-Oil

| Code      | Description                        | Code     | Description         |
|-----------|------------------------------------|----------|---------------------|
| 7TO/00/30 | holzöl Worktop-Oil Clear 30% Sheen | Thinners | R047 - White Spirit |

|                          |  |
|--------------------------|--|
| <b>Technical Data</b>    | holzöl Worktop-Oil is formulated on a blend of quality, modified natural oils for use on kitchen worktops and furniture  |
| <b>Properties</b>        | <p>holzöl Worktop-Oil is a food safe fast drying natural oil with a pleasant bouquet, designed to penetrate solid wood worktops and kitchen / bathroom surfaces.</p> <p>High resistance to scratching, staining (e.g. alcohol, coffee, cola, fruit juice etc.), easy to clean and to restore.</p> <p>It conforms to EN71-3: 2013 and does not release any potentially harmful hazardous substances.</p>  |
| <b>Mixing Guidelines</b> | Supplied ready for use (RFU) but can be thinned up to 15% by volume with the recommended thinner, R047, if required  |
| <b>Typical Handling</b>  | <p>Drying Time: 12 hours,<br/>Recoat Time: 6 - 8 hours<br/>Packing Time: Overnight minimum.</p> <p>Maximum hardness after 24 hours.</p> <p>These times are dependant amounts applied, the absorbency of the wooden substrate and application conditions.</p>   |
| <b>Cleaning</b>          | R047 - White Spirit should be used for cleaning equipment.   |
| <b>Coverage</b>          | Approximately 10-12m <sup>2</sup> per litre depending upon the application method, absorbency and surface quality of the timber being coated.  |
| <b>System Guidelines</b> | <p>Morrells recommends the following guidance for use of this product:</p> <p><b>Typical Finish:</b></p> <ul style="list-style-type: none"> <li>○ The surfaces of the timber to be coated should be clean, dry and free from oils, greases, waxes, silicones, old finishes etc.</li> <li>○ Apply an even film of <b>holzöl</b> Worktop-Oil with a brush or rag over the surface. Work the oil fully into the grain of the wood. If required, and especially with exotic or oily timbers, the first coat can be thinned (See Mixing Guidelines).</li> <li>○ Allow to dry for 6-8 hours, then lightly abrade with 220/240 silicon carbide abrasive.</li> </ul> |



|                              |  |
|------------------------------|--|
|                              | <p>o Apply a second coat of <b>holzöl</b> Worktop-Oil, as above. Allow 12 hours to completely dry.</p> <p>Using this product in systems outside these guidelines can lead to immediate and latent problems with the integrity of the finish.</p>   |
| <b>Maintenance</b>           | <p>The <b>holzöl</b> Worktop-Oil should be maintained using a clean, lightly dampened cloth.</p> <p>If the finish becomes "tired" looking or damaged, abrade with 240/320 silicon carbide abrasive and apply a further coat of <b>holzöl</b> Worktop-Oil.</p>  |
| <b>Important Information</b> | <ul style="list-style-type: none"> <li>➤ Designed for manual (brush, rag) application.</li> <li>➤ Use only the recommended thinner. Use of non-recommended thinner can cause uneven/patchy drying.</li> <li>➤ Always test the product on a spare surface or inconspicuous area to assess compatibility, colour and finish.</li> <li>➤ Sawdust, cloths, brushes, papers and similar products containing wet product may cause spontaneous combustion. Either allow to fully dry or drench in water before disposal.</li> <li>➤ Product should be stored above 5°C and protected from frost.</li> <li>➤ Optimum application is achieved between 18°C and 22°C with good air movement and ventilation.</li> <li>➤ Finished products should not be subjected to environments with temperatures of &lt; 2°C.</li> <li>➤ Meets the VOC requirements of 2004/42/EC, Annex II(cat A/i).</li> </ul> |
| <b>Health &amp; Safety</b>   | <p>Reference should be made to the appropriate MSDS for this product, which can be found at <a href="http://www.morrells.co.uk">www.morrells.co.uk</a></p> <p>The use of appropriate personal protection equipment (PPE) is recommended.</p>   |

The information provided on this information sheet is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.

For further technical information contact our Technical Support Team on 0161 406 5300.

