



**WOOD
FINISHES
DIRECT**



Finish. Finished.

The following Safety Datasheet is provided by **Jacpol**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Jacpol Furniture Wax](#)

SAFETY DATA SHEET
ANTIQUUE WAXES - JACPOL & JACKSON

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name ANTIQUE WAXES - JACPOL & JACKSON
Product No. 437*/*2* TO 4388/*2* RANGE plus 4978/200

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial wood coating.

1.3. Details of the supplier of the safety data sheet

Supplier: Morrells Woodfinishes Ltd
 Wellington Works
 Mill Lane, Woodley
 Stockport
 England
 SK6 1RN
 0161 406 5300
 0161 406 6276
 enquiries@morrells.co.uk

1.4. Emergency telephone number

0161 406 5300 DURING OFFICE HOURS

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture**Classification (EC 1272/2008)**

Physical	Flam. Liq. 3 - H226
Health	EUH066;STOT Single 3 - H335, H336
Environmental	Aquatic Chronic 2 - H411

Classification (1999/45) Xi;R37. N;R51/53. R10, R66, R67.

Human Health

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Repeated exposure may cause skin dryness or cracking. In high concentrations, vapours may be irritating to the respiratory system.

Environment

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Physical And Chemical Hazards

Vapours are heavier than air and may travel along the floor and in the bottom of containers.

2.2. Label elements**Label In Accordance With (Ec) No. 1272/2008****Signal Word**

Warning

Hazard Statements

H226	Flammable liquid and vapour.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

ANTIQUE WAXES - JACPOL & JACKSON

Precautionary Statements

P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Supplementary Precautionary Statements

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P370+378	In case of fire: Use ... for extinction.
P391	Collect spillage.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P403+235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to ...

Supplemental Label Information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

SOLVENT NAPHTHA LOW BOILING POINT		60-100%
CAS-No.: 64742-95-6	EC No.: 265-199-0	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT Single 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548) Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

Composition Comments

The data shown are in accordance with the latest EC Directives.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Information

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

Inhalation.

Place unconscious person on the side in the recovery position and ensure breathing. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

Ingestion

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions.

Skin Contact

Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water.

ANTIQUÉ WAXES - JACPOL & JACKSON

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing Media

Use: Alcohol resistant foam. Carbon dioxide (CO₂). Dry chemicals, sand, dolomite etc. DO NOT use water if avoidable.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Fire causes formation of toxic gases.

Specific Hazards

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Keep run-off water out of sewers and water sources. Dike for water control.

Protective Measures In Fire

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Do not discharge onto the ground or into water courses. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.

6.3. Methods and material for containment and cleaning up

Keep combustibles away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Wash contaminated area with water. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Do not use contact lenses. Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Use explosion proof electric equipment. Eye wash facilities and emergency shower must be available when handling this product. During application and drying, solvent vapours will be emitted.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
SOLVENT NAPHTHA LOW BOILING POINT	WEL	600 ppm				

WEL = Workplace Exposure Limit.

Ingredient Comments

OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

8.2. Exposure controls

Protective Equipment



Process Conditions

Provide eyewash station.

Engineering Measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Hand Protection

Protective gloves and goggles must be used if there is a risk of direct contact or splash.

Eye Protection

Contact lenses should not be worn when working with this chemical! Wear approved safety goggles.

Other Protection

Use engineering controls to reduce air contamination to permissible exposure level. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station and safety shower.

Hygiene Measures

Wash promptly if skin becomes contaminated. Promptly remove non-impervious clothing that becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Wax
Colour	Varying
Initial Boiling Point and Boiling Range:	145
Flash Point (°C)	39

9.2. Other information

Volatile Organic Compound (VOC)	720 to 730 g/litre
---------------------------------	--------------------

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

No particular stability concerns.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhalation

In high concentrations, vapours may irritate throat and respiratory system and cause coughing. Vapours have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Ingestion.

Gastrointestinal symptoms, including upset stomach.

Skin Contact

Repeated exposure may cause skin dryness or cracking. May cause sensitisation by skin contact.

Eye Contact

Irritating and may cause redness and pain.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

General Information

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

13.1. Waste treatment methods

Absorb in vermiculite or dry sand and dispose of at a licenced hazardous waste collection point. Make sure containers are empty before discarding (explosion risk).

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN) 1263

14.2 UN Proper Shipping Name

Proper Shipping Name PAINT or PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group III

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant
No.

14.6. Special precautions for user

EMS F-E, S-D

Emergency Action Code 3YE

Hazard No. (ADR) 33

Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

ANTIQUÉ WAXES - JACPOL & JACKSON

Uk Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

Statutory Instruments

The Classification, Labelling and Packaging of substances and mixtures Regulations EC 1272/2008 (CLP) and amendments

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

Guidance Notes

Introduction to Local Exhaust Ventilation HS(G)37.

National Regulations

Workplace Exposure Limits 2005 (EH40)

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

Revision Date	10/05/2013
Revision	1
Risk Phrases In Full	
R10	Flammable.
R37	Irritating to respiratory system.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.
Hazard Statements In Full	
EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.