



**WOOD
FINISHES
DIRECT**



Finish. Finished.

The following Product Datasheet is provided by **Liberon**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Liberon Decking Oil](#)



Decking Oil

- Protects and enhances most types of timber decking
- Contains UV filters to prevent fading from sunlight
- Revives weathered and greying decking
- Suitable for use on fences, sheds and hot tubs



USAGE

Exterior

COVERAGE

1 Litre

8-10 m²

APPLICATION

Brush or roller

DRYING TIME

15 mins between coats, 24 hours final

TOOL CLEANING

White Spirit

Product use

Liberon Decking Oil is ideal for feeding, protecting and enhancing the natural beauty of most types of timber decking. It is perfect for reviving and restoring colour to old or new decking and is suitable for use on fences, garden sheds, gates and hot tubs etc. Containing UV filters it helps reduce discolouration and fading from the sun, whilst maintaining the finish.

Preparation

Ensure the surface is clean, dry and free from previous finishes and dust. Lightly sand new wood and clean old wood with Liberon Tough Deck Clean and Revive.

Application

Softwoods:

Stir well before use. Apply a generous coat of Decking Oil with a paint brush or roller. Allow to penetrate for 15 to 30 minutes then apply the second coat without waiting for the first to dry. Continue to apply more coats of Decking Oil until the timber no longer absorbs the oil. Wipe off any excess with a lint-free cotton cloth and allow to dry for 24 to 48 hours before using the decking.

Hardwoods:

Unless the hardwood is very absorbent, best results are achieved by wiping on the oil in very thin coats with a cloth. It is essential that any oil that has not been absorbed into the timber is wiped off thoroughly with a clean lint-free cloth. For new hardwoods, it is recommended to leave the wood exposed for up to 12 months before applying any finish. This allows the grain in the wood to open and breathe and aids penetration and adhesion of the finish. For a superior finish on hardwoods, we recommend using Liberon AQUA-STOP® Tough Deck Finish.

Important: Oil finishes bring out the natural colours of timber. A wet surface will be an indication of the final colour. Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.

Cleaning and maintenance

For general maintenance clean with Liberon Tough Deck Clean and Revive. We recommend applying 1 or 2 coats of Decking Oil once a year as routine maintenance. On high traffic areas re-apply 1 or 2 coats of Decking Oil as and when required.

Precautions

- Wear suitable clothing and protective gloves when using the Decking Oil.
- Store Liberon Decking Oil at a temperature above 5°C. Always replace the lid otherwise the oil can deteriorate.

- Oily cloths can self combust. Do not leave impregnated cloths in bundles. Before discarding lay them flat outside to dry to avoid a fire hazard.
- May not be suitable for some foreign hardwoods.

Packaging

Decking Oil is available in 2.5 L and 5 L containers.

Colours

Clear, teak and medium oak.

Health and Safety

Repeated exposure may cause skin dryness or cracking. Keep out of the reach of children. Do not empty into drains. Use only in well-ventilated areas. If swallowed do not induce vomiting: seek medical advice and show this container or label. Contains methylethylketoxime. May produce an allergic reaction.

VOC information

EU limit value for Decking Oil (CatA/I): 600 g/L (2007). Decking Oil contains Max 590 g/L VOC.