



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Liberon**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Liberon Extreme Woodstain](#)



Extreme Woodstain

- Resistant to severe weathering
- Excellent UV protection
- Long lasting colour durability
- Up to 10 years protection



USAGE

Exterior

COVERAGE

1 L 12 m²
depending on
condition of
wood

APPLICATION

Brush, roller
or spray

DRYING TIME

4 hours between
coats
24 hours final

TOOL CLEANING

Water

Product use

Liberon Extreme Woodstain is a highly durable woodstain, with added UV protection, that is specially developed to protect exterior wood against severe weathering (ice, snow, rain, heat) and prolonged exposure to sunlight. Providing up to 10 years protection, it is ideal for use on heavily exposed exterior wood such as cladding, gates, window frames, doors and fences.

Preparation

Ensure the surface is clean and dry.

Bare Wood: brush and remove all traces of dust. For greater protection timber may be treated with an exterior wood preserver before applying Extreme Woodstain.

Previously stained wood: brush the timber to remove any flaking pieces, sand to a smooth surface and remove all dust.

Varnished or painted wood: strip the timber with a general wood stripper. Neutralise in accordance with wood stripper manufacturer's instructions, then rinse with water and allow to dry for 24 hours. Sand and remove all dust.

Oily wood: degrease before applying Extreme Woodstain.

Application

Stir well with a stirring stick before use. Apply a minimum of 2 coats of Extreme Woodstain with a brush, spray (10% dilution with water) or a roller (specially designed for woodstains). On new or heavily exposed timber we recommend applying a third coat when using a light coloured stain. Ideal conditions for application are between 12° and 25°C on wood that is not too hot in order to avoid drying marks.

Important: Always test product on a spare surface or inconspicuous area for compatibility and end result.

Liberon advice

Apply out of direct sunlight and where there is good ventilation. This prevents the woodstain from drying too quickly.

10 Year Protection

Material: New wood with the exclusion of temperate hardwoods (ie. oak, red cedar and iroko). Old or renovated wood: clean, bare, sound and non-greasy. Application: correctly applied. Exposure: on vertical woodwork only. South and South-West exposure apply 3 coats. The guarantee is limited to reimbursing the cost of the product (when accompanied by a receipt) and only relates to the finish of the woodstain.

**Packaging**

Liberon Extreme Woodstain is available in 1L and 2.5 L containers.

Health and Safety

Keep out of the reach of children. Do not empty into drains. Use only in well-ventilated areas. Do not allow to freeze. Contains cobalt carboxylate and hydroxyphenyl benzotriazole, may cause an allergic reaction.

EU limit value for this product (cat. A/e): 150 g/l (2007) / 130 g/l (2010).
This product contains Max 8 g/l VOC.