



# WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Liberon**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Liberon Garden ColourCare Decorative Woodstain](#)



# Garden ColourCare® DECORATIVE WOODSTAIN

- *Highly resistant formula for extreme weather conditions*
- *Non-drip formula*
- *Waterproof and UV resistant*

**Garden ColourCare DECORATIVE WOODSTAIN** is ideal for all exterior and interior woodwork: shutters, gates, fences, windows or beams. For most types of European and exotic woods, new or old: Oak, Softwood, Larch, Douglas, Red Cedar. Suitable on most old woodstains

**APPLICATION:** Brush, roller or spray  
**DRYING TIME:** 3H recoat – 12H fully dry  
**COVERAGE:** 12 m<sup>2</sup>/L  
**TOOL CLEANING:** Water

## PREPARATION

Ensure the surface is clean, dry and non-greasy. Sand angles and edges to lightly round off.

**BARE WOODS:** Sand to obtain a smooth surface and remove dust. Apply a suitable wood treatment product.

**BARE Hardwoods (OAK, CHESTNUT, LARCH, DOUGLAS, RED CEDAR, EXOTIC):** dilute the first coat with 15% water and apply a non-diluted second coat. (avoid a generous application). On greasy wood, degrease the surface before application.

**STAINED WOODS:** Brush to remove any loose or flaking finishes. Use sandpaper to obtain a smooth surface and remove dust.

**BLACKENED WOODS:** Apply Liberon Wood Bleacher or apply a suitable undercoat to affected area.

## APPLICATION

Ideal application conditions: between 12° and 25°C, in dry weather. We wouldn't recommend applying Decorative Woodstain in strong winds or when bad weather is forecast.

Stir the product well before and during use using a wide stick. Apply in 2 coats. For a spray application, dilute the Woodstain with 10% water.

**Hardwoods:** Sand lightly between the 2 coats. Important: always test the product on a small or inconspicuous area for colour, compatibility and end result.

Do not apply on heat treated woods, thermo treated woods or acidic woods. For bright colours on new or exposed woods, it may be necessary to apply a 3rd coat.

## 8 YEAR GUARANTEE

The eight year guarantee applies for new wood, wood to renovate and usual wood species when product is applied according to preparation and application instructions. Exposition: only vertical surfaces. For South and South-West exposition: apply 3 coats. The guarantee is limited to refunding of the product (presentation of the receipt and the tin) and concerns only the aspect of the paint.

## HEALTH AND SAFETY

DO NOT ALLOW TO FREEZE

EUH208: Contains Benzisothiazolinone. May produce an allergic reaction.

P102: Keep out of reach of children.

P271: Use only outdoors or in a well-ventilated area.

P501: Dispose of contents / container at a waste collection centre (contact the local authority).

EU limit value for this product (cat. A/e): 130g/l (2010). This product contains max 4 g/l VOC.