



# WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Liberon**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Liberon Garden ColourCare Shed and Building Paint](#)



## Garden ColourCare® SHED & BUILDING PAINT

- *Intense colours for sheds, summer houses, gazebos and other exterior timbers*
- *2 in 1: decorates and protects, quality and highly durable finish*



**Garden ColourCare SHED & BUILDING PAINT** is ideal for exterior wood : sheds, summer houses, gazebos, windows, doors, conservatories, cladding... For all types of European and exotic wood, new or old.

### PREPARATION

For timber previously treated with Sealer/Paint/Woodstain. To ensure a perfect finish, please sand and remove any existing Sealer, Paint or Woodstain to expose the original bare wood.

Ensure the wood is dust-free. Raw Wood has to be treated.

Oak, chestnut, larch and other exotic woods: dilute the first coat diluted with 15% water and apply a second non-diluted coat. On greasy wood, degrease the surface with denatured alcohol before application.

### APPLICATION

Ideal application conditions: between 12° and 25°C, in dry weather. We wouldn't recommend applying Building & Shed Paint in strong winds and when bad weather is forecast.

- Stir the product well before and during use.
- Ensure the product is mixed thoroughly.
- Apply in 2 coats. For a spray application, dilute the paint with 10% water.

Hardwoods: sand lightly between the 2 coats.

Important : always test product on a small or inconspicuous area for colour, compatibility and end result.

### 8 YEAR GUARANTEE

The eight year guarantee applies for new wood, wood to renovate and usual wood species when product is applied according to preparation and application instructions. Exposition: only vertical surfaces. For South and South-West exposition: apply 3 coats. The guarantee is limited to refunding of the product (presentation of the receipt and the tin) and concerns only the aspect of the paint.

### HEALTH AND SAFETY

This product should be used in accordance with the manufacturer's instructions. Recommendations are for guidance only. **DO NOT ALLOW TO FREEZE**

EUH208: Contains Benzisothiazolinone. May produce an allergic reaction. P102: Keep out of reach of children.

P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents / container at a waste collection centre (contact the local authority). EU limit value for this product (cat. A/e) : 130g/l (2010).

This product contains max 3 g/l VOC.

**APPLICATION:** Brush, roller or spray  
**DRYING TIME:** 3H recoat – 12H fully dry  
**COVERAGE:** 12 m<sup>2</sup>/L  
**TOOL CLEANING:** Water

