



**WOOD
FINISHES
DIRECT**



Finish. Finished.

The following Product Datasheet is provided by **Liberon**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Liberon Hard Wax Oil](#)



Hard Wax Oil

- Blend of premium quality oil and wax for protecting wooden flooring and furniture
- Makes surfaces waterproof and stain resistant
- Ideal for use throughout the home
- Provides a long lasting smooth and durable finish
- Maintains the natural look of the wood



USAGE

Interior

COVERAGE

1 Litre

14 m²

APPLICATION

Brush or roller

DRYING TIME

8 hours per coat, 24 hours final

TOOL CLEANING

Water

Product use

Liberon Hard Wax Oil is a blend of premium quality oil and wax to give superior protection to wooden flooring and furniture. Maintaining the natural look of the wood, it forms a highly durable barrier on soft and hardwoods against water, stains, heat, dirt and wear and tear. It is especially suited to humid environments such as kitchens and bathrooms, but can be used throughout the home and the product can be applied to bare wood or previously oiled wood. The matt or satin finish is washable with mild detergent and tools can be easily cleaned with water. Hard Wax Oil is pleasant to use and does not have a strong odour.

Preparation

The wood must be bare, clean and dry.

Varnished, painted or waxed wood: Remove all old varnish, paint or wax with stripper or sand the surface back to bare wood. Clean and remove all dust.

Oiled wood: Sand lightly with 240 grit paper and remove all dust.

Bare wood: Clean, sand lightly with 240 grit paper and remove all dust.

Application

Stir the contents of the tin well before use.

Apply the first coat thinly with a brush or roller and leave to dry for 8 hours. Then sand with 240 grit paper and remove all dust. Apply a second coat in the same way as the first and leave to dry for 24 hours. Whilst the product is drying, do not allow any textile fibres to come into contact with it.



Important: The final finish can vary depending on the type of wood, especially with hardwoods. Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.

Cleaning and maintenance

The treated surface can be washed with mild detergents.

Precautions

- Wear suitable clothing and protective gloves.
- It is advisable to avoid allowing water to sit on the surface of the treated wood during the immediate 3 weeks after application. This will give the product time to fully cure.
- If a small area becomes worn, sand the area lightly with 240 grit paper and remove all dust. Then apply another coat of Hard Wax Oil to the area and leave to dry for 24 hours.
- Recommended temperature for application: minimum 12°C. Drying time may be increased in cooler conditions.

Health and Safety

EUH208: Contains Benzisothiazolinone and methyl ethyl ketoxime. May produce an allergic reaction.

P102: Keep out of reach of children.

P271: Use only in a well ventilated area.

P501: Dispose of contents/container to a waste collection center

Do not allow to freeze.

Oily cloths can self combust. Do not leave impregnated cloths in bundles. Before discarding lay them flat outside to dry to avoid a fire hazard.

VOC information

EU limit for this product (Cat A/i): 140g/L (2010)

This product contains max 24g/L VOC.

This product should be used in accordance with the manufacturer's instructions.

Recommendations are for guidance only since conditions of use are completely beyond our control. For technical advice please contact us on 01797 367555.

Liberon Limited
Mountfield Industrial Estate
New Romney
Kent
TN28 8XU

Tel: 01797 367555

Fax: 01797 367575

www.liberon.co.uk

Liberon Ltd is a V33 Group Company.