



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Liberon**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Liberon Home ColourCare Decorative Floor Varnish](#)



Home
Colourcare

DECORATIVE FLOOR VARNISH



Format: 1L + 2.5L

- **Highly Durable Protection**
- **Decorative colour finish**
- **No undercoat required**
- **Available in 6 colours**

Home ColourCare **DECORATIVE FLOOR VARNISH** is ideal for decorating and protecting wooden and laminate floors, with no need to strip them back to bare wood.

- Excellent adhesion with no stripping or undercoat required.
- Creates a contemporary and innovative look.
- Resistant to traffic and stains.

Can be used on varnished and pre-varnished wooden floors made from European or exotic species and laminates.

APPLICATION: Brush or roller

DRYING TIME: 3h recoat/12h fully dry

COVERAGE: 2.5L = 30m²

TOOL CLEANING: Water

PREPARATION

Preparation of the surface is **ESSENTIAL**. The prepared surface must be clean, dry and free of grease.

- **BARE WOODEN FLOORS:** sand lightly (120 grit abrasive) and remove all dust.
 - **VARNISHED, PRE-VARNISHED OR PAINTED WOODEN FLOORS:**
 - In good condition: wash, rinse and leave to dry. Sand lightly (240 grit abrasive) and remove dust.
 - Partially worn condition: sand back to bare wood and remove dust.
 - **WAXED OR OILED WOODEN FLOORS:** remove wax using a cleaner then mechanically sand twice (once with 60 abrasive grit then 120) until bare wood is reached. Remove dust carefully.
 - **LAMINATE FLOORING:** wash, rinse and leave to dry. Sand lightly (240 grit abrasive) and remove dust.
- Any grease or film can stop the paint from adhering properly. Washing the surface is therefore essential. Use a sugar soap cleaner.



Home
Colourcare

DECORATIVE FLOOR VARNISH



Format : 1L + 2.5L

APPLICATION

Ideal application conditions: between 12 and 25°C, in dry weather.

- Stir the floor varnish before and during use with a long wide stick, working around the bottom of the tin to mix thoroughly.
- Apply the varnish using a soft-bristled brush or 3 to 5 mm short pile roller.
- Apply the varnish in regular, criss-cross strokes and spread evenly. Finish in the direction of the grain.
- Leave to dry for 3 hours.
- Apply the second coat of varnish. Apply a third coat if necessary.
- Leave to dry for 12 hours. Use the room with care in the first few days following application of the varnish. Optimal resistance is obtained after two weeks.

HEALTH AND SAFETY

This product should be used in accordance with the manufacturer's instructions. Recommendations are for guidance only since conditions of use are completely beyond our control.

DO NOT ALLOW TO FREEZE

EUH208: Contains 2-methyl-2H-isothiazole-3-one and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

P102: Keep out of reach of children.

P271: Use only outdoors or in a well-ventilated area.

P501: Dispose of contents / container at a waste collection centre (contact the local authority).