

The following Safety Datasheet is provided by **Liberon** 

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: Liberon Natural Finish Floor Varnish

# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name: LIBERON - NATURAL FINISH FLOOR VARNISH - Clear Satin - 1L

Product code: 126853

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Floor Varnish

## 1.3. Details of the supplier of the safety data sheet

Registered company name: LIBERON Ltd

Address: .Mountfield Industrial Estate KENT TN28 8XU NEW ROMNEY GB Telephone: + (44) 1797 367 555. Fax: + (44) 1797 367 575. Telex: .

fds.produits@v33.com www.liberon.co.uk

# 1.4. Emergency telephone number : .

Association/Organisation: .

#### Other emergency numbers

UK/NI: 111 - Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

Republic of Ireland: +353 (0)1 809

2166 - Emergency medical information: 8am-10pm (seven days) contact NPIC, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

#### **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1. Classification of the substance or mixture

# In compliance with EC regulation No. 1272/2008 and its amendments.

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

## 2.2. Label elements

# In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling:

EUH208 Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.

EUH208 Contains REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H

-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction.

Precautionary statements - General :

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P271 Use only outdoors or in a well-ventilated area.

Precautionary statements - Disposal:

P501 Dispose of contents/container to a waste collection center (contact the local authority)

## 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European

CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

## 3.2. Mixtures

# Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 613_088_006B	GHS06, GHS05, GHS09		0 <= x % < 0.036
CAS: 2634-33-5	Dgr		
EC: 220-120-9	Acute Tox. 4, H302		
	Skin Irrit. 2, H315		

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)  LIBERON - NATURAL FINISH FLOOR VARNISH - Clear Satin - 1L - 126853		Version 1.1 (13-12-2022) - Page 2/8
1,2-BENZISOTHIAZOL-3(2H)-ONE	Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Chronic 2, H411 Aquatic Acute 1, H400 M Acute = 1	
INDEX: Z117 CAS: 55965-84-9 REACH: 01-2120764691-48  REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLI N-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1)	GHS06, GHS05, GHS09 Dgr Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 M Acute = 100 Aquatic Chronic 1, H410 M Chronic = 100	0 <= x % < 0.0015

# Specific concentration limits:

Identification	Specific concentration limits	ATE
INDEX: 613_088_006B	Skin Sens. 1: H317 C>= 0.05%	
CAS: 2634-33-5		
EC: 220-120-9		
1,2-BENZISOTHIAZOL-3(2H)-ONE		
INDEX: Z117	Eye Dam. 1: H318 C>= 0.25%	
CAS: 55965-84-9	Eye Irrit. 2: H319 0.025% <= C <	
REACH: 01-2120764691-48	0.25%	
	Skin Sens. 1A: H317 C>= 0.0015%	
REACTION MASS OF:		
5-CHLORO-2-METHYL-4-ISOTHIAZOLI		
N-3-ONE AND 2-METHYL-2H		
-ISOTHIAZOL-3-ONE (3:1)		

# Information on ingredients:

(Full text of H-phrases: see section 16)

# **SECTION 4: FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

# 4.1. description of first aid measures

# In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

# In the event of splashes or contact with skin:

In the event of an allergic reaction, seek medical attention.

# In the event of swallowing:

Seek medical attention, showing the label.

# 4.2. Most important symptoms and effects, both acute and delayed

No data available.

# 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

# **SECTION 5: FIREFIGHTING MEASURES**

Non-flammable.

# 5.1. Extinguishing media

# Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist

- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

## Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

# 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

## 5.3. Advice for firefighters

No data available

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

# 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

#### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

## 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

#### 6.4. Reference to other sections

No data available.

# **SECTION 7: HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

# 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

## Fire prevention:

Prevent access by unauthorised personnel.

# Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

# Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

# 7.2. Conditions for safe storage, including any incompatibilities

No data available.

# Storage

Keep out of reach of children.

Do not allow to freeze

# **Packaging**

Always keep in packaging made of an identical material to the original.

# 7.3. Specific end use(s)

No data available.

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

# 8.1. Control parameters

No data available.

## 8.2. Exposure controls

# Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

#### - Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

#### - Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1. Information on basic physical and chemical properties Physical state

Fluid liquid.
Not stated.
Not relevant.
Not stated.
Not relevant.
Not stated.
Not stated.
Not stated.
Not relevant.
Not relevant.
Not relevant.
Not stated.
8.50 .
Slightly basic.
Not stated.
Dilutable.

Not stated.

Fat solubility:

# Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water:	Not stated.
Vapour pressure	
Vapour pressure (50°C):	Not relevant.
Density and/or relative density	
Density:	>1
Relative vapour density	
Vapour density :	Not stated.

#### 9.2. Other information

No data available.

# 9.2.1. Information with regard to physical hazard classes

No data available.

## 9.2.2. Other safety characteristics

No data available

## **SECTION 10: STABILITY AND REACTIVITY**

#### 10.1. Reactivity

No data available.

# 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

#### 10.3. Possibility of hazardous reactions

No data available.

## 10.4. Conditions to avoid

Avoid:

- frost

# 10.5. Incompatible materials

No data available.

## 10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

# **SECTION 11: TOXICOLOGICAL INFORMATION**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No data available.

# 11.1.1 Substances

# Acute toxicity:

REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)

Oral route : LD50 > 2000 mg/kg

Dermal route: LD50 > 5000 mg/kg

# 11.1.2. Mixture

# Respiratory or skin sensitisation:

Contains at least one sensitising substance. May cause an allergic reaction.

11.2. Information on other hazards

# **SECTION 12: ECOLOGICAL INFORMATION**

# 12.1. Toxicity

# 12.1.1 Substances

REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)

Fish toxicity: LC50 = 0.22 mg/l

Factor M = 1

Species : Oncorhynchus mykiss Duration of exposure : 96 h SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version 1.1 (13-12-2022) - Page 6/8

LIBERON - NATURAL FINISH FLOOR VARNISH - Clear Satin - 1L - 126853

OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

Crustacean toxicity: EC50 = 0.1 mg/l

Factor M = 10

Species : Daphnia magna Duration of exposure : 48 h

OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

Algae toxicity: ECr50 = 0.0052 mg/l

Factor M = 100

Species : Skeletonema costatum Duration of exposure : 48 h

OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

EC50 mg/l Factor M = 10

Species : Skeletonema costatum Duration of exposure : 48 h

ISO 10253 (Essai d'inhibition de la croissance des algues marines avec

Skeletonema costatum et Phaeodactylum tricornutum)

NOEC = 0.00064 mg/l Factor M = 100

Species : Skeletonema costatum Duration of exposure : 48 h

ISO 10253 (Essai d'inhibition de la croissance des algues marines avec

Skeletonema costatum et Phaeodactylum tricornutum)

# 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

#### 12.2. Persistence and degradability

#### 12.2.1. Substances

REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)

Biodegradability: no degradability data is available, the substance is considered as not

degrading quickly.

1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5)

Biodegradability: Rapidly degradable.

# 12.3. Bioaccumulative potential

## 12.3.1. Substances

REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)

Octanol/water partition coefficient : log Koe <= 0.71

OCDE Ligne directrice 117 (Coefficient de partage (n-octanol/eau), méthode

HPLC)

Bioaccumulation : BCF = 3.16

# 12.4. Mobility in soil

No data available.

## 12.5. Results of PBT and vPvB assessment

No data available.

# 12.6. Endocrine disrupting properties

No data available.

## 12.7. Other adverse effects

No data available.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

# 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

# **SECTION 14: TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

14.1. UN number or ID number

-

14.2. UN proper shipping name

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Maritime transport in bulk according to IMO instruments

-

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

- Container information:

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): https://echa.europa.eu/substances-restricted-under-reach.

- Particular provisions :

No data available.

# 15.2. Chemical safety assessment

No data available.

## **SECTION 16: OTHER INFORMATION**

guarantee of the properties thereof.

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a

# Wording of the phrases mentioned in section 3:

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)	Version 1.1 (13-12-2022) - Page 8/8
LIBERON - NATURAL FINISH FLOOR VARNISH - Clear Satin - 1L - 126853	

H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

# Abbreviations:

LD50: The dose of a test substance resulting in 50% lethality in a given time period.

LC50: The concentration of a test substance resulting in 50% lethality in a given period.

EC50: The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

NOEC: The concentration with no observed effect.

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

STEL : Short-term exposure limit TWA : Time Weighted Averages

TMP : French Occupational Illness table TLV : Threshold Limit Value (exposure)

AEV: Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.