

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: TRADITIONAL OIL GLOSS
Product code	: DP1
Type of product	: Paint
Product group	: End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category	: Consumer use
Function or use category	: Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

The Little Greene Paint Company Ltd
The Coach Works
420 Ashton Old Road
M11 2DT Manchester
United Kingdom
T +44 (0)161 230 0880, F +44 (0)161 223 3208
mail@thelittlegreene.com

1.4. Emergency telephone number

Emergency number	: +44 (0)1248 600315 (Office hours only)
------------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)	: 
	GHS02

Signal word (CLP)	: Warning
-------------------	-----------

Hazard statements (CLP)	: H226 - Flammable liquid and vapour.
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting equipment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

EUH-statements : EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH208 - Contains 2-BUTANONE OXIME (96-29-7) (350). May produce an allergic reaction.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY substance with national workplace exposure limit(s) (PL, CH); substance with a Community workplace exposure limit	CAS-No.: 64742-48-9 EC-No.: 265-150-3 EC Index-No.: 649-327-00-6 REACH-no: 01-2119463258-33	26.99775 – 27.34475	Flam. Liq. 3, H226 Asp. Tox. 1, H304
TITANIUM DIOXIDE substance with national workplace exposure limit(s) (AT, BE, BG, DK, EE, ES, GB, GR, HR, IE, LT, LV, PL, PT, RO, SE, SK, IS, NO, CH)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2 REACH-no: 01-2119489379-17	10 – 30	Not classified
XYLENE substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9	< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Aquatic Chronic 2, H411
2-BUTANONE OXIME substance with national workplace exposure limit(s) (DE, IE, SI)	CAS-No.: 96-29-7 EC-No.: 202-496-6 EC Index-No.: 616-014-00-0 REACH-no: 01-2119539477-28	< 5	Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 1, H370 STOT SE 3, H336 STOT RE 2, H373
Calcium Carbonate substance with national workplace exposure limit(s) (FR, HR, LV, PL, CH)	CAS-No.: 471-34-1 EC-No.: 207-439-9	0.122 – 0.244	Aquatic Chronic 3, H412

Full text of H- and EUH-statements: see section 16

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
Self protection of the first-aider	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	--

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking.

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

6.3. Methods and material for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.
- Packaging materials : Store always product in container of same material as original container.

Germany

Storage class (LGK, TRGS 510)

Joint storage table

: LGK 3 - Flammable liquids

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

: LGK 1, LGK 2A, LGK 4.1A, LGK 4.1B, LGK 4.2, LGK 4.3, LGK 5.1A, LGK 5.1C, LGK 5.2, LGK 6.1B, LGK 6.2, LGK 7

Joint storage with restrictions permitted for

: LGK 5.1B, LGK 6.1D, LGK 11, LGK 10-13

Joint storage permitted for

: LGK 2B, LGK 3, LGK 6.1A, LGK 6.1C, LGK 8A, LGK 8B, LGK 10, LGK 12, LGK 13

Switzerland

Storage class (LK)

: LK 3 - Flammable liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	White spirit Type 3
------------	---------------------

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
IOEL TWA	116 mg/m ³
	20 ppm
IOEL STEL	290 mg/m ³
	50 ppm
Remark	Skin. (Year of adoption 2007)
Regulatory reference	SCOEL Recommendations
Poland - Occupational Exposure Limits	
Local name	Benzyna do lakierów
NDS (OEL TWA)	300 mg/m ³
NDSch (OEL STEL)	900 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286 wraz z późn. zm.
Switzerland - Occupational Exposure Limits	
Local name	Naphta lourd (pétrole), hydrotraité / Naphtha (Erdöl), mit Wasserstoff behandelte, schwere
MAK (OEL TWA)	300 mg/m ³
	50 ppm
KZGW (OEL STEL)	600 mg/m ³
	100 ppm
Critical toxicity	SNC / ZNS
Regulatory reference	www.suva.ch, 01.01.2023
XYLENE (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m ³
	50 ppm
IOEL STEL	442 mg/m ³
	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Austria - Occupational Exposure Limits	
Local name	Xylol (alle Isomeren): Xylol
MAK (OEL TWA)	221 mg/m ³
	50 ppm
MAK (OEL STEL)	442 mg/m ³ (4x 15(Miw) min)
	100 ppm (4x 15(Miw) min)
Regulatory reference	BGBI. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Xylène, isomères mixtes, purs # Xyleen, mengsel van isomeren, zuiver
OEL TWA	221 mg/m ³

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

XYLENE (1330-20-7)	
	50 ppm
OEL STEL	442 mg/m ³
	100 ppm
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	Ксилен (смес от изомери), чист
OEL TWA	221 mg/m ³
	50 ppm
OEL STEL	442 mg/m ³
	100 ppm
Remark	Кожа (възможна е значителна резорбция чрез кожата); • (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	Ksilen (svi izomeri)
GVI (OEL TWA)	221 mg/m ³
	50 ppm
KGV I (OEL STEL)	442 mg/m ³
	100 ppm
Remark	Direktiva: 2000/39/EZ. Napomena: Koža (razvrstana kao tvar koja nadražuje kožu (H315))
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
Croatia - Biological limit values	
Local name	Ksilen
BLV	14.13 µmol/l Karakteristični pokazatelj: ksilen - Biološki uzorak: krv - Vrijeme uzorkovanja: na kraju radne smjene - Napomena: uzimanje alkohola prije izloženosti ksilenu povisuje nalaz 1.5 mg/l Karakteristični pokazatelj: ksilen - Biološki uzorak: krv - Vrijeme uzorkovanja: na kraju radne smjene - Napomena: uzimanje alkohola prije izloženosti ksilenu povisuje nalaz 0.88 mol/mol Creatinine Karakteristični pokazatelj: metilhipurna kiselina - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene 1.5 g/g creatinine Karakteristični pokazatelj: metilhipurna kiselina - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/2018)
Cyprus - Occupational Exposure Limits	
Local name	Ξυλένιο, μικτά ισομερή, καθαρά

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

XYLENE (1330-20-7)	
OEL TWA	221 mg/m ³
	50 ppm
OEL STEL	442 mg/m ³
	100 ppm
Remark	δέρμα
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)
Czech Republic - Occupational Exposure Limits	
Local name	Xylen technická směs isomerů a všechny isomery
PEL (OEL TWA)	200 mg/m ³
	45 ppm
NPK-P (OEL C)	400 mg/m ³
	90 ppm
Remark	B - u látky je zaveden biologický expoziční test (BET) v moči nebo krvi, D - při expozici se významně uplatňuje pronikání faktoru kůží, I - dráždí sliznice (oči, dýchací cesty), respektive kůží.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Czech Republic - Biological limit values	
Local name	Xyleny
BLV	1400 mg/g creatinine Ukazatel: Methylhippurová kyselina - Biologický vzorek: moči - Doba odběru: konec směny 820 μmol/mmol Creatinine Ukazatel: Methylhippurová kyselina - Biologický vzorek: moči - Doba odběru: konec směny
Regulatory reference	Vyhláška č. 107/2013 Sb. (kterou se mění vyhláška č. 432/2003 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Xylen (Dimethylbenzen), alle isomere
OEL TWA	109 mg/m ³
	25 ppm
OEL STEL	442 mg/m ³
	100 ppm
Remark	E (betyder, at stoffet har en EF-grænseværdi); H (betyder, at stoffet kan optages gennem huden)
Regulatory reference	BEK nr 202 af 21/02/2023
Estonia - Occupational Exposure Limits	
Local name	Ksüleen (dimetüülbenseen)
OEL TWA	200 mg/m ³
	50 ppm
OEL STEL	450 mg/m ³
	100 ppm
Remark	A (Naha kaudu kergesti imenduv aine)
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 21.12.2022, 3)

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

XYLENE (1330-20-7)	
Finland - Occupational Exposure Limits	
Local name	Ksyleeni
HTP (OEL TWA)	220 mg/m ³
	50 ppm
HTP (OEL STEL)	440 mg/m ³
	100 ppm
Remark	Iho
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
Finland - Biological limit values	
Local name	Ksyleeni
BLV	5 mmol/l Parametri: Virtsan metyylhippuurihappo - Näytteenottoajankohta: Työvuoron päätyttyä
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
Germany - Biological limit values (TRGS 903)	
Local name	Xylol (alle Isomere)
Biological limit value	2000 mg/l Parameter: Methylhippur-(Tolur-) säure (alle Isomere) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2016 DFG
Regulatory reference	TRGS 903
Gibraltar - Occupational Exposure Limits	
Local name	Xylene, mixed isomers, pure
OEL TWA	221 mg/m ³
	50 ppm
OEL STEL	442 mg/m ³
	100 ppm
Remark	Skin
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
Greece - Occupational Exposure Limits	
Local name	Ξυλόλια (όλα τα ισομερή)
OEL TWA	435 mg/m ³
	100 ppm
OEL STEL	650 mg/m ³
	150 ppm
Remark	Η ένδειξη «δέρμα» στις οριακές τιμές επαγγελματικής έκθεσης επισημαίνει το ενδεχόμενο σημαντικής διείσδυσης μέσω του δέρματος.
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	XILOL izomerek keveréke
AK (OEL TWA)	221 mg/m ³
CK (OEL STEL)	442 mg/m ³

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

XYLENE (1330-20-7)	
Remark	b (Bőrön át is felszívódik), BEM (biológiai expozíciós mutató); EU1 (2000/39/EK irányelvben közölt érték); R (Azok az anyagok, amelyek egészségkárosító hatása RÖVID expozíció hatására jelentkeznek)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Hungary - Biological Exposure Indices	
Local name	Xilol
BEI	1500 mg/g creatinine Biológiai expozíciós (hatás) mutató: metilhippursavak - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén) 860 µmol/mmol Creatinine Biológiai expozíciós (hatás) mutató: metilhippursavak - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Xylene, mixed isomers
OEL TWA	221 mg/m ³
	50 ppm
OEL STEL	442 mg/m ³
	100 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
Ireland - Biological limit values	
Local name	Xylene
BMGV	1.5 g/g creatinine Parameter: methylhippuric acids - Medium: urine - Sampling time: End of Shift
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
Italy - Occupational Exposure Limits	
Local name	Xilene, isomeri misti, puro
OEL TWA	221 mg/m ³
	50 ppm
OEL STEL	442 mg/m ³
	100 ppm
Remark	Cute
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Latvia - Occupational Exposure Limits	
Local name	Ksilols (o-,m-,p-ksilols, dimetilbenzols)
OEL TWA	221 mg/m ³
	50 ppm
OEL STEL	442 mg/m ³
	100 ppm

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

XYLENE (1330-20-7)	
Remark	Āda
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325
Lithuania - Occupational Exposure Limits	
Local name	Ksilenas, mišrūs izomerai, grynās
IPRV (OEL TWA)	221 mg/m ³
	50 ppm
TPRV (OEL STEL)	442 mg/m ³
	100 ppm
Remark	O (medžiaga į organizmą gali prasiskverbti pro nepažeistą odą)
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	Xylène, isomères mixtes, purs
OEL TWA	221 mg/m ³
	50 ppm
OEL STEL	442 mg/m ³
	100 ppm
Remark	Peau
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	Xylene, mixed isomers, pure # Xylene, Isomeri mhallta, puri
OEL TWA	221 mg/m ³
	50 ppm
OEL STEL	442 mg/m ³
	100 ppm
Remark	Skin # Ġilda
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)
Netherlands - Occupational Exposure Limits	
Local name	Xyleen, o-, m-, p-isomeren
TGG-8u (OEL TWA)	210 mg/m ³
	47.5 ppm
TGG-15min (OEL STEL)	442 mg/m ³
	100 ppm
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2023
Poland - Occupational Exposure Limits	
Local name	Ksilen mieszanina izomerów: 1,2-; 1,3-; 1,4-

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

XYLENE (1330-20-7)	
NDS (OEL TWA)	100 mg/m ³
NDSch (OEL STEL)	200 mg/m ³
Remark	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286 wraz z późn. zm.
Portugal - Occupational Exposure Limits	
Local name	Xileno (isómeros)
OEL TWA	100 ppm
OEL STEL	150 ppm
Remark	A4 (Agente não classificável como carcinogénico no Homem); IBE (Índice biológico de exposição)
Regulatory reference	Norma Portuguesa NP 1796:2014
Portugal - Biological Exposure Indices	
Local name	Xilenos (graus técnico e comercial)
BEI	1.5 g/g creatinine Parâmetro: Ácidos (o, m, p)-metilhipúricos - Meio: urina - Momento da amostragem: Fim do turno
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Xilen, izomer mixt, pur
OEL TWA	221 mg/m ³
	50 ppm
OEL STEL	442 mg/m ³
	100 ppm
Remark	P - posibilitatea unei penetrări cutanate importante
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Romania - Biological limit values	
Local name	Xilen
BLV	3 g/l Indicador biologic: Acid metilhipuric - Material biologic: urină - Momentul recoltării: sfârșit schimb
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 584/2018)
Serbia - Occupational Exposure Limits	
Local name	ксилен, мешани изомери, чист
OEL TWA	221 mg/m ³
	50 ppm
OEL STEL	442 mg/m ³
	100 ppm
Remark	ЕУ* – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2000/39/ЕЗ (прва листа); К – напомена да хемијска материја може штетно деловати на кожу
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09, 117/17 и 107/21)

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

XYLENE (1330-20-7)	
Slovakia - Occupational Exposure Limits	
Local name	Xylén, zmiešané izoméry
NPHV (OEL TWA)	221 mg/m ³
	50 ppm
NPHV (OEL STEL)	442 mg/m ³
	100 ppm
Remark	K - znamená, že faktor môže byť ľahko absorbovaný kožou
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovakia - Biological limit values	
Local name	Xylén (všetky izoméry)
BLV	1.5 mg/l Zisťovaný faktor: Xylén - Vyšetrovaný materiál: krv - Čas odberu vzorky: b) koniec expozície alebo pracovnej zmeny 2000 mg/l Zisťovaný faktor: Suma kyselín 2,3,4-metyl-hippurových - Vyšetrovaný materiál: moč - Čas odberu vzorky: b) koniec expozície alebo pracovnej zmeny
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (Zmena: 471/2011 Z.z.)
Slovenia - Occupational Exposure Limits	
Local name	ksilen (mešane izomere)
OEL TWA	221 mg/m ³
	50 ppm
OEL STEL	442 mg/m ³
	100 ppm
Remark	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), BAT (Biološka mejna vrednost), EU
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Slovenia - Biological limit values	
Local name	ksilen (vse izomere)
BLV	2 g/l Parameter: metilhipurna kislina (vse izomere) - Biološki vzorec: urin - Čas vzorčenja: ob koncu delovne izmene
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	Xileno, mezcla isómeros
VLA-ED (OEL TWA)	221 mg/m ³
	50 ppm
VLA-EC (OEL STEL)	442 mg/m ³
	100 ppm
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLB® (Agente químico que tiene Valor Límite Biológico), VLI (Agente químico para el que la U.E. estableció en su día un valor Límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

XYLENE (1330-20-7)	
Spain - Biological limit values	
Local name	Xilenos, mezcla isómeros
BLV	1 g/g creatinine Parámetro: Ácidos metilhipúricos - Medio: Orina - Momento de muestreo: Final de la jornada laboral
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT
Sweden - Occupational Exposure Limits	
Local name	Xylen
NGV (OEL TWA)	221 mg/m ³
	50 ppm
KGV (OEL STEL)	442 mg/m ³
	100 ppm
Remark	H (Ämnet kan lätt upptas genom huden. Det föreskrivna gränsvärdet bedöms ge tillräckligt skydd endast under förutsättning att huden är skyddad mot exponering för ämnet ifråga)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Xylene
WEL TWA (OEL TWA)	220 mg/m ³ o-,m-,p- or mixed isomers
	50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m ³ o-,m-,p- or mixed isomers
	100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	Xýlen, allir ísómerar (dímetýlbensen)
OEL TWA	109 mg/m ³
	25 ppm
OEL STEL	442 mg/m ³
	100 ppm
Remark	H (efnið getur auðveldlega borist inn í líkamann gegnum húð)
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	Xylen (alle isomere)
Grenseverdi (OEL TWA)	108 mg/m ³
	25 ppm

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

XYLENE (1330-20-7)	
Remark	H: Kjemikalier som kan tas opp gjennom huden; E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet.
Regulatory reference	FOR-2021-06-28-2248
North Macedonia - Occupational Exposure Limits	
Local name	ксилен (смеша од изомери)
OEL TWA	221 mg/m ³
	50 ppm
KTV	2
Short time value [mg/m ³]	442 mg/m ³
Short time value [ppm]	100 ppm
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (K) својство на полесно пренесување на супстанциите во организмот преку кожата; (BAT) биолошка гранична вредност – праг на биолошка гранична вредност, што значи предупредување на опасна хемиска супстанца и нејзини метаболити во ткивата, телесните течности или издишувањето на воздухот, без оглед на тоа, дали опасната хемиска супстанца е внесена во организмот со вдишување, голтање или преку кожата; (EU) European Union – гранична вредност, определена на ниво на Европската унија
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	Xylène (tous les isomères) / Xylol (alle Isomere)
MAK (OEL TWA)	220 mg/m ³
	50 ppm
KZGW (OEL STEL)	440 mg/m ³
	100 ppm
Critical toxicity	SNC / ZNS
Notation	R, B / H, B
Remark	INRS, NIOSH
Regulatory reference	www.suva.ch, 01.01.2023
Switzerland - BAT	
Local name	Xylène (tous les isomères) / Xylol (alle Isomere)
BAT	2 g/l (Paramètre biologique: Acides méthylhippuriques; Substrat d'examen: Urine; Moment du prélèvement: Fin de l'exposition, de la période de travail.) / (Biologischer Parameter: Methylhippursäuren; Untersuchungsmaterial: Urin; Probennahmezeitpunkt: Expositionsende, bzw. Schichtende.)
Regulatory reference	Ordonnance 832.30 (OPA), article 50 al. 3, www.suva.ch/valeurs-limites / Verordnung 832.30 (VUV), Art. 50 Abs. 3, www.suva.ch/grenzwerte

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

XYLENE (1330-20-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
ACGIH® TLV® TWA	20 ppm
Remark (ACGIH®)	TLV® Basis: URT & eye irr; hematologic eff; ototoxicity (for mixtures containing p-xylene); CNS impair. Notations: OTO (for mixtures containing p-xylene); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2023
USA - ACGIH - Biological Exposure Indices	
Local name	XYLENES (Technical or commercial grade)
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2023
TITANIUM DIOXIDE (13463-67-7)	
Austria - Occupational Exposure Limits	
Local name	Titandioxid (Alveolarstaub)
MAK (OEL TWA)	5 mg/m³ (A)
MAK (OEL STEL)	10 mg/m³ (A, 2x 60(Miw) min)
Regulatory reference	BGBI. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Titane (dioxyde de) # Titaandioxide
OEL TWA	10 mg/m³
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	Титанов диоксид
OEL TWA	10 mg/m³ (респирабилен прах)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	Titanov dioksid
GVI (OEL TWA)	10 mg/m³ U (ukupna prašina) 4 mg/m³ R (respirabilna prašina)
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
Denmark - Occupational Exposure Limits	
Local name	Titandioxid
OEL TWA	6 mg/m³ beregnet som Ti
Remark	K (betyder, at stoffet anses for at kunne være kræftfremkaldende)
Regulatory reference	BEK nr 202 af 21/02/2023
Estonia - Occupational Exposure Limits	
Local name	Titaanoksiid

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

TITANIUM DIOXIDE (13463-67-7)	
OEL TWA	5 mg/m ³
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 21.12.2022, 3)
Greece - Occupational Exposure Limits	
Local name	Τιτανίου διοξείδιο
OEL TWA	10 mg/m ³ εισπν. 5 mg/m ³ σναπν.
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Ireland - Occupational Exposure Limits	
Local name	Titanium dioxide
OEL TWA	10 mg/m ³ total inhalable dust 4 mg/m ³ respirable dust
Regulatory reference	Chemical Agents Code of Practice 2021
Latvia - Occupational Exposure Limits	
Local name	Titāna dioksīds
OEL TWA	10 mg/m ³
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2011. gada 1. februārī noteikumiem Nr. 92)
Lithuania - Occupational Exposure Limits	
Local name	Titano dioksidas
IPRV (OEL TWA)	5 mg/m ³
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Poland - Occupational Exposure Limits	
Local name	Ditlenek tytanu
NDS (OEL TWA)	10 mg/m ³ frakcja wdychalna
Remark	Frakcja wdychalna – frakcja aerozolu wnikająca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia. Obowiązuje jednocześnie oznaczanie stężeń frakcji respirabilnej krzemionki krystalicznej.
Regulatory reference	Dz. U. 2018 poz. 1286 wraz z późn. zm.
Portugal - Occupational Exposure Limits	
Local name	Dióxido de titânio
OEL TWA	10 mg/m ³
Remark	A4 (Agente não classificável como carcinogénico no Homem)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Dioxid de titan
OEL TWA	10 mg/m ³
OEL STEL	15 mg/m ³
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Slovakia - Occupational Exposure Limits	
Local name	Oxid titaničitý

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

TITANIUM DIOXIDE (13463-67-7)	
NPHV (OEL TWA)	5 mg/m ³
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Spain - Occupational Exposure Limits	
Local name	Dióxido de titanio
VLA-ED (OEL TWA)	10 mg/m ³
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT
Sweden - Occupational Exposure Limits	
Local name	Titandioxid
NGV (OEL TWA)	5 mg/m ³ totaldamm
Remark	3 (Med totaldamm menas de partiklar (aerosoler) som fastnar på ett filter i den provtagare som beskrivs i Metodserien, Provtagning av totaldamm och respirabelt damm, Metod nr 1010, Arbetarskyddsstyrelsen, numera Arbetsmiljöverket. Filterdiameteren är normalt 37 mm, men kan även vara 25 mm. Trots sitt namn provtas inte den totala mängden luftburna partiklar med denna metod)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Titanium dioxide
WEL TWA (OEL TWA)	4 mg/m ³ respirable 10 mg/m ³ total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	Títandíoxíð, sem Ti
OEL TWA	6 mg/m ³
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	Titandioksid
Grenseverdi (OEL TWA)	5 mg/m ³
Regulatory reference	FOR-2021-06-28-2248
Switzerland - Occupational Exposure Limits	
Local name	Dioxyde de titane / Titandioxid
MAK (OEL TWA)	3 mg/m ³ (a) / (a)
Critical toxicity	VRI / UAW
Notation	SS _C / SS _C
Remark	NIOSH
Regulatory reference	www.suva.ch, 01.01.2023
USA - ACGIH - Occupational Exposure Limits	
Local name	Titanium dioxide
ACGIH® TLV® TWA	0.2 mg/m ³ (Nanoscale particles. R - Respirable particulate matter) 2.5 mg/m ³ (Finescale particles. R - Respirable particulate matter)
Remark (ACGIH®)	TLV® Basis: LRT irr; pneumoconiosis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

TITANIUM DIOXIDE (13463-67-7)	
Regulatory reference	ACGIH 2023
Calcium Carbonate (471-34-1)	
Croatia - Occupational Exposure Limits	
Local name	Kalcijev karbonat
GVI (OEL TWA)	10 mg/m ³ U (ukupna prašina) 4 mg/m ³ R (respirabilna prašina)
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
France - Occupational Exposure Limits	
Local name	Calcium (carbonate de) (Calcite, Marbre, Carbonate de calcium)
VME (OEL TWA)	10 mg/m ³
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Latvia - Occupational Exposure Limits	
Local name	Kalcija karbonāts
OEL TWA	6 mg/m ³
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2011. gada 1. februārī noteikumiem Nr. 92)
Poland - Occupational Exposure Limits	
Local name	Węglan wapnia
NDS (OEL TWA)	10 mg/m ³ frakcja wdychalna
Remark	Frakcja wdychalna – frakcja aerozolu wnikająca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia.
Regulatory reference	Dz. U. 2018 poz. 1286 wraz z późn. zm.
Switzerland - Occupational Exposure Limits	
Local name	Carbonate de calcium / Calciumcarbonat
MAK (OEL TWA)	3 mg/m ³ (a) / (a)
Remark	NIOSH
Regulatory reference	www.suva.ch, 01.01.2023
2-BUTANONE OXIME (96-29-7)	
Austria - Occupational Exposure Limits	
Local name	2-Butanonoxim
Remark	Sh. Krebserzeugend: III B
Regulatory reference	BGBI. II Nr. 156/2021
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	1 mg/m ³
	0.3 ppm
Peak exposure limitation factor	8(l)
Remark	AGS - Ausschuss für Gefahrstoffe; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; H - hautresorptiv; Sh - Hautsensibilisierender Stoff

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2-BUTANONE OXIME (96-29-7)	
Regulatory reference	TRGS900
Ireland - Occupational Exposure Limits	
Local name	Methyl ethyl ketoxime
OEL TWA	10 mg/m ³
	3 ppm
OEL STEL	33 mg/m ³
	10 ppm
Remark	Sens. (In the workplace respiratory or dermal exposures to sensitising agents may occur. Sensitizers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The notation does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitizers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))
Regulatory reference	Chemical Agents Code of Practice 2021
Slovenia - Occupational Exposure Limits	
Local name	Butanonoksim
OEL TWA	1 mg/m ³
	0.3 ppm
OEL STEL	8 mg/m ³
	2.4 ppm
Remark	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti)
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Safety glasses

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Various.
Odour	: Characteristic odour.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 149 – 213 °C
Flammability	: Flammable liquid and vapour.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 43 °C
Auto-ignition temperature	: ≈ 250 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 408 mm²/s
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: ≈ 300 Pa
Vapour pressure at 50°C	: Not available
Density	: ≈ 1.15 kg/l
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

LD50 oral rat	> 5000 mg/kg
LD50 dermal	> 5000 mg/kg

XYLENE (1330-20-7)

LD50 oral rat	4300 mg/kg
LD50 oral	2119 mg/kg
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:

TITANIUM DIOXIDE (13463-67-7)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

Calcium Carbonate (471-34-1)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LC50 Inhalation - Rat	> 3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)

2-BUTANONE OXIME (96-29-7)

LD50 oral rat	930 mg/kg
LD50 oral	1 mg/kg
LD50 dermal rabbit	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 4.83 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

TITANIUM DIOXIDE (13463-67-7)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Reproductive toxicity : Not classified
STOT-single exposure : Not classified

2-BUTANONE OXIME (96-29-7)

STOT-single exposure	Causes damage to organs. May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

XYLENE (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
Calcium Carbonate (471-34-1)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	≥ 0.212 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
2-BUTANONE OXIME (96-29-7)	
LOAEL (oral, rat, 90 days)	40 mg/kg bodyweight Animal: rat, Guideline: other:
NOAEC (inhalation, rat, vapour, 90 days)	0.09 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
NOAEL (subchronic, oral, animal/male, 90 days)	110 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

TRADITIONAL OIL GLOSS	
Viscosity, kinematic	408 mm²/s
LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
Viscosity, kinematic	< 1 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'
TITANIUM DIOXIDE (13463-67-7)	
Viscosity, kinematic	Not applicable
2-BUTANONE OXIME (96-29-7)	
Viscosity, kinematic	16237.281 – 16247.834 mm²/s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

XYLENE (1330-20-7)	
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

TITANIUM DIOXIDE (13463-67-7)

LC50 - Fish [1]	> 100 mg/l
-----------------	------------

Calcium Carbonate (471-34-1)

EC50 72h - Algae [1]	> 14 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
----------------------	--

2-BUTANONE OXIME (96-29-7)

LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	≈ 201 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	≈ 11.8 mg/l Test organisms (species): Scenedesmus capricornutum
EC50 72h - Algae [2]	≈ 6.09 mg/l Test organisms (species): Scenedesmus capricornutum
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

TRADITIONAL OIL GLOSS

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

XYLENE (1330-20-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

TITANIUM DIOXIDE (13463-67-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Calcium Carbonate (471-34-1)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

2-BUTANONE OXIME (96-29-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
PAINT	Not regulated	Not regulated	Not regulated	Not regulated
Transport document description				
UN 1263 PAINT, 3, III, (D/E)	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
3	Not regulated	Not regulated	Not regulated	Not regulated
	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
III	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Dangerous for the environment: No	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30


TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Orange plates

:



Tunnel restriction code (ADR)

: D/E

EAC code

: •3Y

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals): Naphtha (petroleum), hydrotreated heavy (64742-48-9)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

National regulations

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

- Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
- Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).

Netherlands

- ABM category : Z(1) - non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/bioaccumulative potential/ toxicity or persistence)
- SZW-lijst van kankerverwekkende stoffen : LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY, 2-BUTANONE OXIME are listed
- SZW-lijst van mutagene stoffen : LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY is listed
- SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Ontwikkeling : XYLENE is listed

Denmark

- Class for fire hazard : Class II-1
- Store unit : 5 liter
- Classification remarks : R10 <H226>; Emergency management guidelines for the storage of flammable liquids must be followed
- Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Poland

Polish National Regulations

: Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).
Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).
The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).
Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).
Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).
Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).
The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488).
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).
Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).
ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891).
Regulation of the Minister of Health of 25 August 2015 on the method of marking places, pipelines, and containers and tanks used for storing or containing hazardous substances or hazardous mixtures (J.o.L. 2015, item 1368 as ammended)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:	
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor
ACGIH	American Conference of Government Industrial Hygienists
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
CSA	Chemical safety assessment
EWC	European waste catalogue
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
OSHA	Occupational Safety Health Administration
PPE	Personal protection equipment
TF	Technical function
TWA	Time Weighted Average
UFI	Unique Formula Identifier

Full text of H- and EUH-statements:	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2

TRADITIONAL OIL GLOSS

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 1	Specific target organ toxicity – single exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains 2-BUTANONE OXIME (96-29-7) (350). May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.