



**WOOD  
FINISHES  
DIRECT**



Finish. Finished.

The following Safety Datasheet is provided by **Manns**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Manns Trade Shellac Sanding Sealer](#)



# MANNS TRADE Safety Data Sheet

Manns Trade Shellac Sanding Sealer

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

### 1.1. Product Identifier

Name	Manns Trade Shellac Sanding Sealer
------	------------------------------------

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	Industrial wood coating.
Name	Manns Trade Shellac Sanding Sealer

### 1.3. Details of the supplier of the safety data sheet

Company	Wood Finishes Direct LTD
Address	Unit B, 5 Acre Trade Estate, Park Farm Road, Folkestone, KENT, CT19 5DS
Web	<a href="http://www.wood-finishes-direct.com">www.wood-finishes-direct.com</a>
Telephone	+44 (0)1303 213838
Fax	+44 (0)844 815 4992
Email	<a href="mailto:wood@finishes-direct.com">wood@finishes-direct.com</a>
Email address of the competent person	<a href="mailto:wood@finishes-direct.com">wood@finishes-direct.com</a>

### 1.4. Emergency telephone number

Emergency telephone number	111 (England and Wales) or 08454 24 24 24 (Scotland)
Company	National Poisons Information Service (NHS Direct)


## 2. HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

Classification - (1999/45)	Xi;R41. F;R11. R67.
Classification - EC 1272/2008	Flam. Liq. 2 - H225 Eye Dam. 1 - H318 STOT SE 2 - H371 STOT SE 3 - H336
Human health	Vapours and spray/mists in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Irritating to eyes. Repeated exposure may cause skin dryness or cracking.
Environmental	The product is not expected to be hazardous to the environment.
Physicochemical	The product is highly flammable. Vapours may form explosive mixtures with air.

# Manns Trade Shellac Sanding Sealer

## 2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	<p>H225 Highly flammable liquid and vapour.  H318 Causes serious eye damage.  H336 May cause drowsiness or dizziness.  H371 May cause damage to organs .</p>
Precautionary Statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  P240 Ground/ bond container and receiving equipment.  P241 Use explosion-proof electrical equipment.  P242 Use only non-sparking tools.  P243 Take precautionary measures against static discharge.  P260 Do not breathe vapour/ spray.  P261 Avoid breathing vapour/ spray.  P264 Wash contaminated skin thoroughly after handling.  P270 Do not eat, drink or smoke when using this product.  P271 Use only outdoors or in a well-ventilated area.  P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  P308+P311 IF exposed or concerned: Call a POISON CENTER or doctor.  P310 Immediately call a POISON CENTER/ doctor.  P312 Call a POISON CENTER/ doctor if you feel unwell.  P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.  P403+P233 Store in a well-ventilated place. Keep container tightly closed.  P403+P235 Store in a well-ventilated place. Keep cool.  P405 Store locked up.  P501 Dispose of contents/ container in accordance with national regulations.</p>
Contains	PROPAN-1-OL, METHANOL
Supplementary precautionary statements	<p>P233 Keep container tightly closed.  P240 Ground/ bond container and receiving equipment.  P241 Use explosion-proof electrical/ ventilating /lighting/.../ equipment.  P242 Use only non-sparking tools.  P243 Take precautionary measures against static discharge.  P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p>

# Manns Trade Shellac Sanding Sealer

PP310 Immediately call a POISON CENTER/ doctor.  
 P312 Call a POISON CENTER/ doctor if you feel unwell.  
 P370+P378 In case of fire: Use ... for extinction.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.  
 P501 Dispose of contents/ container to ...

## 2.3. Other Hazards

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

### 3.2. Mixtures

#### ETHANHOL

Concentration	35 - 55 %
CAS number	64-17-5
EC number	200-578-6
Classification (EC 1272/2008) Flam. Liq. 2 - H225	Classification (67/548/EEC) F;R11

#### PROPAN-1-OL

Concentration	30 - 40 %
CAS number	71-23-8
EC number	200-746-9
Classification Flam. Liq. 2 - H225 Eye Dam. 1 - H318 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R41 R67

#### METHANOL

Concentration	0.5 - 2.5 %
CAS number	67-56-1
EC number	200-659-6
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370	Classification (67/548/EEC or 1999/45/EC) F;R11 T;R23/24/25,R39/23/24/25

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16  
 The data shown are in accordance with the latest EC Directives.

# Manns Trade Shellac Sanding Sealer

## 4. FIRST AID MEASURES

### 4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.
Inhalation	Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Skin contact	Immediately remove contaminated clothing. Rinse immediately with plenty of water. Remove contaminated clothing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## 5. FIREFIGHTING MEASURES

### 5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Alcohol-resistant foam. Carbon dioxide (CO <sub>2</sub> ). Dry chemicals, sand, dolomite etc. Do not use water, if avoidable.
------------------------------	--

### 5.2. Special hazards arising from the substance or mixture

Specific hazards	The product is flammable. Heating may generate flammable vapours. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.
------------------	--

### 5.3. Advice for firefighters

Protective actions during firefighting	Control run-off water by containing and keeping it out of sewers and watercourses.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
----------------------	---

### 6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.
---------------------------	--

# Manns Trade Shellac Sanding Sealer

## 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Keep combustible materials away from spillage. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage.
-------------------------	---

## 6.4. Reference to other sections

## 7. HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Usage precautions	Avoid spilling. Avoid contact with skin and eyes. Do not wear contact lenses. Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Use explosion proof electric equipment. Eye wash facilities and emergency shower must be available when handling this product. During application and drying, solvent vapours will be emitted.
-------------------	--

### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.
Storage class	Flammable liquid storage.

### 7.3. Specific end use(s)

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 hrs		STEL - 15 min		Notes
ETHANOL	WEL	1000 ppm	1920 mg/m <sup>3</sup>			
PROPAN-1-OL	WEL	200 ppm(Sk)	500 mg/m <sup>3</sup> (Sk)	250 ppm(Sk)	625 mg/m <sup>3</sup> (Sk)	
METHANOL	WEL	200 ppm	266 mg/m <sup>3</sup>	250 ppm	333 mg/m <sup>3</sup>	Sk

WEL = Workplace Exposure Limit.  
Sk = Can be absorbed through skin.

### 8.2. Exposure controls

Ingredient comments	OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.
---------------------	---

ETHANOL (CAS: 64-17-5)	
DNEL	Professional - Dermal; Short term systemic effects: 22 mg/l
DMEL	Consumer - Oral; Long term local effects: 111 mg/cm <sup>2</sup>
PNEC	Industry - Sediment; Short term 11111 mg/kg/day

### 8.2. Exposure controls



## Manns Trade Shellac Sanding Sealer

Appropriate engineering controls	Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	Contact lenses should not be worn when working with this chemical. The following protection should be worn: Chemical splash goggles.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.
Other skin and body protection	Use engineering controls to reduce air contamination to permissible exposure level. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station and safety shower.
Hygiene measures	Provide eyewash station. Wash promptly if skin becomes contaminated. Promptly remove non-impervious clothing that becomes contaminated. When using do not eat, drink or smoke.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Light Brown
Odour	No data available
Odour threshold	No data available
pH	No data available
Melting point	No data available
Initial boiling point	No data available
Flash point	14°C OC (Open cup).
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available
Solubility	No data available

#### 9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	No data available
Lead content	No data available
VOC (Volatile organic compounds)	600 g/litre

### 10. STABILITY AND REACTIVITY

#### 10.1. Reactivity

#### 10.2. Chemical stability

	No particular stability concerns.
--	-----------------------------------

#### 10.3. Possibility of hazardous reactions

# Manns Trade Shellac Sanding Sealer

## 10.4. Conditions to avoid

Avoid heat. Avoid contact with oxidisers or reducing agents.

## 10.5. Incompatible materials

## 10.6. Hazardous decomposition products

Hazardous decomposition products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.
----------------------------------	--

## 11. TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Acute toxicity - oral	ATE oral (mg/kg)	6,610.26
Acute toxicity - dermal	ATE dermal (mg/kg)	19,830.78
Acute toxicity - inhalation	ATE inhalation (gases ppm)	46,271.81
	ATE inhalation (vapours mg/l)	198.31
	ATE inhalation (dusts/mists mg/l)	33.05
Inhalation	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following over exposure may include the following: Coughing. Vapours have a narcotic effect. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting.	
Ingestion	Gastrointestinal symptoms, including upset stomach.	
Skin contact	Repeated exposure may cause skin dryness or cracking.	
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.	

## 12. ECOLOGICAL INFORMATION

<b>Ecotoxicity</b>	The product is not expected to be hazardous to the environment.
--------------------	---

### 12.1. Toxicity

Persistence and degradability	There are no data on the degradability of this product.
-------------------------------	---

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## 13. DISPOSAL CONSIDERATIONS

General Information	Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
---------------------	--

### 13.1. Waste treatment methods

Disposal methods	Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor. Containers should be thoroughly emptied before disposal because of the risk of an explosion.
------------------	---



# Manns Trade Shellac Sanding Sealer

## 14. TRANSPORT INFORMATION


### 14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263

### 14.2. UN proper shipping name

Proper shipping name	PAINT OR PAINT RELATED PRODUCTS
----------------------	---------------------------------

### 14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID label	3
IMDG class	3
ICAO class/division	3
Transport Labels	

### 14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II

### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant	No.
--	-----

### 14.6. Special precautions for user

EmS	F-E, S-D
Emergency Action Code	3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

# Manns Trade Shellac Sanding Sealer

## 15. REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	EH40/2005 Workplace exposure limits. Control of Substances Hazardous to Health Regulations 2002 (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. The Classification, Labelling and Packaging of substances and mixtures Regulations EC 1272/2008 (CLP) and amendments
----------------------	--

### 15.2. Chemical safety assessment

## 16. OTHER INFORMATION

<b>Risk phrases in full</b>	R11 Highly flammable. R23/24/25 Toxic by inhalation, in contact with skin and if swallowed. R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed. R41 Risk of serious damage to eyes. R67 Vapours may cause drowsiness and dizziness.
<b>Hazard Statements In Full</b>	H225 Highly flammable liquid and vapour. H301 Toxic if swallowed. H311 Toxic in contact with skin. H318 Causes serious eye damage. H331 Toxic if inhaled. H336 May cause drowsiness or dizziness. H370 Causes damage to organs. H371 May cause damage to organs.
<b>General information</b>	This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy