



WOOD FINISHES DIRECT

The following Safety Datasheet is provided by **Morrells**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Morrells 280 High Solids Basecoat](#)

Product Data Sheet



9*03/280 Range: Precatalyst Lacquers (981/XXX – 986/XXX Tinted Precat. Lacquers)

Code	Description	Code	Description
9901/280	90% Sheen	9203/280	20% Sheen
9503/280	50% Sheen	9103/280	10% Sheen
9403/280	40% Sheen	Basecoat	9004/280
9303/280	30% Sheen	Thinners	2007/000

Technical Data	A high solids Precatalyst system formulated to give a fuller finish with fewer coats and prevent aeration on deep-grained timbers such as crown-cut mahogany. This range utilises silica for sheen reduction and as a consequence can be used either over the recommended basecoat or coat-on-coat. This Range can also be used over 9004/250 High Solids Basecoat.
Properties	Meets the requirements of BS (FIRA Std) 6250 for horizontal surfaces (excluding kitchen worktops) in General Use.
Mixing Guidelines	Supplied ready for use (RFU) but can be thinned upto 5% by volume with the recommended thinner, 2007/000, if required.
Typical Handling	Touch Dry: 8 – 10 minutes @ 18°C Sandable: 30 minutes @ 18°C. Use 320 or finer Silicone Carbide paper. Recoatible: 30 minutes minimum @ 18°C Packing Time: Overnight minimum, dependent on conditions.
Cleaning	2007/100 should be used for cleaning equipment.
Coverage	Approximately 40m ² per 5Lts dependent upon the size, orientation and surface quality of the item being coated.
Tinting	Use Morrells Light Fast Stains up to a maximum of 5%. Bespoke tints can be matched on request.
System Guidelines	Morrells recommends the following guidance for use of this product range: Typical Finish: 1-3 coats at 75g/m ² per coat (Dry Film Thickness ~ 23µ per coat) coat on coat or over Morrells recommended basecoat/sealers. Using these products in systems outside these guidelines can lead to immediate and latent problems with the integrity of the finish.
Important Information	<ul style="list-style-type: none"> ➤ Designed for spray application. ➤ Use only the recommended thinner. Use of non-recommended thinner can cause uneven/patchy drying.



Morrells Woodfinishes Ltd. Wellington Works, Mill Lane, Woodley, Stockport, Cheshire. SK6 1RN
Tel: 08705 60 61 62 Fax: 08705 604 604 Email: enquiries@morrells.co.uk Web: www.morrells.co.uk

Registered Office: Morrells Woodfinishes Limited. Company no. 785935 VAT. Reg No GB 712 5048 66



	<ul style="list-style-type: none"> ➤ Leave adequate time between coats. Do not apply more than 3 coats in one day. Denib between coats to aid adhesion. ➤ Excessive coating weights can lead to cracking or lifting. ➤ Do not overcoat with 1K or 2K Polyurethane (PU) products. ➤ This range is not suitable for 'pulling over'. ➤ Use 2007/200 Anti-Chill Thinners when applying in conditions of high atmospheric humidity, using a maximum of 5% by volume. ➤ Use 2007/201 Retarder Thinners to slow down the drying in warm conditions, using a maximum of 5% by volume. ➤ Product should be stored above 5°C and protected from frost. ➤ Optimum application is achieved between 18°C and 22°C with good air movement and ventilation. ➤ Finished products should not be subjected to environments with temperatures of < 2°C. ➤ Out of scope with 2004/42/EC.
<p>Health & Safety</p>	<p>Reference should be made to the appropriate MSDS for this product range, which can be found at www.morrells.co.uk</p> <p>The use of appropriate personal protection equipment (PPE) is recommended.</p> <p>These products are intended for professional use only.</p>

The information provided on this information sheet is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.

For further technical information contact our Technical Support Team on 0161 406 5300.



SAFETY DATA SHEET
9901/280 Range of Precatalyst lacquer

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name 9901/280 Range of Precatalyst lacquer
Product No. 10% to 90% Sheen

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial wood coating.

1.3. Details of the supplier of the safety data sheet

Supplier: Morrells Woodfinishes Ltd
Wellington Works
Mill Lane, Woodley
Stockport
England
SK6 1RN
0161 406 5300
0161 406 6276
enquiries@morrells.co.uk

1.4. Emergency telephone number

0161 406 5300 DURING OFFICE HOURS

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical	Flam. Liq. 2 - H225
Health	EUH066;Eye Dam. 1 - H318;STOT Single 3 - H336
Environmental	Not classified.

Classification (1999/45) Xi;R41. F;R11. R66, R67.

Human Health

In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Physical And Chemical Hazards

The product is highly flammable, and explosive vapours/air mixtures may be formed even at normal room temperatures.

2.2. Label elements

Label In Accordance With (Ec) No. 1272/2008



Signal Word Danger

Hazard Statements

H225	Highly flammable liquid and vapour.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

9901/280 Range of Precatalyst lacquer

P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Supplementary Precautionary Statements

P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P310 Immediately call a POISON CENTER or doctor/physician.
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.
 P370+378 In case of fire: Use ... for extinction.
 P403+233 Store in a well-ventilated place. Keep container tightly closed.
 P403+235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container to ...

Supplemental Label Information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

This product does not contain any PBT or vPvB Substances.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

BUTANOL-norm	5-10%
CAS-No.: 71-36-3	EC No.: 200-751-6
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT Single 3 - H335 STOT Single 3 - H336	Classification (67/548) R10 Xn;R22 Xi;R37/38,R41 R67
BUTYL ACETATE -norm	10-30%
CAS-No.: 123-86-4	EC No.: 204-658-1
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT Single 3 - H336	Classification (67/548) R10 R66 R67
ETHANOL	10-30%
CAS-No.: 64-17-5	EC No.: 200-578-6
Classification (EC 1272/2008) Flam. Liq. 2 - H225	Classification (67/548) F;R11

9901/280 Range of Precatalyst lacquer

ISOBUTYL ACETATE		10-30%
CAS-No.: 110-19-0	EC No.: 203-745-1	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066	Classification (67/548) F;R11 R66	
METHANOL		< 1%
CAS-No.: 67-56-1	EC No.: 200-659-6	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT Single 1 - H370	Classification (67/548) F;R11 T;R23/24/25,R39/23/24/25	
PROPAN-1-OL		1-5%
CAS-No.: 71-23-8	EC No.: 200-746-9	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Dam. 1 - H318 STOT Single 3 - H336	Classification (67/548) F;R11 Xi;R41 R67	
PROPAN-2-OL		10-30%
CAS-No.: 67-63-0	EC No.: 200-661-7	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT Single 3 - H336	Classification (67/548) F;R11 Xi;R36 R67	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Information

NOTE! Keep affected person away from heat, sparks and flames! Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation.

Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT INDUCE VOMITING! Remove victim immediately from source of exposure. Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Skin Contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

9901/280 Range of Precatalyst lacquer

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing Media

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Special Fire Fighting Procedures

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Use explosion proof electric equipment.

7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BUTANOL-norm	WEL			50 ppm(Sk)	154 mg/m3(Sk)	
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3	
ETHANOL	WEL	1000 ppm	1920 mg/m3			
ISOBUTYL ACETATE	WEL	150 ppm	724 mg/m3	187 ppm	903 mg/m3	
METHANOL	WEL	200 ppm	266 mg/m3	250 ppm	333 mg/m3	
PROPAN-1-OL	WEL	200 ppm(Sk)	500 mg/m3(Sk)	250 ppm(Sk)	625 mg/m3(Sk)	
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective Equipment

9901/280 Range of Precatalyst lacquer



Engineering Measures

Provide adequate general and local exhaust ventilation.

Respiratory Equipment

Respiratory protection must be used if air contamination exceeds acceptable level.

Hand Protection

Use protective gloves.

Eye Protection

Use approved safety goggles or face shield.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene Measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless to pale yellow
Initial Boiling Point and Boiling Range:	92
Flash Point (°C)	11

9.2. Other information

Volatile Organic Compound (VOC) 645 to 655 g/litre

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat. Avoid contact with oxidisers or reducing agents.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

General Information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may irritate respiratory system or lungs.

Ingestion.

Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs. Narcotic effect.

Skin Contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

Eye Contact

Irritating to eyes. Vapour or spray may cause temporary (reversible) eye damage.

9901/280 Range of Precatalyst lacquer

Route of entry

Inhalation. Ingestion. Skin and/or eye contact.

Target Organs

Respiratory system, lungs

Medical Symptoms

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN) 1263

14.2 UN Proper Shipping Name

Proper Shipping Name PAINT OR PAINT RELATED PRODUCTS

14.3 Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group II

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

14.6. Special precautions for user

Hazard No. (ADR) 33

Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

9901/280 Range of Precatalyst lacquer

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Uk Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

Statutory Instruments

The Classification, Labelling and Packaging of substances and mixtures Regulations EC 1272/2008 (CLP) and amendments

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Issued By	HS&E Manager.
Revision Date	08/12/2011
Revision	1
Supersedes Date	23/06/2011
Risk Phrases In Full	
R10	Flammable.
R11	Highly flammable.
R22	Harmful if swallowed.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R36	Irritating to eyes.
R37/38	Irritating to respiratory system and skin.
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R41	Risk of serious damage to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.
Hazard Statements In Full	
EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs <<Organs>>.

SAFETY DATA SHEET
9004/280 PRECAT BASECOAT

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name 9004/280 PRECAT BASECOAT
Product No. 9004/280

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial wood coating.

1.3. Details of the supplier of the safety data sheet

Supplier: Morrells Woodfinishes Ltd
Wellington Works
Mill Lane, Woodley
Stockport
England
SK6 1RN
0161 406 5300
0161 406 6276
enquiries@morrells.co.uk

1.4. Emergency telephone number

0161 406 5300 DURING OFFICE HOURS

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical	Flam. Liq. 2 - H225
Health	Acute Tox. 4 - H312; Acute Tox. 4 - H332; Skin Irrit. 2 - H315; Eye Irrit. 2 - H319; Repr. 2 - H361d; STOT Rep. 2 - H373
Environmental	Not classified.

Classification (1999/45) Xn; R20/21, R48/20. Repr. Cat. 3; R63. Xi; R36/38. F; R11.

Human Health

In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Environment

Contains a substance which causes risk of hazardous effects to the environment.

Physical And Chemical Hazards

The product is highly flammable, and explosive vapours/air mixtures may be formed even at normal room temperatures.

2.2. Label elements

Contains: TOLUENE

Label In Accordance With (Ec) No. 1272/2008



Signal Word Danger

Hazard Statements

H225	Highly flammable liquid and vapour.
H312	Harmful in contact with skin.

9004/280 PRECAT BASECOAT

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P313	Get medical advice/attention.

Supplementary Precautionary Statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P308+313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see ... on this label).
P322	Specific measures (see ... on this label).
P332+313	If skin irritation occurs: Get medical advice/attention.
P337	If eye irritation persists:
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370+378	In case of fire: Use ... for extinction.
P403+235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to ...

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

1-METHOXY-2-PROPANOL		1-5%
CAS-No.: 107-98-2	EC No.: 203-539-1	
Classification (EC 1272/2008)	Classification (67/548)	
Flam. Liq. 3 - H226	R10	
STOT Single 3 - H336	R67	

9004/280 PRECAT BASECOAT

BUTANOL-norm		1-5%
CAS-No.: 71-36-3	EC No.: 200-751-6	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT Single 3 - H335 STOT Single 3 - H336	Classification (67/548) R10 Xn;R22 Xi;R37/38,R41 R67	
ETHANOL		5-10%
CAS-No.: 64-17-5	EC No.: 200-578-6	
Classification (EC 1272/2008) Flam. Liq. 2 - H225	Classification (67/548) F;R11	
ISO-BUTANOL		1-5%
CAS-No.: 78-83-1	EC No.: 201-148-0	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT Single 3 - H335 STOT Single 3 - H336	Classification (67/548) R10 Xi;R37/38,R41 R67	
ISOBUTYL ACETATE		10-30%
CAS-No.: 110-19-0	EC No.: 203-745-1	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066	Classification (67/548) F;R11 R66	
METHANOL		< 1%
CAS-No.: 67-56-1	EC No.: 200-659-6	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT Single 1 - H370	Classification (67/548) F;R11 T;R23/24/25,R39/23/24/25	
PROPAN-1-OL		5-10%
CAS-No.: 71-23-8	EC No.: 200-746-9	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Dam. 1 - H318 STOT Single 3 - H336	Classification (67/548) F;R11 Xi;R41 R67	

9004/280 PRECAT BASECOAT

SOLVENT NAPHTHA LOW BOILING POINT		< 1%
CAS-No.: 64742-95-6	EC No.: 265-199-0	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT Single 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548) Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.	
TOLUENE		10-30%
CAS-No.: 108-88-3	EC No.: 203-625-9	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT Single 3 - H336 STOT Rep. 2 - H373 Asp. Tox. 1 - H304	Classification (67/548) F;R11 Repr.Cat.3;R63 Xn;R48/20,R65 Xi;R38 R67	
UREA P/W		1-5%
CAS-No.: 68002-18-6	EC No.:	
Classification (EC 1272/2008) Aquatic Chronic 4 - H413	Classification (67/548) R53.	
XYLENE		10-30%
CAS-No.: 1330-20-7	EC No.: 215-535-7	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	Classification (67/548) R10 Xn;R20/21 Xi;R38	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Information

NOTE! Keep affected person away from heat, sparks and flames! Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation.

Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT INDUCE VOMITING! Remove victim immediately from source of exposure. Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Skin Contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing Media

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Special Fire Fighting Procedures

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Use explosion proof electric equipment.

7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
1-METHOXY-2-PROPANOL	WEL	100 ppm(Sk)	375 mg/m3(Sk)	150 ppm(Sk)	560 mg/m3(Sk)	
BUTANOL-norm	WEL			50 ppm(Sk)	154 mg/m3(Sk)	
ETHANOL	WEL	1000 ppm	1920 mg/m3			
ISO-BUTANOL	WEL	50 ppm	154 mg/m3	75 ppm	231 mg/m3	
ISOBUTYL ACETATE	WEL	150 ppm	724 mg/m3	187 ppm	903 mg/m3	
METHANOL	WEL	200 ppm	266 mg/m3	250 ppm	333 mg/m3	
PROPAN-1-OL	WEL	200 ppm(Sk)	500 mg/m3(Sk)	250 ppm(Sk)	625 mg/m3(Sk)	
TOLUENE	WEL	50 ppm(Sk)	191 mg/m3(Sk)	150 ppm(Sk)	574 mg/m3(Sk)	
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls**Protective Equipment****Engineering Measures**

Provide adequate general and local exhaust ventilation.

Respiratory Equipment

Respiratory protection must be used if air contamination exceeds acceptable level.

Hand Protection

Use protective gloves.

Eye Protection

Use approved safety goggles or face shield.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene Measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless to pale yellow
Initial Boiling Point and Boiling Range:	102
Flash Point (°C)	12

9.2. Other information

Volatile Organic Compound (VOC)	658 g/litre
--	-------------

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity**10.2. Chemical stability**

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions**10.4. Conditions to avoid**

Avoid heat. Avoid contact with oxidisers or reducing agents.

10.5. Incompatible materials**10.6. Hazardous decomposition products**

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects**General Information**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may irritate respiratory system or lungs.

Ingestion.

Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs. Narcotic effect.

Skin Contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

9004/280 PRECAT BASECOAT

Eye Contact

Irritating to eyes. Vapour or spray may cause temporary (reversible) eye damage.

Route of entry

Inhalation. Ingestion. Skin and/or eye contact.

Target Organs

Respiratory system, lungs

Medical Symptoms

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN) 1263

14.2 UN Proper Shipping Name

Proper Shipping Name PAINT OR PAINT RELATED PRODUCTS

14.3 Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group II

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

14.6. Special precautions for user

Hazard No. (ADR) 33

Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**Uk Regulatory References**

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

Statutory Instruments

The Classification, Labelling and Packaging of substances and mixtures Regulations EC 1272/2008 (CLP) and amendments

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. Spraying of Highly Flammable Liquids EH9.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Issued By	HS&E Manager.
Revision Date	08/12/2011
Revision	1
Supersedes Date	23/06/2011
Risk Phrases In Full	
R10	Flammable.
R11	Highly flammable.
R20/21	Harmful by inhalation and in contact with skin.
R22	Harmful if swallowed.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R37	Irritating to respiratory system.
R37/38	Irritating to respiratory system and skin.
R38	Irritating to skin.
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R41	Risk of serious damage to eyes.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53	May cause long-term adverse effects in the aquatic environment.
R63	Possible risk of harm to the unborn child.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

9004/280 PRECAT BASECOAT

Hazard Statements In Full

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs <<Organs>>.
H373	May cause damage to organs <<Organs>> through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

SAFETY DATA SHEET
2007/000 CELLULOSE THINNERS

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name 2007/000 CELLULOSE THINNERS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial wood coating.

1.3. Details of the supplier of the safety data sheet

Supplier: Morrells Woodfinishes Ltd
Wellington Works
Mill Lane, Woodley
Stockport
England
SK6 1RN
0161 406 5300
0161 406 6276
enquiries@morrells.co.uk

1.4. Emergency telephone number

0161 406 5300 DURING OFFICE HOURS

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical	Flam. Liq. 2 - H225
Health	Skin Irrit. 2 - H315; Eye Dam. 1 - H318; Repr. 2 - H361d; STOT Single 3 - H336; STOT Rep. 2 - H373; Asp. Tox. 1 - H304
Environmental	Not classified.

Classification (1999/45) Xn; R48/20, R65. Repr. Cat. 3; R63. Xi; R38, R41. F; R11. R67.

2.2. Label elements

Contains: TOLUENE

Label In Accordance With (Ec) No. 1272/2008



Signal Word Danger

Hazard Statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

2007/000 CELLULOSE THINNERS

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container to ...

Supplementary Precautionary Statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P308+313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see ... on this label).
P331	Do NOT induce vomiting.
P332+313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P370+378	In case of fire: Use ... for extinction.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P403+235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

2.3. Other hazards

This product does not contain any PBT or vPvB Substances.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

ACETONE	5-10%
CAS-No.: 67-64-1	EC No.: 200-662-2
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 Eye Irrit. 2 - H319 STOT Single 3 - H336	Classification (67/548) F;R11 Xi;R36 R66 R67
BUTANOL-norm	5-10%
CAS-No.: 71-36-3	EC No.: 200-751-6

2007/000 CELLULOSE THINNERS

Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT Single 3 - H335 STOT Single 3 - H336	Classification (67/548) R10 Xn;R22 Xi;R37/38,R41 R67
--	--

BUTYL ACETATE -norm	5-10%
CAS-No.: 123-86-4	EC No.: 204-658-1

Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT Single 3 - H336	Classification (67/548) R10 R66 R67
--	--

PROPAN-1-OL	1-5%
CAS-No.: 71-23-8	EC No.: 200-746-9

Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Dam. 1 - H318 STOT Single 3 - H336	Classification (67/548) F;R11 Xi;R41 R67
---	---

TOLUENE	60-100%
CAS-No.: 108-88-3	EC No.: 203-625-9

Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT Single 3 - H336 STOT Rep. 2 - H373 Asp. Tox. 1 - H304	Classification (67/548) F;R11 Repr.Cat.3;R63 Xn;R48/20,R65 Xi;R38 R67
---	---

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Information

NOTE! Keep affected person away from heat, sparks and flames! Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation.

Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT INDUCE VOMITING! Remove victim immediately from source of exposure. Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Skin Contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

2007/000 CELLULOSE THINNERS

5.1. Extinguishing media

Extinguishing Media

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Special Fire Fighting Procedures

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Use explosion proof electric equipment.

7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ACETONE	WEL	500 ppm	1210 mg/m ³	1500 ppm	3620 mg/m ³	
BUTANOL-norm	WEL			50 ppm(Sk)	154 mg/m ³ (Sk)	
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m ³	200 ppm	966 mg/m ³	
PROPAN-1-OL	WEL	200 ppm(Sk)	500 mg/m ³ (Sk)	250 ppm(Sk)	625 mg/m ³ (Sk)	
TOLUENE	WEL	50 ppm(Sk)	191 mg/m ³ (Sk)	150 ppm(Sk)	574 mg/m ³ (Sk)	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective Equipment



Engineering Measures

Provide adequate general and local exhaust ventilation.

2007/000 CELLULOSE THINNERS

Respiratory Equipment

Respiratory protection must be used if air contamination exceeds acceptable level.

Hand Protection

Use protective gloves.

Eye Protection

Use approved safety goggles or face shield.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene Measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Odour	Characteristic
Initial Boiling Point and Boiling Range:	97
Flash Point (°C)	6

9.2. Other information

Volatile Organic Compound (VOC) 857 g/litre

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat. Avoid contact with oxidisers or reducing agents.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

General Information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may irritate respiratory system or lungs.

Ingestion.

Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs. Narcotic effect.

Skin Contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

Eye Contact

Irritating to eyes. Vapour or spray may cause temporary (reversible) eye damage.

Route of entry

Inhalation. Ingestion. Skin and/or eye contact.

Target Organs

Respiratory system, lungs

Medical Symptoms

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

There are no data on the ecotoxicity of this product.

12.1. Toxicity**12.2. Persistence and degradability****12.3. Bioaccumulative potential****12.4. Mobility in soil****12.5. Results of PBT and vPvB assessment****12.6. Other adverse effects**

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN) 1263

14.2 UN Proper Shipping Name

PAINT OR PAINT RELATED MATERIAL

Proper Shipping Name PAINT OR PAINT RELATED PRODUCTS

14.3 Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

Transport Labels**14.4. Packing group**

ADR/RID/ADN Packing group II

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant
No.

14.6. Special precautions for user

Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**Statutory Instruments**

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

2007/000 CELLULOSE THINNERS

Guidance Notes

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Date 28/06/2013

Revision 2

Supersedes Date 23/06/2011

Risk Phrases In Full

R10 Flammable.
R11 Highly flammable.
R22 Harmful if swallowed.
R36 Irritating to eyes.
R37/38 Irritating to respiratory system and skin.
R38 Irritating to skin.
R41 Risk of serious damage to eyes.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63 Possible risk of harm to the unborn child.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

EUH066 Repeated exposure may cause skin dryness or cracking.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs <<Organs>> through prolonged or repeated exposure.

SAFETY DATA SHEET
2007/100 gun cleaner

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name 2007/100 gun cleaner

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial wood coating.

1.3. Details of the supplier of the safety data sheet

Supplier: Morrells Woodfinishes Ltd
Wellington Works
Mill Lane, Woodley
Stockport
England
SK6 1RN
0161 406 5300
0161 406 6276
enquiries@morrells.co.uk

1.4. Emergency telephone number

0161 406 5300 DURING OFFICE HOURS

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical	Flam. Liq. 2 - H225
Health	Acute Tox. 4 - H302; Acute Tox. 4 - H312; Acute Tox. 4 - H332; Skin Irrit. 2 - H315; Eye Irrit. 2 - H319; Repr. 2 - H361d; STOT Single 2 - H371; STOT Rep. 2 - H373; Asp. Tox. 1 - H304
Environmental	Not classified.

Classification (1999/45)

Xn; R20/21/22, R68/20/21/22, R48/20, R65. Repr. Cat. 3; R63. Xi; R36/38. F; R11.

2.2. Label elements

Contains: METHANOL
TOLUENE

Label In Accordance With (Ec) No. 1272/2008



Signal Word Danger

Hazard Statements

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

2007/100 gun cleaner

H361d	Suspected of damaging the unborn child.
H371	May cause damage to organs .
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P313	Get medical advice/attention.

Supplementary Precautionary Statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301+312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P308+313	IF exposed or concerned: Get medical advice/attention.
P309+311	IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see ... on this label).
P322	Specific measures (see ... on this label).
P330	Rinse mouth.
P331	Do NOT induce vomiting.
P332+313	If skin irritation occurs: Get medical advice/attention.
P337	If eye irritation persists:
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370+378	In case of fire: Use ... for extinction.
P403+235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to ...

2.3. Other hazards

This product does not contain any PBT or vPvB Substances.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

2007/100 gun cleaner

ACETONE		30-60%
CAS-No.: 67-64-1		EC No.: 200-662-2
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 Eye Irrit. 2 - H319 STOT Single 3 - H336	Classification (67/548) F;R11 Xi;R36 R66 R67	
BUTYL ACETATE -norm		10-30%
CAS-No.: 123-86-4		EC No.: 204-658-1
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT Single 3 - H336	Classification (67/548) R10 R66 R67	
METHANOL		5-10%
CAS-No.: 67-56-1		EC No.: 200-659-6
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT Single 1 - H370	Classification (67/548) F;R11 T;R23/24/25,R39/23/24/25	
TOLUENE		30-60%
CAS-No.: 108-88-3		EC No.: 203-625-9
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT Single 3 - H336 STOT Rep. 2 - H373 Asp. Tox. 1 - H304	Classification (67/548) F;R11 Repr.Cat.3;R63 Xn;R48/20,R65 Xi;R38 R67	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Information

NOTE! Keep affected person away from heat, sparks and flames! Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation.

Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT INDUCE VOMITING! Remove victim immediately from source of exposure. Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Skin Contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

2007/100 gun cleaner

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing Media

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Special Fire Fighting Procedures

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Use explosion proof electric equipment.

7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3	
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3	
METHANOL	WEL	200 ppm	266 mg/m3	250 ppm	333 mg/m3	
TOLUENE	WEL	50 ppm(Sk)	191 mg/m3(Sk)	150 ppm(Sk)	574 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective Equipment



2007/100 gun cleaner

Engineering Measures

Provide adequate general and local exhaust ventilation.

Respiratory Equipment

Respiratory protection must be used if air contamination exceeds acceptable level.

Hand Protection

Use protective gloves.

Eye Protection

Use approved safety goggles or face shield.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene Measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Odour	Characteristic
Initial Boiling Point and Boiling Range:	92
Flash Point (°C)	-1

9.2. Other information

Volatile Organic Compound (VOC)	838 g/litre
---------------------------------	-------------

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat. Avoid contact with oxidisers or reducing agents.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

General Information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may irritate respiratory system or lungs.

Ingestion.

Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs. Narcotic effect.

Skin Contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

Eye Contact

Irritating to eyes. Vapour or spray may cause temporary (reversible) eye damage.

Route of entry

Inhalation. Ingestion. Skin and/or eye contact.

Target Organs

Respiratory system, lungs

2007/100 gun cleaner

Medical Symptoms

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

There are no data on the ecotoxicity of this product.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN) 1263

14.2 UN Proper Shipping Name

PAINT OR PAINT RELATED MATERIAL

Proper Shipping Name PAINT OR PAINT RELATED PRODUCTS

14.3 Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group II

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

14.6. Special precautions for user

Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

2007/100 gun cleaner

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Date 28/06/2013

Revision 2

Supersedes Date 23/06/2011

Risk Phrases In Full

R10 Flammable.

R11 Highly flammable.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R36 Irritating to eyes.

R38 Irritating to skin.

R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R63 Possible risk of harm to the unborn child.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

EUH066 Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H370 Causes damage to organs <<Organs>>.

H373 May cause damage to organs <<Organs>> through prolonged or repeated exposure.