



WOOD FINISHES DIRECT

The following Safety Datasheet is provided by **Morrells**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Morrells Induro XLA Anti-Slip Floor Varnish](#)

SAFETY DATA SHEET
454 Range of INDURO AC Flooring lacquer (Mix 9:1 with 5CAT/100)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name 454 Range of INDURO AC Flooring lacquer (Mix 9:1 with 5CAT/100)
Product No. 5901/454 90% Sheen to 5103/454 10% Sheen

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial wood coating.

1.3. Details of the supplier of the safety data sheet

Supplier: Morrells Woodfinishes Ltd
Wellington Works
Mill Lane, Woodley
Stockport
England
SK6 1RN
0161 406 5300
0161 406 6276
enquiries@morrells.co.uk

1.4. Emergency telephone number

0161 406 5300 DURING OFFICE HOURS

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical	Flam. Liq. 2 - H225
Health	Acute Tox. 4 - H312; Acute Tox. 4 - H332; Skin Irrit. 2 - H315; Eye Dam. 1 - H318
Environmental	Not classified.

Classification (1999/45) Xn;R20/21. Xi;R38, R41. F;R11.

Human Health

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Harmful by inhalation and in contact with skin. The product is irritating to eyes and skin.

Environment

The product contains a substance which may cause long term adverse effects in the aquatic environment.

Physical And Chemical Hazards

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

2.2. Label elements

Contains: XYLENE

Label In Accordance With (Ec) No. 1272/2008



Signal Word Danger

Hazard Statements

H225	Highly flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.

454 Range of INDURO AC Flooring lacquer (Mix 9:1 with 5CAT/100)

H318 Causes serious eye damage.
H332 Harmful if inhaled.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Supplementary Precautionary Statements

P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash ... thoroughly after handling.
P302+352 IF ON SKIN: Wash with plenty of soap and water.
P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P310 Immediately call a POISON CENTER or doctor/physician.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P321 Specific treatment (see ... on this label).
P322 Specific measures (see ... on this label).
P332+313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.
P363 Wash contaminated clothing before reuse.
P370+378 In case of fire: Use ... for extinction.
P403+235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container to ...

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

ETHANOL	5-10%
CAS-No.: 64-17-5	EC No.: 200-578-6
Classification (EC 1272/2008) Flam. Liq. 2 - H225	Classification (67/548) F;R11
ISO-BUTANOL	10-30%
CAS-No.: 78-83-1	EC No.: 201-148-0
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT Single 3 - H335 STOT Single 3 - H336	Classification (67/548) R10 Xi;R37/38,R41 R67

454 Range of INDURO AC Flooring lacquer (Mix 9:1 with 5CAT/100)

METHANOL		< 1%
CAS-No.: 67-56-1	EC No.: 200-659-6	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT Single 1 - H370	Classification (67/548) F;R11 T;R23/24/25,R39/23/24/25	
SOLVENT NAPHTHA LOW BOILING POINT		< 1%
CAS-No.: 64742-95-6	EC No.: 265-199-0	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT Single 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548) Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.	
TOLUENE		1-5%
CAS-No.: 108-88-3	EC No.: 203-625-9	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT Single 3 - H336 STOT Rep. 2 - H373 Asp. Tox. 1 - H304	Classification (67/548) F;R11 Repr.Cat.3;R63 Xn;R48/20,R65 Xi;R38 R67	
UREA P/W		10-30%
CAS-No.: 68002-18-6	EC No.:	
Classification (EC 1272/2008) Aquatic Chronic 4 - H413	Classification (67/548) R53.	
XYLENE		10-30%
CAS-No.: 1330-20-7	EC No.: 215-535-7	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	Classification (67/548) R10 Xn;R20/21 Xi;R38	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

Composition Comments

The data shown are in accordance with the latest EC Directives.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Information

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

454 Range of INDURO AC Flooring lacquer (Mix 9:1 with 5CAT/100)

Inhalation.

Place unconscious person on the side in the recovery position and ensure breathing. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

Ingestion

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions.

Skin Contact

Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water.

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing Media

Fire can be extinguished using: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Fire causes formation of toxic gases.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Use pressurised air mask if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out.

Protective Measures In Fire

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Keep combustibles away from spilled material. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Avoid contact with oxidising agents.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

454 Range of INDURO AC Flooring lacquer (Mix 9:1 with 5CAT/100)

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ETHANOL	WEL	1000 ppm	1920 mg/m ³			
ISO-BUTANOL	WEL	50 ppm	154 mg/m ³	75 ppm	231 mg/m ³	
METHANOL	WEL	200 ppm	266 mg/m ³	250 ppm	333 mg/m ³	
SOLVENT NAPHTHA LOW BOILING POINT	WEL	600 ppm				
TOLUENE	WEL	50 ppm(Sk)	191 mg/m ³ (Sk)	150 ppm(Sk)	574 mg/m ³ (Sk)	
XYLENE	WEL	50 ppm(Sk)	220 mg/m ³ (Sk)	100 ppm(Sk)	441 mg/m ³ (Sk)	

WEL = Workplace Exposure Limit.

Ingredient Comments

OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

8.2. Exposure controls

Protective Equipment



Process Conditions

Provide eyewash station.

Engineering Measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. All handling to take place in well-ventilated area.

Respiratory Equipment

Wear mask supplied with: Gas cartridge suitable for organic substances.

Hand Protection

Use protective gloves made of: Neoprene. Nitrile. Rubber (natural, latex).

Eye Protection

Wear splash-proof eye goggles to prevent any possibility of eye contact.

Other Protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene Measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Colourless-pale yellow liquid
Odour	Characteristic
Initial Boiling Point and Boiling Range:	108
Flash Point (°C)	20

9.2. Other information

Volatile Organic Compound (VOC) 504 g/litre

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

No particular stability concerns.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

454 Range of INDURO AC Flooring lacquer (Mix 9:1 with 5CAT/100)

10.5. Incompatible materials

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

General Information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

In high concentrations, vapours may irritate throat and respiratory system and cause coughing. Harmful by inhalation.

Ingestion.

Gastrointestinal symptoms, including upset stomach.

Skin Contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Irritating to skin. Harmful in contact with skin.

Eye Contact

Irritating and may cause redness and pain.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

The product is not expected to be hazardous to the environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

General Information

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Absorb in vermiculite or dry sand and dispose of at a licenced hazardous waste collection point.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263

14.2 UN Proper Shipping Name

PAINT OR PAINT RELATED MATERIAL

Proper Shipping Name paint or paint related product

14.3 Transport hazard class(es)

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3
Transport Labels	

454 Range of INDURO AC Flooring lacquer (Mix 9:1 with 5CAT/100)



14.4. Packing group

ADR/RID/ADN Packing group	II
IMDG Packing group	II
ICAO Packing group	II

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

14.6. Special precautions for user

EMS	F-E, S-E UNDERLINED
Emergency Action Code	3YE
Hazard No. (ADR)	33
Tunnel Restriction Code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Classification, Labelling and Packaging of substances and mixtures Regulations EC 1272/2008 (CLP) and amendments

Guidance Notes

Workplace Exposure Limits EH40. Spraying of Highly Flammable Liquids EH9. Introduction to Local Exhaust Ventilation HS(G)37.

National Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits 2005 (EH40)

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

Revision Date	20/12/2011
Revision	1
Risk Phrases In Full	
R10	Flammable.
R11	Highly flammable.
R20/21	Harmful by inhalation and in contact with skin.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R37	Irritating to respiratory system.
R37/38	Irritating to respiratory system and skin.
R38	Irritating to skin.
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R41	Risk of serious damage to eyes.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53	May cause long-term adverse effects in the aquatic environment.
R63	Possible risk of harm to the unborn child.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

454 Range of INDURO AC Flooring lacquer (Mix 9:1 with 5CAT/100)

Hazard Statements In Full

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs <<Organs>>.
H373	May cause damage to organs <<Organs>> through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.