



WOOD FINISHES DIRECT

The following Safety Datasheet is provided by **Manns**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Nitromors All Purpose Paint and Varnish Remover](#)



Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 15

Nitromors All Purpose Paint & Varnish Remover - Dichloromethane Free

SDS No. : 378770
V005.1

Revision: 21.05.2015

printing date: 10.08.2016

Replaces version from: 24.11.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Nitromors All Purpose Paint & Varnish Remover - Dichloromethane Free

Contains:

Methanol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Stripper

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

Fax-no.: +44 (1442) 278071

ua-productsafety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids

Category 2

H225 Highly flammable liquid and vapor.

Acute toxicity

Category 4

H302 Harmful if swallowed.

Route of Exposure: Oral

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

Specific target organ toxicity - single exposure

Category 2

H371 May cause damage to organs.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Danger

Hazard statement:

H225 Highly flammable liquid and vapor.
H302 Harmful if swallowed.
H319 Causes serious eye irritation.
H371 May cause damage to organs.

Precautionary statement:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

**Precautionary statement:
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P233 Keep container tightly closed.
P260 Do not breathe gas.

**Precautionary statement:
Response**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.

**Precautionary statement:
Disposal**

P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

Pregnant women should absolutely avoid inhalation and skin contact.

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Composition

Base substances of preparation:

Organic solvent

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
1,3-Dioxolane 646-06-0	211-463-5	50- < 60 %	Flam. Liq. 2 H225
Methylal 109-87-5	203-714-2	< 30 %	Flam. Liq. 2 H225
Methanol 67-56-1	200-659-6 01-2119433307-44	3- < 10 %	Flam. Liq. 2 H225 STOT SE 1 H370 Acute Tox. 3; Inhalation H331 Acute Tox. 3; Dermal H311 Acute Tox. 3; Oral H301
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene 64742-48-9	265-150-3 01-2119463258-33	3- < 10 %	Flam. Liq. 3 H226 Asp. Tox. 1 H304 STOT SE 3 H336
Docusate sodium 577-11-7	209-406-4 01-2119491296-29	1- < 5 %	Skin Irrit. 2; Dermal H315 Eye Dam. 1 H318

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures**4.1. Description of first aid measures**

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remains (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

INGESTION: Nausea, vomiting, diarrhea, abdominal pain.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

Additional information:

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not empty waste into waste water drains.

Also to be noted when processing larger amounts (> 1 kg): during processing and drying after adhesion, ventilate well. Avoid all sources of fire such as stoves and ovens. Switch off all electrical devices such as parabolic heaters, hot plates, storage heaters etc. in good time for them to have cooled down before commencing work. Avoid all sparks, including those occurring at electrical switches and devices.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry place.

Store in sealed original container.

Store in a cool, well-ventilated place.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Stripper

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Dimethoxymethane 109-87-5 [DIMETHOXYMETHANE]	1.250	3.950	Short Term Exposure Limit (STEL):		EH40 WEL
Dimethoxymethane 109-87-5 [DIMETHOXYMETHANE]	1.000	3.160	Time Weighted Average (TWA):		EH40 WEL
Methanol 67-56-1 [METHANOL]	250	333	Short Term Exposure Limit (STEL):		EH40 WEL
Methanol 67-56-1 [METHANOL]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Methanol 67-56-1 [METHANOL]	200	266	Time Weighted Average (TWA):		EH40 WEL
Methanol 67-56-1 [METHANOL]	200	260	Time Weighted Average (TWA):	Indicative	ECTLV
1,2,4-Trimethylbenzene 95-63-6 [TRIMETHYLBENZENES, ALL ISOMERS OR MIXTURES]	25	125	Time Weighted Average (TWA):		EH40 WEL
1,2,4-Trimethylbenzene 95-63-6 [1,2,4-TRIMETHYLBENZENE]	20	100	Time Weighted Average (TWA):	Indicative	ECTLV

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Methanol 67-56-1	aqua (freshwater)					20,8 mg/L	
Methanol 67-56-1	sediment (freshwater)				77 mg/kg		
Methanol 67-56-1	aqua (marine water)					2,08 mg/L	
Methanol 67-56-1	soil				3,18 mg/kg		
Methanol 67-56-1	STP					100 mg/L	
Methanol 67-56-1	aqua (intermittent releases)					1540 mg/L	
Methanol 67-56-1	sediment (marine water)				7,7 mg/kg		
Docusate sodium 577-11-7	aqua (freshwater)					0,0066 mg/L	
Docusate sodium 577-11-7	aqua (marine water)					0,0007 mg/L	
Docusate sodium 577-11-7	aqua (intermittent releases)					0,066 mg/L	
Docusate sodium 577-11-7	soil				0,138 mg/kg		
Docusate sodium 577-11-7	STP					122 mg/L	
Docusate sodium 577-11-7	sediment (freshwater)				0,653 mg/kg		
Docusate sodium 577-11-7	sediment (marine water)				0,0653 mg/kg		
Solvent naphtha (petroleum), light arom. 64742-95-6	aqua (freshwater)					0,635 mg/L	
Solvent naphtha (petroleum), light arom. 64742-95-6	aqua (marine water)					0,0635 mg/L	
Solvent naphtha (petroleum), light arom. 64742-95-6	aqua (intermittent releases)					6,35 mg/L	
Solvent naphtha (petroleum), light arom. 64742-95-6	STP					100 mg/L	
Solvent naphtha (petroleum), light arom. 64742-95-6	sediment (freshwater)				3,29 mg/kg		
Solvent naphtha (petroleum), light arom. 64742-95-6	sediment (marine water)				0,329 mg/kg		
Solvent naphtha (petroleum), light arom. 64742-95-6	soil				0,29 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Methanol 67-56-1	Workers	Dermal	Acute/short term exposure - systemic effects		40 mg/kg bw/day	
Methanol 67-56-1	Workers	Inhalation	Acute/short term exposure - systemic effects		260 mg/m3	
Methanol 67-56-1	Workers	Inhalation	Acute/short term exposure - local effects		260 mg/m3	
Methanol 67-56-1	Workers	Dermal	Long term exposure - systemic effects		40 mg/kg bw/day	
Methanol 67-56-1	Workers	Inhalation	Long term exposure - systemic effects		260 mg/m3	
Methanol 67-56-1	Workers	Inhalation	Long term exposure - local effects		260 mg/m3	
Methanol 67-56-1	general population	Dermal	Acute/short term exposure - systemic effects		8 mg/kg bw/day	
Methanol 67-56-1	general population	Inhalation	Acute/short term exposure - systemic effects		50 mg/m3	
Methanol 67-56-1	general population	oral	Acute/short term exposure - systemic effects		8 mg/kg bw/day	
Methanol 67-56-1	general population	Inhalation	Acute/short term exposure - local effects		50 mg/m3	
Methanol 67-56-1	general population	Dermal	Long term exposure - systemic effects		8 mg/kg bw/day	
Methanol 67-56-1	general population	Inhalation	Long term exposure - systemic effects		50 mg/m3	
Methanol 67-56-1	general population	oral	Long term exposure - systemic effects		8 mg/kg bw/day	
Methanol 67-56-1	general population	Inhalation	Long term exposure - local effects		50 mg/m3	
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene 64742-48-9	Workers	Dermal	Long term exposure - systemic effects		208 mg/kg bw/day	
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene 64742-48-9	Workers	Inhalation	Long term exposure - systemic effects		871 mg/m3	
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene 64742-48-9	general population	Dermal	Long term exposure - systemic effects		125 mg/kg bw/day	
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene 64742-48-9	general population	Inhalation	Long term exposure - systemic effects		185 mg/m3	
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene 64742-48-9	general population	oral	Long term exposure - systemic effects		125 mg/kg bw/day	
Docusate sodium 577-11-7	Workers	Dermal	Long term exposure - systemic effects		31,3 mg/kg bw/day	
Docusate sodium 577-11-7	Workers	Inhalation	Long term exposure - systemic effects		44,1 mg/m3	
Docusate sodium 577-11-7	general population	Inhalation	Long term exposure - systemic effects		13 mg/m3	
Docusate sodium 577-11-7	general population	Dermal	Long term exposure - systemic effects		18,8 mg/kg bw/day	
Docusate sodium 577-11-7	general population	oral	Long term exposure -		18,8 mg/kg bw/day	

			systemic effects			
Solvent naphtha (petroleum), light arom. 64742-95-6	Workers	Dermal	Long term exposure - systemic effects		25 mg/kg bw/day	
Solvent naphtha (petroleum), light arom. 64742-95-6	Workers	Inhalation	Long term exposure - systemic effects		150 mg/m3	
Solvent naphtha (petroleum), light arom. 64742-95-6	general population	Inhalation	Long term exposure - systemic effects		32 mg/m3	
Solvent naphtha (petroleum), light arom. 64742-95-6	general population	Dermal	Long term exposure - systemic effects		11 mg/kg bw/day	
Solvent naphtha (petroleum), light arom. 64742-95-6	general population	oral	Long term exposure - systemic effects		11 mg/kg bw/day	

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Combination filter: ABEKP

This recommendation should be matched to local conditions.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s). Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374.

material thickness > 0.4 mm

Perforation time > 10 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Skin protection:

Suitable protective clothing

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance

gel
liquid
Cloudy, green

Odor

characteristic

Odour threshold

No data available / Not applicable

pH

No data available / Not applicable

Initial boiling point

42 °C (107.6 °F)

Flash point

-18 °C (0.4 °F)

Decomposition temperature

No data available / Not applicable

Vapour pressure

No data available / Not applicable

Density

0,90 - 0,97 g/cm3

(20 °C (68 °F))

Bulk density

No data available / Not applicable

Viscosity

4.500 - 7.000 mPa.s

(; 20 °C (68 °F))

Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Partially miscible
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	
lower	2,3 %(V)
upper	30,5 %(V)
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

May cause damage to organs

Oral toxicity:

Harmful if swallowed.

Inhalative toxicity:

Harmful by inhalation.

The toxicity of the product is due to its narcotic effect after inhalation.

In the event of protracted or repeated exposure, damage to health cannot be excluded.

Dermal toxicity:

Harmful in contact with skin.

Eye irritation:

Causes serious eye irritation.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Methanol 67-56-1	Acute toxicity estimate (ATE)	100 mg/kg	oral			Expert judgement
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene 64742-48-9	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
Docusate sodium 577-11-7	LD50	> 2.000 mg/kg	oral		rat	

Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Methanol 67-56-1	Acute toxicity estimate (ATE)	3 mg/l	Vapour			Expert judgement

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
---------------------------------	---------------	-------	-------------------------	------------------	---------	--------

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Methanol 67-56-1	not irritating		rabbit	BASF Test

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Methanol 67-56-1	not irritating		rabbit	BASF Test

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Methanol 67-56-1	not sensitising	Guinea pig maximisation test	guinea pig	Magnusson and Kligman Method

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Methanol 67-56-1	NOAEL=6,63 mg/l	inhalation	4 weeks 6 h/d, 5 d/w	rat	

SECTION 12: Ecological information**General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.
Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
1,3-Dioxolane 646-06-0	LC50	> 95,4 mg/l	Fish	96 h	Lepomis macrochirus	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,3-Dioxolane 646-06-0	EC50	> 772 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,3-Dioxolane 646-06-0	ErC50	> 877 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEC	877 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methylal 109-87-5	LC50	6.990 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Methylal 109-87-5	EC50	> 500 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methylal 109-87-5	EC10	> 500 mg/l	Algae	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methanol 67-56-1	LC50	> 1.000 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
	NOEC	7.900 mg/l	Fish	200 h	Oryzias latipes	OECD 210 (fish early lite stage toxicity test)
Methanol 67-56-1	EC50	> 10.000 mg/l	Daphnia	48 h	Daphnia magna	
Methanol 67-56-1	EC50	28,44 g/l	Algae		Chlorella pyrenoidosa	OECD Guideline 201 (Alga, Growth Inhibition Test)
Docusate sodium 577-11-7	LC50	10 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
Docusate sodium 577-11-7	EC50	23 mg/l	Daphnia	24 h	Daphnia magna	
Docusate sodium 577-11-7	EC0	22 mg/l	Algae	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
	EC50	47 mg/l	Algae	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09

12.2. Persistence and degradability

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
1,3-Dioxolane 646-06-0		aerobic	20 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Methylal 109-87-5			88 %	OECD 301 A - F
Methanol 67-56-1	readily biodegradable	aerobic	82 - 92 %	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)
Docusate sodium 577-11-7	readily biodegradable	aerobic	68 %	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
---------------------------------	--------	----------------------------------	------------------	---------	-------------	--------

1,3-Dioxolane 646-06-0	-0,35					
Methanol 67-56-1	-0,77					

12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
Methanol 67-56-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene 64742-48-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Docusate sodium 577-11-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

SECTION 14: Transport information**14.1. UN number**

ADR	1263
RID	1263
ADN	1263
IMDG	1263
IATA	1263

14.2. UN proper shipping name

ADR	PAINT
RID	PAINT
ADN	PAINT
IMDG	PAINT
IATA	Paint

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packaging group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	Special provision 640D Tunnelcode: (D/E)
RID	Special provision 640D
ADN	Special provision 640D
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content	10,37 %
(VOCV 814.018 VOC regulation CH)	

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapor.
H226 Flammable liquid and vapor.
H301 Toxic if swallowed.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H331 Toxic if inhaled.
H336 May cause drowsiness or dizziness.
H370 Causes damage to organs.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Label elements (DPD):

F - Highly flammable

Xn - Harmful



Risk phrases:

R11 Highly flammable.
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R68/20/21/22 Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

Safety phrases:

S2 Keep out of the reach of children.
S9 Keep container in a well-ventilated place.
S16 Keep away from sources of ignition - No smoking.
S33 Take precautionary measures against static discharges.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S46 If swallowed, seek medical advice immediately and show this container or label.
S51 Use only in well-ventilated areas.
S52 Not recommended for interior use on large surface areas.
S56 Dispose of this material and its container to hazardous or special waste collection point.

Contains:

Methanol

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.

