

The following Safety Datasheet is provided by Osmo

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: Osmo Polyx Oil Tints



Page 1/9

Material Safety Data Sheets according to 1907/2006/EC, Article 31

Printing date 02.07.2015

Version number 5

Revision: 02.07.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Trade name:	Osmo Polyx® Oil Tints
Article number:	3040, 3067, 3071, 3072, 3073, 3074, 3075
1.2 Relevant identified uses of	f the
substance or mixture and use	S
advised against	No further relevant information available.
Application of the substance /	' the
mixture	Priming
	Coating compound/ Surface coating/ paint
1.3 Details of the supplier of t	he safety data sheet
Manufacturer/Supplier:	Osmo Holz und Color GmbH & Co. KG
	Affhüppen Esch 12
	D-48231 Warendorf
Further information obtainab	le
from:	Product safety department
	Phone: +49 (0) 251 / 692 - 188
	Fax: +49 (0) 251 / 692 - 462
	e-mail: helmut.starp@osmo.de
1.4 Emergency telephone	-
number:	emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

Classification according to Regulation (EC) No 1272/2008	The product is not classified according to the CLP regulation.
2.2 Label elements	
Labelling according to Regulation	n
(EC) No 1272/2008	Void
Hazard pictograms	Void
Signal word	Void
Hazard statements	Void
Precautionary statements	Although this product is not subject to identification regulations, we recommend that
	the safety suggestions are observed.
	Keep out of reach of children.
	If medical advice is needed, have product container or label at hand.
	P271 Use only outdoors or in a well-ventilated area.
	P262 Do not get in eyes, on skin, or on clothing.
	P501 Dispose of contents/container in accordance with local/regional/national/
	international regulations.
	(Contd. on page 2)



Page 2/9

Material Safety Data Sheets according to 1907/2006/EC, Article 31

Printing date 02.07.2015

Version number 5

Revision: 02.07.2015

Trade name: Osmo Polyx® Oil Tints

after use or store

SECTION 3: Composition/information on ingredients 3.2 Mixtures Description: Mixture of substances listed below with nonhazardous additions. Dangerous components:

CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	🚯 Asp. Tox. 1, H304	25-50%
EC number: 918-481-9		~	
Index number: 649-327-00-6			
Reg.nr.: 01-2119457273-39			
Additional information:	For the wording of the listed risk phrases r	efer to section 16.	

SECTION 4: Firs	t aid measures
------------------------	----------------

General information:	Immediately remove any clothing soiled by the product.
,	Take affected persons out into the fresh air.
After inhalation:	Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult
	doctor if symptoms persist.
	In case of unconsciousness place patient stably in side position for transportation.
After skin contact:	Immediately wash with water and soap and rinse thoroughly.
	If skin irritation continues, consult a doctor.
After eye contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing:	If swallowed, seek medical advice immediately and show this container or label.
4.2 Most important symptoms an	d
effects, both acute and delayed	Disziness
	Headache
	(Contd on page 3)

(Contd. on page 3)

GB



Page 3/9

Material Safety Data Sheets

according to 1907/2006/EC, Article 31

Printing date 02.07.2015

Version number 5

Revision: 02.07.2015

(Contd. of page 2)

Trade name: Osmo Polyx® Oil Tints

4.3 Indication of any immediate medical attention and special treatment needed N

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing agents:	CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant
	foam.
For safety reasons unsuitable	
extinguishing agents:	Water with full jet
5.2 Special hazards arising from	
the substance or mixture	Formation of toxic gases is possible during heating or in case of fire.
5.3 Advice for firefighters	
Protective equipment:	Mouth respiratory protective device.
Additional information	Cool endangered receptacles with water spray.
	Dispose of fire debris and contaminated fire fighting water in accordance with official
	regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and	
emergency procedures	Ensure adequate ventilation
	Keep away from ignition sources.
6.2 Environmental precautions:	Inform respective authorities in case of seepage into water course or sewage system.
	Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for	
containment and cleaning up:	Warm water and cleansing agent
	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
6.4 Reference to other sections	See Section 7 for information on safe handling.
	See Section 8 for information on personal protection equipment.
	See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handlingKeep away from heat and direct sunlight.
Use only in well ventilated areas.
Keep receptacles tightly sealed.
Prevent formation of aerosols.

(Contd. on page 4)

GB



Page 4/9

Material Safety Data Sheets according to 1907/2006/EC, Article 31

Printing date 02.07.2015

Version number 5

Revision: 02.07.2015

Trade name: Osmo Polyx® Oil Tints (Contd. of page 3) Information about fire - and *explosion protection:* Keep ignition sources away - Do not smoke. 7.2 Conditions for safe storage, including any incompatibilities Storage: Requirements to be met by Store only in the original receptacle. storerooms and receptacles: Store in a cool location. Information about storage in one common storage facility: Do not store together with alkalis (caustic solutions). Do not store together with oxidising and acidic materials. Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles. Keep container tightly sealed. No further relevant information available. 7.3 Specific end use(s) **SECTION 8: Exposure controls/personal protection** Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workplace: 64742-48-9 aliphatic hydrocarbons, C10-C13 TWA (8 H) Long-term value: 1.000 mg/m³, 150 ppm ppm Source: UK SIA Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic Immediately remove all soiled and contaminated clothing measures: Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Do not carry product impregnated cleaning cloths in trouser pockets. Not necessary if room is well-ventilated. **Respiratory protection:** Use suitable respiratory protective device only when aerosol or mist is formed. Short term filter device: Filter A/P2 **Protection of hands:** Protective gloves

(Contd. on page 5)

⁻ GB



Page 5/9

Material Safety Data Sheets according to 1907/2006/EC, Article 31

Printing date 02.07.2015

Version number 5

Revision: 02.07.2015

Trade name: Osmo Polyx® Oil Tints (Contd. of page 4) The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. To avoid skin problems reduce the wearing of gloves to the required minimum. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Nitrile rubber, NBR Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. For the permanent contact gloves made of the following materials are suitable: Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Nitrile rubber, NBR Eye protection: Goggles recommended during refilling **Body protection:** Protective work clothing

.....

SECTION 9: Physical and chemical properties

General Information		
Appearance:		
Form:	Viscous	
Colour:	According to product specification	
Odour:	Mild	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	> 180 °C	
Flash point:	> 61 °C (DIN 53213)	
Ignition temperature:	240 °C	
Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures ar possible.	
Explosion limits:		
Lower:	0.7 Vol %	



Page 6/9

Material Safety Data Sheets

according to 1907/2006/EC, Article 31

Printing date 02.07.2015

Version number 5

Revision: 02.07.2015

Trade name: Osmo Polyx® Oil Tints

		(Contd. of pag
Upper:	6.0 Vol %	
Density at 20 °C:	0.9-0.95 g/cm ³ (DIN 51757)	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Viscosity:		
Kinematic at 20 °C:	25-40 s (DIN 53211/4 mm)	
	>21 mm²/s (40 °C)	
Solvent content:		
VOC (EC)	< 500 g/l (VOC-max. = 500 g/l (2010 A/i))	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

10.1 Reactivity	
10.2 Chemical stability	
Thermal decomposition /	
conditions to be avoided:	No decomposition if used according to specifications.
10.3 Possibility of hazardous	
reactions	Reacts with fabric soaked in the product (e.g. cleaning wool).
10.4 Conditions to avoid	No further relevant information available.
10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous decomposition	
products:	Carbon monoxide and carbon dioxide
	Nitrogen oxides (NOx)
Additional information:	Warning:
	Wash out any used cloth impregnated with this product immediately after use or store
	in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on toxicological effects Acute toxicity

LD/LC50 values relevant for classification:

64742-48-9 aliphatic hydrocarbons, C10-C13

 Oral
 LD50
 > 5000 mg/kg (rat) (OECD 401)

(Contd. on page 7)

⁻ GB



Page 7/9

Material Safety Data Sheets according to 1907/2006/EC, Article 31

Printing date 02.07.2015

Version number 5

Revision: 02.07.2015

Trade name: Osmo Polyx® Oil Tints (Contd. of page 6) > 5000 mg/kg (rat) (OECD 402) Dermal LD50 Inhalative |LC50 / 4h| > 5 mg/l (rat) (OECD 403)96-29-7 2-butanonoxime Oral LD50 3700 mg/kg (rat) Dermal LD50 200-2000 mg/kg (rat) Inhalative |LC50/4h| > 10.5 mg/l (rat)Primary irritant effect: At long or repeated contact with skin it may cause dermatitis due to the degreasing Skin corrosion/irritation effect of the solvent. not tested Serious eye damage/irritation Respiratory or skin sensitisation Sensitising effect by skin contact is possible by prolonged exposure. Additional toxicological information: The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us. Sensitisation Contains 2-butanonoxime. May produce an allergic reaction.

SECTION 12: Ecological information

12.1 Toxicity			
Aquatic toxicity:			
64742-48-9 aliphatic hydrocarbo	64742-48-9 aliphatic hydrocarbons, C10-C13		
EC50 / 48h > 1000 mg/l (daphnia) (OECD 202)		
EC50/ 72h > 1000 mg/l (algae) (OECD 201)		
LC50 / 96h > 1000 mg/l (fish) (O	ECD 203)		
12.2 Persistence and degradability No further relevant information available.			
12.3 Bioaccumulative potential	No further relevant information available.		
12.4 Mobility in soil	No further relevant information available.		
Additional ecological information:			
General notes:	Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for		
	water		
	Do not allow product to reach ground water, water course or sewage system.		
12.5 Results of PBT and vPvB assessment			
PBT:	Not applicable.		
vPvB:	Not applicable.		
	(Contd. on page 8)		



Page 8/9

Material Safety Data Sheets

according to 1907/2006/EC, Article 31

	Printing date 02.07.2015	Version number 5	Revision: 02.07.2015
Trade name: Osmo Polyx® Oil Tints			
	12.6 Other adverse effects	No further relevant information available.	(Contd. of page 7)
*	SECTION 13: Disposal considerations		
	13.1 Waste treatment methods Recommendation	Must not be disposed together with household garba sewage system.	age. Do not allow product to reach
	European waste catalogue		
	08 01 11 waste paint and varnish containing organic solvents or other dangerous substances		
	15 01 10 packaging containing residues of or contaminated by dangerous substances		
	Uncleaned packaging: Recommendation:	Disposal must be made according to official regulation	ons.
*	SECTION 14: Transport information		
	14.1 UN-Number ADR, ADN, IMDG, IATA	Void	
	14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
	14.3 Transport hazard class(es)		
	ADR, ADN, IMDG, IATA Class	Void	
	14.4 Packing group ADR, IMDG, IATA	Void	
	14.5 Environmental hazards: Marine pollutant:	No	
	14.6 Special precautions for use	<i>r</i> Not applicable.	
	14.7 Transport in bulk accordin MARPOL73/78 and the IBC Co		
	Transport/Additional information	on: Not dangerous according to the above	specifications.
	UN "Model Regulation":		
	L		(Contd. on page 9)



Page 9/9

Material Safety Data Sheets

according to 1907/2006/EC, Article 31

Printing date 02.07.2015

Version number 5

Revision: 02.07.2015

Trade name: Osmo Polyx® Oil Tints

(Contd. of page 8)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:GISBAU-CodeGISCODE: Ö60VOC (EC)< 500 g/l (VOC-max. = 500 g/l (2010 A/i))</td>15.2 Chemical safety assessment:A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases	H304 May be fatal if swallowed and enters airways.	
Department issuing MSDS:	product safety department	
Contact:	Hr. Dr. Starp	
Abbreviations and acronyms:	ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)	
	IMDG: International Maritime Code for Dangerous Goods	
	IATA: International Air Transport Association	
	GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
	EINECS: European Inventory of Existing Commercial Chemical Substances	
	ELINCS: European List of Notified Chemical Substances	
	CAS: Chemical Abstracts Service (division of the American Chemical Society)	
	VOC: Volatile Organic Compounds (USA, EU)	
	LC50: Lethal concentration, 50 percent	
	LD50: Lethal dose, 50 percent	
	Asp. Tox. 1: Aspiration hazard, Hazard Category 1	
* Data compared to the previous		
version altered.		