

The following Safety Datasheet is provided by Osmo

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: Osmo Country Colour



Printing date 26.02.2015

Version number 22

Revision: 26.02.2015

1.1 Product identifier	
Trade name:	Osmo Country Color
Article number:	2101 White, 2203 Light Ochre, 2204 Ivory, 2205 Sunflower Yellow, 2308 Nordic Re 2310 Cedar/Redwood, 2311 Signal Red, 2404 Fir Green, 2501 Labraodor Blue, 250 Royal Blue, 2507 Dove Blue, 2606 Medium Brown, 2607 Dark Brown, 270 Charcoal, 2704 Dusk Grey, 2708 Pebble Grey, 2735 Light Grey, 2742 Traffic Grey
1.2 Relevant identified uses of	f the
substance or mixture and use	25
advised against	No further relevant information available.
Application of the substance	/ the
mixture	Coating compound/ Surface coating/ paint
	Paint
1.3 Details of the supplier of	the safety data sheet
Manufacturer/Supplier:	Osmo Holz und Color GmbH & Co. KG
	Affhüppen Esch 12
	D-48231 Warendorf
Further information obtainal	ble
from:	Product safety department
	Phone: +49 (0) 251 / 692 - 188
	Fax: +49 (0) 251 / 692 - 462
	e-mail: helmut.starp@osmo.de
1.4 Emergency telephone	
number:	emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in Germa
	and English

SECTION 2: Hazards identification

2.1 Classification of the substance Classification according to Regulation (EC) No 1272/2008	<i>e or mixture</i> The product is not classified according to the CLP regulation.
Classification according to	
Directive 67/548/EEC or Directiv	<i>pe</i>
1999/45/EC	Not applicable.
Information concerning	
particular hazards for human an	d
environment:	The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
Classification system:	The classification is according to the latest editions of the EU-lists and extended by company and literature data.
2.2 Label elements	
Labelling according to Regulatio	n
(EC) No 1272/2008	Void
Hazard pictograms	Void
	(Contd. on page 2)



Printing date 26.02.2015

Version number 22

Revision: 26.02.2015

Trade name: Osmo Country Color

	(Contd. of page 1)
Signal word	Void
Hazard statements	Void
Precautionary statements	Although this product is not subject to identification regulations, we recommend that
	the safety suggestions are observed.
	If medical advice is needed, have product container or label at hand.
	Keep out of reach of children.
	P271 Use only outdoors or in a well-ventilated area.
	P262 Do not get in eyes, on skin, or on clothing.
	P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.
Additional information:	Observe the general safety regulations when handling chemicals.
	Always wear a dust mask when sanding.
	Contains 2-butanonoxime. May produce an allergic reaction.
Information concerning	
particular hazards for human	and
environment:	Warning:
	Wash out any used cloth impregnated with this product immediately after use or store
	in an airtight container (danger of self-ignition)
2.3 Other hazards	
Results of PBT and vPvB asses	ssment
PBT:	Not applicable.
vPvB:	Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions. Dangerous components: Xn R65 R66 CAS: 64742-48-9 aliphatic hydrocarbons, C10-C13 25-50% EC number: 918-481-9 Index number: 649-327-00-6 🚯 Asp. Tox. 1, H304 Reg.nr.: 01-2119457273-39 For the wording of the listed risk phrases refer to section 16.

Additional information:

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:	Immediately remove any clothing soiled by the product.
After inhalation:	Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult
	doctor if symptoms persist.
	In case of unconsciousness place patient stably in side position for transportation.
After skin contact:	Immediately wash with water and soap and rinse thoroughly.
	If skin irritation continues, consult a doctor.
After eye contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.
	(Contd. on page 3)



Printing date 26.02.2015

Version number 22

Revision: 26.02.2015

Trade name: Osmo Country Color

After swallowing:	(Contd. of page 2) If swallowed, seek medical advice immediately and show this container or label. Induce vomiting only, if affected person is fully conscious.
4.2 Most important symptoms and effects, both acute and delayed 4.3 Indication of any immediate medical attention and special	<i>R</i> No further relevant information available.
meatcat attention and special treatment needed	No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing agents:	CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant
	foam.
For safety reasons unsuitable	
extinguishing agents:	Water with full jet
5.2 Special hazards arising from	
the substance or mixture	Formation of toxic gases is possible during heating or in case of fire.
5.3 Advice for firefighters	
Protective equipment:	Mouth respiratory protective device.
Additional information	Cool endangered receptacles with water spray.
	Dispose of fire debris and contaminated fire fighting water in accordance with official
	regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and	
emergency procedures	Keep away from ignition sources.
	Ensure adequate ventilation
6.2 Environmental precautions:	Inform respective authorities in case of seepage into water course or sewage system.
	Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for	
containment and cleaning up:	Warm water and cleansing agent
	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
6.4 Reference to other sections	See Section 7 for information on safe handling.
·	See Section 8 for information on personal protection equipment.
	See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep receptacles tightly sealed.Keep away from heat and direct sunlight.Use only in well ventilated areas.

(Contd. on page 4)

Page 4/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.02.2015

Version number 22

Revision: 26.02.2015

Trade name: Osmo Country Color

	(Contd. of	page
	Prevent formation of aerosols.	
Information about fire - and		
explosion protection:	Keep ignition sources away - Do not smoke.	
7.2 Conditions for safe storage,	including any incompatibilities	
Storage:		
Requirements to be met by		
storerooms and receptacles:	Store in a cool location.	
	Store only in the original receptacle.	
Information about storage in o	ne	
common storage facility:	Do not store together with alkalis (caustic solutions).	
	Do not store together with oxidising and acidic materials.	
Further information about		
storage conditions:	Keep container tightly sealed.	
	Store receptacle in a well ventilated area.	
	Protect from frost.	
	Protect from heat and direct sunlight.	
7.3 Specific end use(s)	No further relevant information available.	

SECTION 8: Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

TWA (8 H) Long-term value: Source: UK SIA	1.000 mg/m ³ , 150 ppm ppm
Additional information:	The lists valid during the making were used as basis.
8.2 Exposure controls	
Personal protective equipment	nt:
General protective and hygier	nic
measures:	Immediately remove all soiled and contaminated clothing
	Avoid contact with the eyes and skin.
	Do not eat, drink, smoke or sniff while working.
	Do not carry product impregnated cleaning cloths in trouser pockets.
Respiratory protection:	Use suitable respiratory protective device only when aerosol or mist is formed.
	Not necessary if room is well-ventilated.
	Short term filter device:
	Filter A/P2
Protection of hands:	Protective gloves
	(Contd. on page



Printing date 26.02.2015

Version number 22

Revision: 26.02.2015

Trade name: Osmo Country Color (Contd. of page 4) The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Nitrile rubber, NBR *Penetration time of glove material* The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. For the permanent contact gloves made of the following materials are suitable: Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6). As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR If risk of splashing: Eye protection: Safety glasses according to EN 166:2001 (e.g. densely closing frame glasses with side protection) **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties 9.1 Information on basic physical and chemical properties **General Information** Appearance: Form: Fluid Colour: According to product specification Mild Odour: Change in condition Melting point/Melting range: Undetermined. **Boiling point/Boiling range:** > 180 °C (DIN 51751) ≥ 63 °C (DIN 53213) Flash point: 240 °C Ignition temperature: Product is not selfigniting. Self-igniting: Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible. **Explosion limits:** Lower: 0.6 Vol % (Contd. on page 6) GB



Printing date 26.02.2015

Version number 22

Revision: 26.02.2015

GB

Trade name: Osmo Country Color

		(Contd. of page
Upper:	7.0 Vol %	
Vapour pressure:	3 hPa [20 °C]	
Density at 20 °C:	1.05 - 1.30 g/cm ³ (DIN 51757)	
Solubility in / Miscibility with	!	
water:	Not miscible or difficult to mix.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic at 20 °C:	40-80 s (DIN 53211/4)	
	>21 mm²/s (40 °C)	
Solvent separation test:	< 3 % (ADR 2.2.1.4f)	
Solvent content:		
VOC (EC)	< 400 g/l (VOC-max. = 400 g/l (2010 A/e))	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

10.1 Reactivity	
10.2 Chemical stability	
Thermal decomposition /	
conditions to be avoided:	No decomposition if used and stored according to specifications.
10.3 Possibility of hazardous	
reactions	Reacts with fabric soaked in the product (e.g. cleaning wool).
	Reacts with acids, alkalis and oxidising agents.
10.4 Conditions to avoid	No further relevant information available.
10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous decomposition	
products:	Formation of toxic gases is possible during heating or in case of fire.
	Carbon monoxide and carbon dioxide
	Nitrogen oxides (NOx)
Additional information:	Warning:
	Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)
	(Contd. on page 7)



Printing date 26.02.2015

Version number 22

Revision: 26.02.2015

GB

		(Contd. of
SECTIO	DN 11: To	exicological information
11.1 Infor Acute toxi		toxicological effects
	•	vant for classification:
		c hydrocarbons, C10-C13
Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	
		> 5000 mg/kg (rat) (OECD 402)
		> 5 mg/l (rat) (OECD 403)
	-butanonox	
Oral	LD50	3700 mg/kg (rat)
Dermal	LD50	200-2000 mg/kg (rat)
	LC50 / 4h	>10.5 mg/l (rat)
on the ski on the eye Sensitisati Additiona	:	At long or repeated contact with skin it may cause dermatitis due to the degree effect of the solvent. not tested No sensitising effects known.
informatio		The product is not subject to classification according to the calculation method General EU Classification Guidelines for Preparations as issued in the latest version When used and handled according to specifications, the product does not have harmful effects to our experience and the information provided to us.
Sensitisati	on	Contains 2-butanonoxime. May produce an allergic reaction.
SECTIO	DN 12: Ec	cological information
12.1 Toxid	city	
Aquatic to	oxicity:	
64742-48-	9 aliphatic	hydrocarbons, C10-C13
EC50 / 48	h > 1000 n	ng/l (daphnia) (OECD 202)
EC50/ 72h	n > 1000 n	ng/l (algae) (OECD 201)
		ng/l (fish) (OECD 203)
96-29-7 2	 -butanonox	kime
EC50/48	h 201 mg/l	(daphnia)
	n 11.8 mg/	

Page 8/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.02.2015

Version number 22

Revision: 26.02.2015

Trade name: Osmo Country Color

	(Contd. of page 7)
12.4 Mobility in soil	No further relevant information available.
Additional ecological informa	
General notes:	Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
	Do not allow product to reach ground water, water course or sewage system.
12.5 Results of PBT and vPvB assessment	
PBT:	Not applicable.
vPvB:	Not applicable.
12.6 Other adverse effects	No further relevant information available.
SECTION 13: Disposal considerations	
13.1 Waste treatment methods	S
Recommendation	Must not be disposed together with household garbage. Do not allow product to reach
	sewage system.
European waste catalogue	
-	ish containing organic solvents or other dangerous substances
15 01 10 packaging containing residues of or contaminated by dangerous substances	
Uncleaned packaging:	
Recommendation:	Disposal must be made according to official regulations.
SECTION 14: Transport information	
14.1 UN-Number	
ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping nam	
ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(e	s)
ADR, ADN, IMDG, IATA	
Class	Void
14 4 Deching group	
14.4 Packing group ADR, IMDG, IATA	Void
	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for u	iser Not applicable.
14.7 Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC	
	11
	(Contd. on page 9)



Version number 22

Revision: 26.02.2015

Printing date 26.02.2015 Trade name: Osmo Country Color (Contd. of page 8) Transport/Additional information: Not dangerous according to the above specifications. UN "Model Regulation": **SECTION 15: Regulatory information** 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture National regulations: VOC (EC) < 400 g/l (VOC-max. = 400 g/l (2010 A/e)) 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out. **SECTION 16: Other information** This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. H304 May be fatal if swallowed and enters airways. **Relevant phrases** R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. product safety department Department issuing MSDS: Contact: Hr. Dr. Starp Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Asp. Tox. 1: Aspiration hazard, Hazard Category 1