

A decorative graphic in the top left corner consisting of concentric, wavy orange lines that resemble the grain of wood, curving downwards and to the right.

WOOD FINISHES DIRECT



Finish. Finished.

The following Product Datasheet is provided by **Osmo**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Osmo Garden Furniture Maintenance Kit](#)



WOOD REVIVER POWER GEL

Cleans and refreshes greyed wood highly effectively!



6609
Clear



Power-Gel



PRODUCT DESCRIPTION

Jelly-like special cleaner for refreshing greyed exterior wood. Wood Reviver Power Gel is a non-drip product, and thus it is easy to apply – especially on vertical surfaces. The gel penetrates the wood deeply and removes grey patina. Afterwards by re-applying oils, the fresh warm colour tone of the wood is restored.

RECOMMENDED USE

Osmo Wood Reviver Power Gel is highly recommended for wooden decking, timber cladding, garden furniture and similar surfaces.

INGREDIENTS

Osmo Wood Reviver Power Gel contains biodegradable oxalic acid (<5 %). This product is free of solvents, formaldehyde, chlorine compounds and amines. Detailed declaration of ingredients available upon request.

TECHNICAL DATA

Specific gravity: 0.99-1.05 g/cm³
Viscosity: >70s DIN EN ISO 2431/3 mm, thixotropic
Odour: faint/mild, after drying odourless
Flash point: not applicable

STORAGE

Up to 2 years and longer if container is kept dry, closed tightly and stored at temperatures between 5 and 35°C. Do not expose to frost during transport!

SURFACE PREPARATION

Remove coarse dirt from greyed wood; afterwards dampen with water.
Wood Reviver Power Gel is ready to use, do not thin.
Perform a trial application before treating wood with Wood Reviver Power Gel.

METHODS OF APPLICATION

Apply the gel generously along the wood grain. After approx. 20 minutes clean with a hard brush and rinse with a lot of water. After approx. 48 hours drying time, protect the now newly refreshed wood with a wood finish (e.g. Osmo Natural Oil Woodstain, Decking-Oils, Country Colour).

For mechanical processing on decking, we recommend using Osmo Decking and Flooring Cleaner.

CLEANING OF TOOLS

Immediately after use, with soap and water.

DRYING TIME

Approx. 24-48 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Allow for good ventilation while drying.

COVERAGE

1 litre covers approx. 10 m² with one coat.
Product coverage depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to reduced coverage.

NOTE

Protect metal (e.g. hinges) and plants against direct contact (e.g. cover ornamental and farm plants with a tarpaulin.)



CAUTION

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Observe the general safety regulations when handling chemicals. Safety data sheet upon request.

DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

COLOUR TONES

6609 Clear

CAN SIZES

0.5 L; 2.50 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 06/15