



**WOOD
FINISHES
DIRECT**



Finish. Finished.

The following Product Datasheet is provided by **Osmo**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Osmo Interior Wax](#)



INTERIOR-WAX

Opaque / transparent coloured, satin, hard-wearing finish with a wax-like character for interior wood!



7393 White
Transparent



7394 White
Opaque



PRODUCT DESCRIPTION

Transparent or opaque, satin and tough wood finish with a wax-like character for the interior.

Osmo Interior-Wax is resistant to dirt, water and abrasion and smoothens the surface. The wood grain remains visible.

Simple application – without primer or intermediate sanding – this saves time and money.

Suitable for wood; microporous surface does not crack, peel or flake.

When dry, finish is safe for humans, animals and plants (saliva-resistant and sweatproof acc. DIN 53160 (German industrial norm), suitable for children's toys acc. EN 71.3 (European norm)).

RECOMMENDED USE

Osmo Interior-Wax is suitable as a protection and decorative finish of interior wood: wall and ceiling paneling, moulding and beams as well as furniture, door and children's toys. It is also suitable for recoating and repairing wood that has been factory finished with Osmo Interior-Wax White Transparent (7393) or White Opaque (7394) and for recoating old ceiling panelling.

INGREDIENTS

Based on a polymer dispersion and waxes, titanium dioxide (white pigment), additives and preservatives. Solvent: water. This product fulfils EU regulations (2004/42/EC) according to the VOC content of max. 130 g/l (Cat. A/e (2010)).

Detailed declaration of ingredients available upon request.

TECHNICAL DATA

Specific gravity: 1,10-1,25 g/cm³

Viscosity: 1300-1700 mPas viscid

pH value: 8.0-9.0

Odour: faint/mild, odourless after drying

Flash point: not applicable

STORAGE

Up to 2 years and longer if can is kept dry, closed tightly and stored at temperatures between 5° and 35°C. Do not expose to frost during transport and storage.

SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 18%, apply at min. +10° C).

Osmo Interior-Wax is ready to use, please do not thin. Stir well before use.

Clean old microporous stains thoroughly. Old paints and lacquers must be completely removed. As a general rule, wear a dust mask during sanding works. Fill small cracks, larger joints or holes in wood (with Osmo Wood Filler). Wood treated with Osmo Interior-Wax generally only needs cleaning and recoating.

The finished surface is, among other things, influenced by the wood's natural characteristics. Therefore, a trial application is always required, especially for unfamiliar surfaces.

METHODS OF APPLICATION

With Osmo Natural Bristle Brush Aqua or Microfibre Roller, apply thinly and quickly length by length along the wood grain and spread well. Allow for good ventilation while drying for 3-4 hours.

If necessary, sand surface with fine sandpaper (P 360) before applying the second coat.

After drying, quickly apply a second coat also thinly.

When renovating, one coat applied to the clean and dry surface is usually sufficient.



CLEANING OF TOOLS

Immediately after use, with soap and water.

DRYING TIME

Approx. 3-4 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Allow for good ventilation while drying.

COVERAGE

1 litre covers approx. 16 m² with one coat.

Product coverage depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to reduced coverage.

NOTE

One coat of Interior-Wax White Opaque creates a coloured surface that is more intensive than two coats of Interior-Wax White Transparent.

CAUTION

Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area. Avoid breathing mist/vapours/spray. If in eyes: Rinse cautiously with water for several minutes. Dispose of contents/container in accordance with national regulations (EU Waste Disposal Code AWV 08 01 12).

Safety data sheet upon request.

DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

COLOUR TONES

7393 White Transparent

7394 White Opaque

CAN SIZES

0.75 L, 2.50 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 06/15