

The following Safety Datasheet is provided by **Osmo** 

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: Osmo Liquid Wax Cleaner Spray



Printing date 03.02.2015 Version number 11 Revision: 03.02.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: 3029 Osmo Liquid Wax Cleaner

1.2 Relevant identified uses of the substance or mixture and uses

advised against No further relevant information available.

Application of the substance / the

*mixture* Maintenance product

Cleaning agent/ Cleaner

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Further information obtainable

*from:* Product safety department

Phone: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German

and English

#### SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to

**Regulation** (EC) No 1272/2008 The product is not classified according to the CLP regulation.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

R66: Repeated exposure may cause skin dryness or cracking.

Classification system: The classification is according to the latest editions of the EU-lists and extended by

company and literature data.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008VoidHazard pictogramsVoidSignal wordVoidHazard statementsVoid

**Precautionary statements**Although this product is not subject to identification regulations, we recommend that

the safety suggestions are observed. Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

P271 Use only outdoors or in a well-ventilated area.

(Contd. on page 2)

GB



Printing date 03.02.2015 Version number 11 Revision: 03.02.2015

Trade name: 3029 Osmo Liquid Wax Cleaner

(Contd. of page 1)

P262 Do not get in eyes, on skin, or on clothing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

**Additional information:** Observe the general safety regulations when handling chemicals.

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:Not applicable.vPvB:Not applicable.

#### SECTION 3: Composition/information on ingredients

3.2 Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

EC number: 918-481-9 Index number: 649-327-00-6

Reg.nr.: 01-2119457273-39

CAS: 64742-48-9

aliphatic hydrocarbons, C10-C13

de flydrocarbons, C10-C13

Xn R65 R66

**&** Asp. Tox. 1, H304

50-100%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons  $\geq 30\%$ 

Additional information: For the wording of the listed risk phrases refer to section 16.

#### SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult

doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing:** Do not induce vomiting; call for medical help immediately.

If swallowed, seek medical advice immediately and show this container or label.

4.2 Most important symptoms and

effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special

treatment needed No further relevant information available.

(Contd. on page 3)



Printing date 03.02.2015 Version number 11 Revision: 03.02.2015

Trade name: 3029 Osmo Liquid Wax Cleaner

(Contd. of page 2)

#### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant

foam.

For safety reasons unsuitable

extinguishing agents: Water with full jet

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

**Protective equipment:** Mouth respiratory protective device.

Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official

regulations.

Cool endangered receptacles with water spray.

#### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

*emergency procedures* Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

**6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

**6.4 Reference to other sections** See Section 13 for disposal information.

#### SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep receptacles tightly sealed.

Use only in well ventilated areas.

Keep away from heat and direct sunlight.

Prevent formation of aerosols.

Information about fire - and

*explosion protection:* Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

(Contd. on page 4)



Printing date 03.02.2015 Version number 11 Revision: 03.02.2015

Trade name: 3029 Osmo Liquid Wax Cleaner

(Contd. of page 3)

Store in a cool location.

Information about storage in one

common storage facility: Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

Further information about

storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 10

7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

64742-48-9 aliphatic hydrocarbons, C10-C13

TWA (8 H) Long-term value: 1.000 mg/m<sup>3</sup>, 150 ppm ppm

Source: UK SIA

**Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment: General protective and hygienic

*measures:* Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Keep away from foodstuffs, beverages and feed.

**Respiratory protection:** Not necessary if room is well-ventilated.

**Protection of hands:** To avoid skin problems reduce the wearing of gloves to the required minimum.

Material of gloves Nitrile rubber, NBR

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective

gloves and has to be observed.

For the permanent contact gloves made of the following materials

are suitable: Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4 \text{ mm}$ 

For the mixture of chemicals mentioned below the penetration time has to be at least

480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following

materials are suitable: Nitrile rubber, NBR

Eye protection: Goggles recommended during refilling

(Contd. on page 5)



Printing date 03.02.2015 Version number 11 Revision: 03.02.2015

Trade name: 3029 Osmo Liquid Wax Cleaner

(Contd. of page 4)

**Body protection:** Protective work clothing

### SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

**General Information** 

Appearance:

Form: Fluid
Colour: Yellowish
Odour: Mild

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 180-210 °C

*Flash point:* ~62 °C (DIN 53213)

*Ignition temperature:* ~200 °C

**Decomposition temperature:** Not determined.

**Self-igniting:** Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are

possible.

**Explosion limits:** 

 Lower:
 0.6 Vol %

 Upper:
 7.0 Vol %

Vapour pressure at 20 °C: <1 hPa

**Density at 20 °C:** 0.77-0.80 g/cm³ (DIN 51757)

Relative densityNot determined.Evaporation rateNot determined.

Solubility in / Miscibility with

water: Insoluble.

Viscosity:

**Dynamic at 23 °C:** ~18 mPas (DIN 53214)

*Kinematic at 40 °C:*  $> 20 \text{ mm}^2/\text{s}$ 

Solvent content:

*VOC (EC)* ~90 %

**9.2 Other information** No further relevant information available.

(Contd. on page 6)



Printing date 03.02.2015 Version number 11 Revision: 03.02.2015

### Trade name: 3029 Osmo Liquid Wax Cleaner

(Contd. of page 5)

### SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous

reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition

products: No hazardous decomposition products when stored and handled correctly.

#### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Acute toxicity:

| LD/LC50 value: | s relevant foi | r classification: |
|----------------|----------------|-------------------|
|----------------|----------------|-------------------|

#### 64742-48-9 aliphatic hydrocarbons, C10-C13

| Oral       | LD50      | > 5000 mg/kg (rat) (OECD 401) |
|------------|-----------|-------------------------------|
| Dermal     | LD50      | > 5000 mg/kg (rat) (OECD 402) |
| Inhalative | LC50 / 4h | 21 mg/l (rat) (OECD 403)      |

Primary irritant effect:

on the skin: At long or repeated contact with skin it may cause dermatitis due to the degreasing

effect of the solvent.

on the eye: not tested

Sensitisation: No sensitising effects known.

Additional toxicological

information: When used and handled according to specifications, the product does not have any

harmful effects to our experience and the information provided to us.

#### SECTION 12: Ecological information

#### 12.1 Toxicity

| Aquatic toxicity:    |                                  |
|----------------------|----------------------------------|
| 64742-48-9 aliphatic | hydrocarbons, C10-C13            |
| Biolog. Abbaubarkeit | (-) (leicht abbaubar)            |
| EC50 / 48h           | > 1000 mg/l (daphnia) (OECD 202) |

EC50/ 72h > 1000 mg/l (algae) (OECD 201)

LC50 / 96h > 1000 mg/l (fish) (OECD 203)

(Contd. on page 7)



Printing date 03.02.2015 Version number 11 Revision: 03.02.2015

### Trade name: 3029 Osmo Liquid Wax Cleaner

(Contd. of page 6)

12.2 Persistence and degradability No further relevant information available.
12.3 Bioaccumulative potential No further relevant information available.
12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for

water

Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

*PBT*: Not applicable.*vPvB*: Not applicable.

12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

13.1 Waste treatment methods

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach

sewage system.

European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

15 01 10\* packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

Recommended cleansing agents: Solvent naphtha

| SECTION 1 | 4: Transport | information |
|-----------|--------------|-------------|
|           |              |             |

| 14.1 UN-Number<br>ADR, ADN, IMDG, IATA               | Void |  |
|--|------|--|
| 14.2 UN proper shipping name<br>ADR, ADN, IMDG, IATA | Void |  |
| 14.3 Transport hazard class(es)                      |      |  |
| ADR, ADN, IMDG, IATA                                 |      |  |
| Class  | Void |  |
| 14.4 Packing group                                   |      |  |
| ADR, IMDG, IATA                                      | Void |  |
| 14.5 Environmental hazards:                          |      |  |
| Marine pollutant:                                    | No   |  |

(Contd. on page 8)



Printing date 03.02.2015 Version number 11 Revision: 03.02.2015

### Trade name: 3029 Osmo Liquid Wax Cleaner

(Contd. of page 7)

14.6 Special precautions for user Not applicable.

14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

UN "Model Regulation":

#### SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the

substance or mixture No further relevant information available.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases** H304 May be fatal if swallowed and enters airways.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

**Department issuing MSDS:** product safety department

Contact: Hr. Dr. Starp

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

\* Data compared to the previous

version altered.

GE

Printing date 27.01.2014 Version number 11 Revision: 27.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Osmo Liquid Wax Cleaner Spray, clear

1.2 Relevant identified uses of the substance or mixture and uses

advised against No further relevant information available.

Application of the substance / the

*mixture* Maintenance product

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Further information obtainable

*from:* Product safety department

Phone: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German

and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

F+; Extremely flammable

R12: Extremely flammable.

R66: Repeated exposure may cause skin dryness or cracking.

Information concerning

particular hazards for human and

environment: The product has to be labelled due to the calculation procedure of the "General

Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

Classification system: The classification is according to the latest editions of the EU-lists and extended by

company and literature data.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms

CH20.

(Contd. on page 2)

Signal word

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.01.2014 Version number 11 Revision: 27.01.2014

| Trade name: Os | mo Liquid | Wax Cleaner | Spray, clear |
|----------------|-----------|-------------|--------------|
|----------------|-----------|-------------|--------------|

Danger

(Contd. of page 1)

| Signai wora   | Danger   |   |
|---|----------|---|
| Hazard statements   | H222-H22 | 29 Extremely flammable aerosol. Pressurized container: May burst if heated. |
| <b>Precautionary statements</b> P101 If medical advice is |          | If medical advice is needed, have product container or label at hand.       |
|   | P102     | Keep out of reach of children.  |
|   | P103     | Read label before use.  |
|   | P210     | Keep away from heat, hot surfaces, sparks, open flames and other ignition   |
|   |          |   |

sources. No smoking. P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P262 Do not get in eyes, on skin, or on clothing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

°F.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Additional information: EUH066 Repeated exposure may cause skin dryness or cracking.

Pressurized container: protect from sunlight and do not expose to temperatures

exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources

of ignition - No smoking.

#### 2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Mixture of substances listed below with nonhazardous additions. Description:

| Dangerous components:      |                                |              |
|----------------------------|--------------------------------|--------------|
| CAS: 64742-49-0            | aliphatic hydrocarbons, C9-C10 | 50-75%       |
| EC number: 927-241-2       | <b>▼</b> Xn R65                |              |
| Index number: 649-328-00-1 | R10-52/53-66-67                |              |
| Reg.nr.: 01-2119471843-32  | Flam. Liq. 3, H226             |              |
|                            | <b>♦</b> Asp. Tox. 1, H304     |              |
|                            | STOT SE 3, H336                |              |
|                            | Aquatic Chronic 3, H412        |              |
|                            | (Cont                          | d on page 3) |

(Contd. on pag

Printing date 27.01.2014 Version number 11 Revision: 27.01.2014

| Trade name: Osmo | Liquid | Wax | Cleaner | Spray, | clear |
|------------------|--------|-----|---------|--------|-------|
|------------------|--------|-----|---------|--------|-------|

|                            | (0                | contd. of page 2) |
|----------------------------|-------------------|-------------------|
| CAS: 106-97-8              | butane            | 10-25%            |
| EINECS: 203-448-7          | F+ R12            |                   |
| Index number: 601-004-00-0 | Flam. Gas 1, H220 |                   |
|                            | Press. Gas, H280  |                   |
| CAS: 74-98-6               | propane           | 2.5-10%           |
| EINECS: 200-827-9          | F+ R12            |                   |
| Index number: 601-003-00-5 |                   |                   |
|                            | Press. Gas, H280  |                   |
| CAS: 75-28-5               | isobutane         | ≤ 2.5%            |
| EINECS: 200-857-2          | F+ R12            |                   |
| Index number: 601-004-01-8 | Flam. Gas 1, H220 |                   |
|                            | Press. Gas, H280  |                   |

Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons ≥ 30%

Additional information:

For the wording of the listed risk phrases refer to section 16.

#### SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult

doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor. If swallowed, seek medical advice immediately and show this container or label. After swallowing:

4.2 Most important symptoms and

Headache effects, both acute and delayed

Dizziness

4.3 Indication of any immediate

medical attention and special

treatment needed No further relevant information available.

#### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant Suitable extinguishing agents:

foam.

For safety reasons unsuitable

Water with full jet extinguishing agents:

(Contd. on page 4)

Printing date 27.01.2014 Version number 11 Revision: 27.01.2014

## Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 3)

5.2 Special hazards arising from

the substance or mixture Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

**Protective equipment:** Mouth respiratory protective device.

**Additional information** Dispose of fire debris and contaminated fire fighting water in accordance with official

regulations.

Cool endangered receptacles with water spray.

### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

*emergency procedures* Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Warm water and cleansing agent

Ensure adequate ventilation.

**6.4 Reference to other sections** See Section 13 for disposal information.

#### SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep away from heat and direct sunlight.

Keep receptacles tightly sealed. Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about fire - and

explosion protection: Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures

exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

#### 7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

Information about storage in one

common storage facility: Do not store together with alkalis (caustic solutions).

Do not store together with oxidizing and acidic materials.

(Contd. on page 5)

Printing date 27.01.2014 Version number 11 Revision: 27.01.2014

## Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 4)

Further information about

storage conditions: Store only outside or in explosion proof rooms.

Store in a cool place. Heat will increase pressure and may lead to the receptacle

bursting.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

8.1 Control parameters

| Ingredients | with limi     | t values th | at reauire | monitoring   | at the  | worknlace: |
|-------------|---------------|-------------|------------|--------------|---------|------------|
| III Calcito | TV CUIT CUITU | i raines in | at require | III O I LILL | ui iiic | mornipude. |

#### 64742-49-0 aliphatic hydrocarbons, C9-C10

TWA (8 H) Short-term value: 1000 mg/m<sup>3</sup>

Source UK SIA

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

74-98-6 propane

AGW Long-term value: 1800 mg/m³, 1000 ppm

4(II);DFG

**75-28-5** isobutane

OEL Short-term value: 3800 mg/m³, 750 ppm

Long-term value: 1900 mg/m³, 600 ppm

EH 40/97

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment: General protective and hygienic

*measures:* Do not inhale gases / fumes / aerosols.

Immediately remove all soiled and contaminated clothing

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

**Respiratory protection:** Not necessary if room is well-ventilated.

(Contd. on page 6)

GB

Printing date 27.01.2014 Version number 11 Revision: 27.01.2014

### Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 5)

In case of brief exposure or low pollution use respiratory filter device. In case of

intensive or longer exposure use self-contained respiratory protective device. Use suitable respiratory protective device in case of insufficient ventilation.

Filter P3

**Protection of hands:** The glove material has to be impermeable and resistant to the product/ the substance/

the preparation.

Selection of the glove material on consideration of the penetration times, rates of

diffusion and the degradation

Material of gloves Nitrile rubber, NBR

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective

gloves and has to be observed.

For the permanent contact gloves made of the following materials

are suitable: Nitrile rubber, NBR

For the mixture of chemicals mentioned below the penetration time has to be at least

480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following

materials are suitable:Nitrile rubber, NBREye protection:Tightly sealed gogglesBody protection:Protective work clothing

#### SECTION 9: Physical and chemical properties

| 9.1      | Information | i on ha | sic nhy  | sical and | d chemic | al properties |
|----------|-------------|---------|----------|-----------|----------|---------------|
| <b>1</b> | my or manor | on ou   | sic pity | sicui uni | i chemic | at properties |

**General Information** 

Appearance:

Form: Aerosol
Colour: Colourless
Odour: Characteristic

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

Flash point: Not applicable, as aerosol.

Self-igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are

possible.

Explosion limits:

 Lower:
 0.8 Vol %

 Upper:
 8.5 Vol %

(Contd. on page 7)

Printing date 27.01.2014 Version number 11 Revision: 27.01.2014

### Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 6)

| Vapour pressure at 20 °C:        | 10 hPa                                     |
|----------------------------------|--|
| Density:                         | Not determined.                            |
| Solubility in / Miscibility with |  |
| water:                           | Not miscible or difficult to mix.          |
| 9.2 Other information            | No further relevant information available. |

#### SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: Pressurized container: protect from sunlight and do not expose to temperatures

exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Store in a cool place. Heat will increase pressure and may lead to the receptacle

bursting.

10.3 Possibility of hazardous

reactions

10.4 Conditions to avoid

10.5 Incompatible materials:

10.6 Hazardous decomposition

products:

Forms explosive gas mixture with air. No further relevant information available.

No further relevant information available.

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

#### SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

| LD/LC50    | values relev | vant for classification:      |
|------------|--------------|-------------------------------|
| 64742-48-  | 9 aliphatic  | hydrocarbons, C10-C13         |
| Oral       | LD50         | > 5000 mg/kg (rat) (OECD 401) |
| Dermal     | LD50         | > 5000 mg/kg (rat) (OECD 402) |
| Inhalative | LC50 / 4h    | 21 mg/l (rat) (OECD 403)      |
| 106-97-8   | butane       |                               |
| Inhalative | LC50 / 4h    | 658 mg/l (rat)                |

Primary irritant effect:

on the skin: At long or repeated contact with skin it may cause dermatitis due to the degreasing

effect of the solvent.

on the eye: Irritating effect.

(Contd. on page 8)

Printing date 27.01.2014 Version number 11 Revision: 27.01.2014

## Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 7)

Sensitization: No sensitizing effects known.

#### SECTION 12: Ecological information

#### 12.1 Toxicity

| Aquatic toxicity:    |                                  |
|----------------------|----------------------------------|
| 64742-48-9 aliphatic | hydrocarbons, C10-C13            |
| Biolog. Abbaubarkeit | (-) (leicht abbaubar)            |
| EC50 / 48h           | > 1000 mg/l (daphnia) (OECD 202) |
| EC50/ 72h            | > 1000 mg/l (algae) (OECD 201)   |
| LC50 / 96h           | > 1000 mg/l (fish) (OECD 203)    |

12.2 Persistence and degradability No further relevant information available.
 12.3 Bioaccumulative potential No further relevant information available.
 12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for

water

Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

*PBT*: Not applicable.*vPvB*: Not applicable.

12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach

sewage system.

| Europear | i waste catalogue  |
|----------|--|
| 08 01 11 | waste paint and varnish containing organic solvents or other dangerous substances                              |
| 16 05 05 | gases in pressure containers other than those mentioned in 16 05 04  |
| 15 01 11 | metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure |
|          | containers   |

Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

Recommended cleansing agents: Solvent naphtha

(Contd. on page 9)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 27.01.2014 Version number 11 Revision: 27.01.2014

## Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 8)

| ROSOLS DLS DLS, flammable ases. |
|---------------------------------|
| DLS, flammable                  |
| DLS, flammable                  |
| DLS, flammable                  |
| DLS, flammable                  |
|                                 |
| ises.                           |
| nses.                           |
| nses.                           |
|                                 |
|                                 |
|                                 |
|                                 |
|                                 |
|                                 |
|                                 |
|                                 |
|                                 |
| : Gases.                        |
|                                 |
|                                 |
|                                 |
| icable.                         |
|                                 |
|                                 |
|                                 |
|                                 |
|                                 |

### SECTION 15: Regulatory information

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

Printing date 27.01.2014 Version number 11 Revision: 27.01.2014

### Trade name: Osmo Liquid Wax Cleaner Spray, clear

(Contd. of page 9)

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

R10 Flammable.

R12 Extremely flammable.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

**Department issuing MSDS:** product safety department

Contact:

Hr. Dr. Starp

Abbreviations and acronyms: ADR: Accord

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

\* Data compared to the previous

version altered.

GE