



**WOOD  
FINISHES  
DIRECT**



Finish. Finished.

The following Safety Datasheet is provided by **Osmo**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Osmo Natural Oil Woodstain Effect](#)

**Safety data sheet**  
 according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 5

Revision: 04.02.2015

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**Trade name:** Osmo Natural Oil Woodstain Effect

**Article number:** 1140, 1141, 1142, 1143

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**advised against** No further relevant information available.

**Application of the substance / the mixture**

Paint  
 Coating compound/ Surface coating/ paint

**1.3 Details of the supplier of the safety data sheet**

**Manufacturer/Supplier:** Osmo Holz und Color GmbH & Co. KG  
 Affhüppen Esch 12  
 D-48231 Warendorf

**Further information obtainable from:**

Product safety department  
 Phone: +49 (0) 251 / 692 - 188  
 Fax: +49 (0) 251 / 692 - 462  
 e-mail: helmut.starp@osmo.de

**1.4 Emergency telephone number:**

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3 H226 Flammable liquid and vapour.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

**Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

R10-52/53: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

**Classification system:**

The classification is according to the latest editions of the EU-lists and extended by company and literature data.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**

GHS02

(Contd. on page 2)

**Safety data sheet**  
 according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 5















Revision: 04.02.2015

**Trade name: Osmo Natural Oil Woodstain Effect**

(Contd. of page 1)

<b>Signal word</b>	Warning
<b>Hazard statements</b>	H226 Flammable liquid and vapour. H412 Harmful to aquatic life with long lasting effects.
<b>Precautionary statements</b>	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat/open flames. - No smoking. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Additional information:</b>	Observe the general safety regulations when handling chemicals. Always wear a dust mask when sanding. Contains propiconazole, 2-butanonoxime. May produce an allergic reaction.
<b>2.3 Other hazards</b>	
<b>Results of PBT and vPvB assessment</b>	
<b>PBT:</b>	Not applicable.
<b>vPvB:</b>	Not applicable.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.

<b>Dangerous components:</b>		
CAS: 64742-48-9 EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39	aliphatic hydrocarbons, C10-C13  Xn R65 R66  Asp. Tox. 1, H304	25-50%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60	(2-methoxymethylethoxy)propanol substance with a Community workplace exposure limit	10-<25%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol  Xi R36;  F R11 R67  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336	1-<2.5%
CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-002-00-1 Reg.nr.: 01-2119529243-45	aluminium powder (stabilised)  F R11  Flam. Sol. 1, H228	1-<2.5%
CAS: 60207-90-1 EINECS: 262-104-4 Index number: 613-205-00-0	propiconazole  Xn R22;  Xi R43;  N R50/53  Aquatic Acute 1, H400;  Aquatic Chronic 1, H410;  Acute Tox. 4, H302; Skin Sens. 1, H317	<1%

(Contd. on page 3)

**Safety data sheet**  
 according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 5

Revision: 04.02.2015

**Trade name: Osmo Natural Oil Woodstain Effect**

**Additional information:**

For the wording of the listed risk phrases refer to section 16.

(Contd. of page 2)

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

**General information:**

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

**After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing:**

Induce vomiting only, if affected person is fully conscious.

If swallowed, seek medical advice immediately and show this container or label.

#### 4.2 Most important symptoms and effects, both acute and delayed

Headache

Disziness

#### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

**Suitable extinguishing agents:**
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
**For safety reasons unsuitable extinguishing agents:**

Water with full jet

#### 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

#### 5.3 Advice for firefighters

**Protective equipment:**

Mouth respiratory protective device.

**Additional information**

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

(Contd. on page 4)

**Safety data sheet**  
 according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 5

Revision: 04.02.2015

**Trade name: Osmo Natural Oil Woodstain Effect**

(Contd. of page 3)

- 6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:** Warm water and cleansing agent  
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).  
 Ensure adequate ventilation.
- 6.4 Reference to other sections** See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling** Keep receptacles tightly sealed.  
 Use only in well ventilated areas.  
 Keep away from heat and direct sunlight.  
 Prevent formation of aerosols.

**Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.

**7.2 Conditions for safe storage, including any incompatibilities**
**Storage:**

- Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.  
 Store in a cool location.

**Information about storage in one common storage facility:**

- Do not store together with alkalis (caustic solutions).  
 Do not store together with oxidising and acidic materials.

**Further information about storage conditions:**

- Store receptacle in a well ventilated area.  
 Protect from frost.  
 Keep container tightly sealed.  
 Store in cool, dry conditions in well sealed receptacles.

**Storage class:** 3

- 7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

**Additional information about design of technical facilities:** No further data; see item 7.

**8.1 Control parameters**
**Ingredients with limit values that require monitoring at the workplace:**
**64742-48-9 aliphatic hydrocarbons, C10-C13**

TWA (8 H)	Long-term value: 1.000 mg/m <sup>3</sup> , 150 ppm ppm Source: UK SIA
-----------	--

(Contd. on page 5)

**Safety data sheet**  
 according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 5

Revision: 04.02.2015

**Trade name: Osmo Natural Oil Woodstain Effect**

(Contd. of page 4)

**34590-94-8 (2-methoxymethylethoxy)propanol**

WEL	Long-term value: 308 mg/m <sup>3</sup> , 50 ppm Sk
-----	---

**67-63-0 propan-2-ol**

WEL	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm Long-term value: 999 mg/m <sup>3</sup> , 400 ppm
-----	--

**Additional information:** The lists valid during the making were used as basis.

**8.2 Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.  
 Do not carry product impregnated cleaning cloths in trouser pockets.  
 Immediately remove all soiled and contaminated clothing  
 Keep away from foodstuffs, beverages and feed.  
 Avoid contact with the eyes and skin.  
 Do not inhale gases / fumes / aerosols.

**Respiratory protection:**

Use suitable respiratory protective device only when aerosol or mist is formed.  
 Not necessary if room is well-ventilated.  
 Short term filter device:

Gas filter EN 14387 Type A (organic gas / vapor (boiling point > 65 °C)).

**Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Nitrile rubber, NBR

**Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact gloves****made of the following materials****are suitable:**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

**As protection from splashes****gloves made of the following****materials are suitable:**

Nitrile rubber, NBR

**Eye protection:**

Goggles recommended during refilling

**Body protection:**

Protective work clothing

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 5

Revision: 04.02.2015

**Trade name: Osmo Natural Oil Woodstain Effect**

(Contd. of page 5)

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

**Appearance:**

<b>Form:</b>	Fluid
<b>Colour:</b>	According to product specification
<b>Odour:</b>	Mild

**Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	> 180 °C

**Flash point:** 43-59 °C (DIN 53213)

**Ignition temperature:** 240 °C

**Self-igniting:** Product is not selfigniting.

**Danger of explosion:** Product does not present an explosion hazard.

**Explosion limits:**

<b>Lower:</b>	0.6 Vol %
<b>Upper:</b>	7.0 Vol %

**Density at 20 °C:** 0.97-0.99 g/cm<sup>3</sup> (DIN 51757)

**Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

**Viscosity:**

<b>Kinematic at 20 °C:</b>	43-60 s (DIN 53211/4)
	>21 mm <sup>2</sup> /s (40 °C)

**Solvent content:**

**VOC (EC)** < 400 g/l (VOC-max. = 400 g/l (2010 A/e))

**9.2 Other information**

No further relevant information available.

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

**10.2 Chemical stability**

**Thermal decomposition / conditions to be avoided:**

No decomposition if used and stored according to specifications.

**10.3 Possibility of hazardous reactions**

Reacts with fabric soaked in the product (e.g. cleaning wool).  
Reacts with acids, alkalis and oxidising agents.

**10.4 Conditions to avoid**

No further relevant information available.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 5

Revision: 04.02.2015

**Trade name: Osmo Natural Oil Woodstain Effect**

(Contd. of page 6)

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:**

Carbon monoxide and carbon dioxide  
Nitrogen oxides (NOx)

**Additional information:**

Warning:  
Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity:

##### LD/LC50 values relevant for classification:

##### 64742-48-9 aliphatic hydrocarbons, C10-C13

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	>20 mg/l (rat) (OECD 403)

##### 60207-90-1 propiconazole

Oral	LD50	660 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rat)
Inhalative	LC50 / 4h	5.27 mg/l (rat)
	LC50 / 72h	0.76 mg/l (algae)

##### 96-29-7 2-butanonoxime

Oral	LD50	3700 mg/kg (rat)
Dermal	LD50	200-2000 mg/kg (rat)
Inhalative	LC50 / 4h	>10.5 mg/l (rat)

##### Primary irritant effect:

**on the skin:** At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

**on the eye:** not tested

**Sensitisation:** Sensitising effect by skin contact is possible by prolonged exposure.

##### Additional toxicological information:

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

**Sensitisation** Contains propiconazole, 2-butanonoxime. May produce an allergic reaction.

(Contd. on page 8)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 5

Revision: 04.02.2015

**Trade name: Osmo Natural Oil Woodstain Effect**

(Contd. of page 7)

**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:****64742-48-9 aliphatic hydrocarbons, C10-C13**

Biolog. Abbaubarkeit	(-) (leicht abbaubar)
EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)

**96-29-7 2-butanonoxime**

EC50 / 48h	201 mg/l (daphnia)
IC50 / 72h	11.8 mg/l (algae)
LC50 / 96h	>100 mg/l (fish)

**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**Ecotoxicological effects:****Remark:** Harmful to fish**Additional ecological information:****General notes:** Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Danger to drinking water if even small quantities leak into the ground.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.**European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 10*	packaging containing residues of or contaminated by dangerous substances

**Uncleaned packaging:****Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 9)

**Safety data sheet**  
 according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 5

Revision: 04.02.2015

**Trade name: Osmo Natural Oil Woodstain Effect**

(Contd. of page 8)

**Recommended cleansing agents:** Solvent naphtha

**SECTION 14: Transport information**

**14.1 UN-Number**

**ADR, IMDG, IATA** UN1263

**14.2 UN proper shipping name**

**ADR** 1263 PAINT  
**IMDG, IATA** PAINT

**14.3 Transport hazard class(es)**

**ADR**  
**Class** 3 (F1) Flammable liquids.  
**Label** 3

**IMDG, IATA**

**Class** 3 Flammable liquids.  
**Label** 3

**14.4 Packing group**

**ADR, IMDG, IATA** III

**14.5 Environmental hazards:**

**Marine pollutant:** No

**14.6 Special precautions for user**

Warning: Flammable liquids.  
**Danger code (Kemler):** 30  
**EMS Number:** F-E,S-E

**14.7 Transport in bulk according to Annex II of**

**MARPOL73/78 and the IBC Code** Not applicable.

**Transport/Additional information:**

**ADR**

**Limited quantities (LQ)** 5L  
**Excepted quantities (EQ)** Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml

**Transport category** 3  
**Tunnel restriction code** D/E

**IMDG**

**Limited quantities (LQ)** 5L

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 5

Revision: 04.02.2015

**Trade name: Osmo Natural Oil Woodstain Effect**

(Contd. of page 9)

**Exempted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

**UN "Model Regulation":**

UN1263, PAINT, 3, III

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulations:

**VOC (EC)** < 400 g/l (VOC-max. = 400 g/l (2010 A/e))

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- H225 Highly flammable liquid and vapour.
- H228 Flammable solid.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- R11 Highly flammable.
- R22 Harmful if swallowed.
- R36 Irritating to eyes.
- R43 May cause sensitisation by skin contact.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

**Department issuing MSDS:**

product safety department

**Contact:**

Hr. Dr. Starp

**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 5

Revision: 04.02.2015

**Trade name: Osmo Natural Oil Woodstain Effect**

(Contd. of page 10)

ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
Flam. Liq. 2: Flammable liquids, Hazard Category 2  
Flam. Liq. 3: Flammable liquids, Hazard Category 3  
Flam. Sol. 1: Flammable solids, Hazard Category 1  
Acute Tox. 4: Acute toxicity, Hazard Category 4  
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1  
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
Asp. Tox. 1: Aspiration hazard, Hazard Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1  
  
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

**\* Data compared to the previous  
version altered.**

