

The following Safety Datasheet is provided by **Osmo** 

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

Osmo Paint Stripper



Printing date 27.03.2020 Version number 2.1 Revision: 27.03.2020

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

*Trade name:* Paint Stripper

Article number: 6000

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

Application of the substance

/ the mixture Paint remover

For removing synthetic resin varnishes, oil paints, thick-film glazes,

architectural coatings.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Further information

obtainable from: Product safety department

Tel.: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in

German and English

#### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H302 Harmful if swallowed. Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements

Hazard pictograms

CH80.

GHS07

Signal word Warning

Hazard-determining

components of labelling: 1-butylpyrrolidin-2-one

formic acid

**Hazard statements** H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

(Contd. on page 2)



Printing date 27.03.2020 Version number 2.1 Revision: 27.03.2020

Trade name:	<b>Paint</b>	Stripper
-------------	--------------	----------

(Contd. of page 1)

**Precautionary statements** P101 If medical advice is needed, have product container or label

at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you

feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists: Get medical advice/attention.
P501 Dispose of contents/container in accordance with national

regulations.

**2.3 Other hazards** Always wear a dust mask when sanding.

Observe the general safety regulations when handling chemicals.

Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

3.2 Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

	Dangerous components:		
ĺ	CAS: 3470-98-2 EINECS: 222-437-8	1-butylpyrrolidin-2-one	10–25%
	Reg.nr.: 01-2120062728-48-0000	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
Ī	CAS: 64-18-6	formic acid	≥2–≤2.5%
	EINECS: 200-579-1	Skin Corr. 1A, H314; (1) Acute Tox. 4, H302	
	Index number: 607-001-00-0	Skin Corr. 1A, H314;  Acute Tox. 4, H302 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 2 %	
		Eye Irrit. 2; H319: C ≥ 2 %	

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

**General information:** Symptoms of poisoning may even occur after several hours; therefore medical

observation for at least 48 hours after the accident.

After inhalation: In case of unconsciousness place patient stably in side position for

transportation.

Take affected persons out into the fresh air.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)



Printing date 27.03.2020 Version number 2.1 Revision: 27.03.2020

Trade name: Paint Stripper

(Contd. of page 2)

After eye contact: Rinse opened eye for several minutes under running water. If symptoms

persist, consult a doctor.

**After swallowing:** Call for a doctor immediately.

Rinse mouth.

4.2 Most important symptoms and effects, both acute and

**delayed** No further relevant information available.

4.3 Indication of any

immediate medical attention

and special treatment needed No further relevant information available.

#### SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing

agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

For safety reasons unsuitable

extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or

mixture Formation of gases harmful to health possible when heated or in the event of

fire.

Do not inhale explosion gases or combustion gases.

5.3 Advice for firefighters

**Protective equipment:** Mouth respiratory protective device.

**Additional information** Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the

sewage system.

#### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Keep away from ignition sources.

Do not breathe vapour/spray. Ensure adequate ventilation

6.2 Environmental

precautions: Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders).

(Contd. on page 4)



Printing date 27.03.2020 Version number 2.1 Revision: 27.03.2020

Trade name: Paint Stripper

(Contd. of page 3)

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other

sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

7.1 Precautions for safe

**handling** Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and

**explosion protection:** No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Information about storage in

one common storage facility: Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

Further information about

**storage conditions:** Protect from frost.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 10

**7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

64-18-6 formic acid

WEL Long-term value: 9.6 mg/m³, 5 ppm

**DNELs** Ameisensäure

INDEX-Nr. 607-001-00-0 / EG-Nr. 200-579-1 / CAS-Nr. 64-18-6

DNEL akut inhalativ (lokal), Arbeitnehmer: 19 mg/m³
DNEL akut inhalativ (systemisch), Arbeitnehmer: 19 mg/m³
DNEL Langzeit inhalativ (lokal), Arbeitnehmer: 9,5 mg/m³
DNEL Langzeit inhalativ (systemisch), Arbeitnehmer: 9,5 mg/m³

DNEL akut inhalativ (lokal), Verbraucher: 9,5 mg/m³

(Contd. on page 5)



Printing date 27.03.2020 Version number 2.1 Revision: 27.03.2020

Trade name: Paint Stripper

(Contd. of page 4)

DNEL akut inhalativ (systemisch), Verbraucher: 9,5 mg/m³ DNEL Langzeit inhalativ (lokal), Verbraucher: 3 mg/m³ DNEL Langzeit inhalativ (systemisch), Verbraucher: 3 mg/m³

N-n-Butylpyrrolidon

EG-Nr. 222-437-8 / CAS-Nr. 3470-98-2

DNEL Langzeit dermal (systemisch), Arbeitnehmer: 10 mg/kg DNEL Langzeit inhalativ (systemisch), Arbeitnehmer: 24,1 mg/m³

DNEL Langzeit oral (wiederholt), Verbraucher: 2,5 mg/kg
DNEL Langzeit dermal (systemisch), Verbraucher: 5 mg/kg
DNEL Langzeit inhalativ (systemisch), Verbraucher: 17,5 mg/m³

**PNECs** Ameisensäure

INDEX-Nr. 607-001-00-0 / EG-Nr. 200-579-1 / CAS-Nr. 64-18-6

PNEC Gewässer, Süßwasser: 2 mg/l PNEC Gewässer, Meerwasser: 0,2 mg/l

PNEC Gewässer, periodische Freisetzung: 1 mg/l

PNEC Sediment, Süßwasser: 13,4 mg/kg PNEC Sediment, Meerwasser: 1,34 mg/kg

PNEC, Boden: 1,5 mg/kg

PNEC Kläranlage (STP): 7,2 mg/l

N-n-Butylpyrrolidon

EG-Nr. 222-437-8 / CAS-Nr. 3470-98-2 PNEC Gewässer, Süßwasser: 4 mg/l PNEC Gewässer, Meerwasser: 0,4 mg/l

PNEC Gewässer, periodische Freisetzung: 1 mg/l

PNEC Sediment, Süßwasser: 29,6 mg/kg PNEC Sediment, Meerwasser: 2,96 mg/kg

PNEC, Boden: 3,57 mg/kg

PNEC Kläranlage (STP): 30,62 mg/l

**Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and

hygienic measures: Keep away from foodstuffs, beverages and feed.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

**Respiratory protection:** Use a properly fitted, air-purifying or air-fed repirator complying with an

approved standard if a risk assessment indicates this is necessary.

Not necessary if room is well-ventilated.

(Contd. on page 6)



Printing date 27.03.2020 Version number 2.1 Revision: 27.03.2020

Trade name: Paint Stripper

(Contd. of page 5)

**Protection of hands:** Protective gloves

The glove material has to be impermeable and resistant to the product/ the

substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates

of diffusion and the degradation

Material of gloves The selection of the suitable gloves does not only depend on the material, but

also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be

checked prior to the application.

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

For the permanent contact gloves made of the following

materials are suitable:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture the penetration time has to be at least 480 minutes

(Permeation according to EN 374 Part 3: Level 6).

**Eye protection:** If risk of splashing:

Tightly sealed goggles

**Body protection:** Protective work clothing

#### SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

**General Information** 

Appearance:

Form: Pasty
Colour: Beige
Odour: Specific type
Odour threshold: Not determined.

pH-value at 20 °C: 3-4 /1.0 Gew-% (Methode: pH-Elektrode)

Change in condition

**Melting point/freezing point:** Undetermined. **Initial boiling point and boiling range:** not applicable

Flash point: 100 °C (Methode: Pensky-Martens)

Flammability (solid, gas): Not determined.

**Decomposition temperature:** Not determined.

**Auto-ignition temperature:** Product is not selfigniting.

(Contd. on page 7)



Printing date 27.03.2020 Version number 2.1 Revision: 27.03.2020

Trade name: Paint Stripper

	(Contd. of page	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	0.95 Vol % (berechnet)	
Upper:	47.6 Vol % (berechnet)	
Vapour pressure at 20 °C:	0.1 hPa	
Density at 20 °C:	1.09 g/cm³ (DIN 51757)	
Relative density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Partly soluble.	
Partition coefficient: n-octanol/water:	see section 12	
Viscosity:		
Dynamic at 20 °C:	10,000 mPas	
Kinematic:	Not determined.	
9.2 Other information	<b>Other information</b> No further relevant information available.	

### SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

10.2 Chemical stability Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous

reactionsReactions with acids and strong oxidizing agents.10.4 Conditions to avoidKeep away from sources of ignition - No smoking.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous

decomposition products: No hazardous decomposition products when stored and handled correctly.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Acute toxicity Harmful if swallowed.

LD/LC50 values relevant for classification:			
3470-98-	2 1-butylp	pyrrolidin-2-one	
Oral	LD50	>300-<2,000 mg/kg (rat)	
Dermal	LD50	>2.000 mg/kg (rat)	

(Contd. on page 8)



Printing date 27.03.2020 Version number 2.1 Revision: 27.03.2020

Trade name: Paint Stripper

(Contd. of page 7)

Inhalative LC50 / 4h >5.1 mg/l (rat)

64-18-6 formic acid

Oral LD50 1,100 mg/kg (rat)

Primary irritant effect:

**Skin corrosion/irritation** Causes skin irritation. **Serious eye damage/irritation** Causes serious eye irritation.

Respiratory or skin

**sensitisation** Based on available data, the classification criteria are not met.

**Experience with humans:** Prolonged and repeated contact with the product leads to fat loss of the skin

and can cause non-allergic contact skin damage (contact dermatitis) and / or

pollutant absorption.

Splashes can cause eye irritation and reversible damage.

This product contains neither chlorinated nor aromatic hydrocarbons. Nevertheless, the usual precautionary measures are to be taken when

handling organic solvents.

Attention! Excessive influence, e.g. poor indoor ventilation can cause blurred

vision. This is reversible when fresh air is supplied.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicityBased on available data, the classification criteria are not met.CarcinogenicityBased on available data, the classification criteria are not met.Reproductive toxicityBased on available data, the classification criteria are not met.STOT-single exposureBased on available data, the classification criteria are not met.STOT-repeated exposureBased on available data, the classification criteria are not met.Aspiration hazardBased on available data, the classification criteria are not met.

#### SECTION 12: Ecological information

#### 12.1 Toxicity

Aquatic toxicity:	
-------------------	--

### 3470-98-2 1-butylpyrrolidin-2-one

EC50 / 48h | 100 mg/l (daphnia) EC50/ 72h | 130 mg/l (algae) LC50 / 96h | >100 mg/l (fish)

12.2 Persistence and

degradability Ameisensäure

Abbaubarkeit: 100 % (9 d)

Leicht biologisch abbaubar (nach OECD-Kriterien)

12.3 Bioaccumulative

potential Ameisensäure

Verteilungskoeffizient n-Octanol/Wasser: -1,9

N-n-Butylpyrrolidon

Verteilungskoeffizient n-Octanol/Wasser: 1,265

(Contd. on page 9)



Printing date 27.03.2020 Version number 2.1 Revision: 27.03.2020

Trade name: Paint Stripper

(Contd. of page 8)

12.4 Mobility in soil

No further relevant information available.

Ecotoxical effects:

Behaviour in sewage processing plants:

3470-98-2 1-butylpyrrolidin-2-one

EC10 100 mg/l (daphnia)

82 mg/l (fish)

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly

hazardous for water

12.5 Results of PBT and vPvB assessment

**PBT:** The substances in the mixture do not meet the PBT / vPvB criteria according

to REACH, Annex XIII.

*vPvB:* Not applicable.

**12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

**Recommendation** Must not be disposed together with household garbage. Do not allow product

to reach sewage system.

European waste catalogue

20 01 29\* | detergents containing hazardous substances

15 01 10\* packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

Recommended cleansing

agents: Water, if necessary together with cleansing agents.

#### **SECTION 14: Transport information**

14.1 UN-Number

ADR, IMDG, IATA Not applicable

14.2 UN proper shipping name

ADR, IMDG, IATA Not applicable

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class Not applicable

(Contd. on page 10)



Printing date 27.03.2020 Version number 2.1 Revision: 27.03.2020

Trade name: Paint Stripper

(Contd. of page 9)

		(
14.4 Packing group		
ADR, IMDG, IATA	Not applicable	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Annex II of		
Marpol and the IBC Code	Not applicable.	
UN "Model Regulation":	Not applicable	

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU
Named dangerous

substances - ANNEX I

None of the ingredients is listed.

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases** Irritating to eyes and skin.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

**Department issuing SDS:** product safety department

Contact: Hr. Dr. Starp

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 11)



Printing date 27.03.2020 Version number 2.1 Revision: 27.03.2020

Trade name: Paint Stripper

(Contd. of page 10)

Acute Tox. 4: Acute toxicity - oral – Category 4
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

\* Data compared to the previous version altered.

GB